

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## ACURA

Year	Description	Lubricant
<b>CL</b>		
03 - 01	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99 - 97	All Eng. - 26.00 Oz. R-134a; 8.45 Oz. PAG-46	59007
<b>ILX</b>		
19 - 16	4 Cyl 2.4L Eng. - 19.20 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
19 - 16	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 15.00 Oz. R-134a	59007
15 - 14	4 Cyl 2.0L Eng. - 14.40 Oz. R-134a; 2.50 Oz. PAG-46	59007
15 - 14	4 Cyl 2.4L Eng. - 14.40 Oz. R-134a; 2.50 Oz. PAG-46	59007
14	4 Cyl 1.5L Eng. - HYBRID; 14.40 Oz. R-134a; 4.30 Oz. POE Oil	59889
13	4 Cyl 1.5L Eng. - HYBRID; 15.00 Oz. R-134a; 8.10 Oz. Hybrid Oil	59889
13	4 Cyl 2.0L Eng. - 14.10-15.90 Oz. R-134a; 6.90 Oz. PAG-46	59007
13	4 Cyl 2.4L Eng. - 14.10-15.90 Oz. R-134a; 6.90 Oz. PAG-46	59007
<b>INTEGRA</b>		
01 - 94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93 - 89	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 33.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>LEGEND</b>		
95 - 94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
92 - 91	All Eng. - 6.50 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 30.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 33.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MDX</b>		
19 - 17	6 Cyl 3.0L Eng. - HYBRID, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
18 - 15	6 Cyl 3.5L Eng. - 4.50 Oz. PAG-46; 22.40 Oz. R-134a	59007
14	6 Cyl 3.5L Eng. - 23.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
13	6 Cyl 3.7L Eng. - 23.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
12 - 10	6 Cyl 3.7L Eng. - w/ Rear AC; 22.00 Oz. R-134a; 8.60 Oz. PAG-46	59007
12 - 10	6 Cyl 3.7L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 7.60 Oz. PAG-46	59007
09 - 07	All Eng. - w/ Rear AC; 22.00 Oz. R-134a; 8.60 Oz. PAG-46	59007
09 - 07	All Eng. - w/o Rear AC; 22.00 Oz. R-134a; 7.60 Oz. PAG-46	59007
06 - 02	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 27.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
<b>NSX</b>		
05 - 97	All Eng. - 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
96 - 93	All Eng. - 30.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
92 - 91	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>RDX</b>		
18	6 Cyl 3.5L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 13	6 Cyl 3.5L Eng. - 16.80 Oz. R-134a; 2.30 Oz. PAG-46	59007
12 - 09	4 Cyl 2.3L Eng. - w/ Rear AC; 17.60 Oz. R-134a; 6.50 Oz. PAG-46	59007
12 - 09	4 Cyl 2.3L Eng. - w/o Rear AC; 15.90 Oz. R-134a; 6.50 Oz. PAG-46	59007
08 - 07	All Eng. - w/ Rear AC; 17.60 Oz. R-134a; 6.50 Oz. PAG-46	59007
08 - 07	All Eng. - w/o Rear AC; 15.90 Oz. R-134a; 6.50 Oz. PAG-46	59007
<b>RL</b>		
12 - 10	6 Cyl 3.7L Eng. - 15.80-17.60 Oz. R-134a; 8.00-8.50 Oz. PAG-46	59007
09 - 06	All Eng. - 7.00 Oz. PAG-46; 17.50 Oz. R-134a	59007
05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03 - 02	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
01 - 96	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>RSX</b>		
06	All Eng. - 17.60-19.40 Oz. R-134a; 7.40-8.10 Oz. PAG-46	59007
05 - 02	All Eng. - 18.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
<b>SLX</b>		
99 - 98	All Eng. - w/ Denso Compressor; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99 - 98	All Eng. - w/ OE Harrison Compressor; 21.00 Oz. R-134a; 5.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## ACURA

Year	Description	Lubricant
------	-------------	-----------

SLX		
97 - 96	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

TL		
14	6 Cyl 3.5L Eng. - 19.20 Oz. R-134a; 2.30 Oz. PAG-46	59007
14	6 Cyl 3.7L Eng. - 19.20 Oz. R-134a; 2.30 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - 20.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
13	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
12 - 10	6 Cyl 3.5L Eng. - 17.60-19.40 Oz. R-134a; 5.81 Oz. PAG-46	59007
12 - 10	6 Cyl 3.7L Eng. - 17.60-19.40 Oz. R-134a; 6.15 Oz. PAG-46	59007
09	All Eng. - 17.60-19.40 Oz. R-134a; 6.15 Oz. PAG-46	59007
08 - 04	All Eng. - 7.00 Oz. PAG-46; 17.60-19.40 Oz. R-134a	59007
03 - 99	All Eng. - 21.00-23.00 Oz. R-134a; 8.80-9.40 Oz. PAG-46	59007
98 - 95	All Eng. - 26.50 Oz. R-134a; 5.33 Oz. PAG-46	59007

TSX		
14	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; 2.60 Oz. PAG-46	59007
14 - 13	4 Cyl 2.4L Eng. - 17.60 Oz. R-134a; 2.60 Oz. PAG-46	59007
12 - 11	6 Cyl 3.5L Eng. - 15.90-17.60 Oz. R-134a; 6.11 Oz. PAG-46	59007
12 - 10	4 Cyl 2.4L Eng. - 15.90-17.60 Oz. R-134a; 6.42-6.83 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 15.90-17.60 Oz. R-134a; 6.42-6.83 Oz. PAG-46	59007
09	All Eng. - 15.80-17.60 Oz. R-134a; 6.50-6.90 Oz. PAG-46	59007
08	4 Cyl 2.4L Eng. - 17.60-19.40 Oz. R-134a; 8.11 Oz. PAG-46	59007
07 - 04	All Eng. - 17.60-19.40 Oz. R-134a; 8.11 Oz. PAG-46	59007

VIGOR		
94 - 92	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

ZDX		
13 - 12	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 3.45 Oz. PAG-46	59007
11	6 Cyl 3.7L Eng. - 17.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
10	6 Cyl 3.7L Eng. - 17.00 Oz. R-134a; 3.40-6.00 Oz. PAG-46	59007

## ALFA ROMEO

Year	Description	Lubricant
------	-------------	-----------

GIULIA		
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
18	6 Cyl 2.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234

STELVIO		
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
18	6 Cyl 2.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234

## AMERICAN MOTORS

Year	Description	Lubricant
------	-------------	-----------

AMX		
80 - 79	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

CONCORD		
83 - 80	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

EAGLE		
88 - 84	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

SPIRIT		
83 - 79	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## AUDI

Year	Description	Lubricant
<b>100 SERIES</b>		
94 - 93	All Eng. - 8.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
93	All Eng. - 8.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - 10.00 Oz. Mineral Oil; 38.00 Oz. R-12	59000 <sup>(1)</sup>
<b>200 SERIES</b>		
91 - 89	All Eng. - 10.00 Oz. Mineral Oil; 38.00 Oz. R-12	59000 <sup>(1)</sup>
<b>5000 SERIES</b>		
88 - 87	5 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 84	5 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>80 SERIES</b>		
92 - 88	All Eng. - 10.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
<b>90 SERIES</b>		
95 - 93	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
91 - 88	All Eng. - 10.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
<b>A3 SERIES</b>		
19 - 18	4 Cyl 2.0L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18	4 Cyl 2.0L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17	4 Cyl 1.4L Eng. - w/ Denso or Delphi Compressor; 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
17 - 15	4 Cyl 2.0L Eng. - w/ Denso or Delphi Compressor; 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
16 - 15	4 Cyl 1.8L Eng. - w/ Denso or Delphi Compressor; 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 08	6 Cyl 3.2L Eng. - 19.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07 - 06	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
07 - 06	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
07 - 06	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.72 Oz. PAG-46	59007
07 - 06	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
07 - 06	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
07 - 06	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 4.72 Oz. PAG-46	59007
<b>A4 SERIES</b>		
19 - 18	4 Cyl 2.0L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
19 - 18	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 20.00 Oz. R-134a	59007
17	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
16 - 14	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13 - 09	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
12	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
09	6 Cyl 3.2L Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08 - 06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	All Eng. - 20.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
03 - 02	All Eng. - 9.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
01 - 00	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99 - 96	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>A5 SERIES</b>		
19 - 18	4 Cyl 2.0L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
19 - 18	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 20.00 Oz. R-134a	59007
17	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
16 - 15	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
14	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
12 - 10	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10 - 08	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>A6 SERIES</b>		
19	4 Cyl 2.0L Eng. - HYBRID, 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
19	6 Cyl 3.0L Eng. - HYBRID, 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## AUDI

Year	Description	Lubricant
<b>A6 SERIES</b>		
18	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 20.16 Oz. R-134a	59007
18	6 Cyl 3.0L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 20.16 Oz. R-134a	59007
17 - 16	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
17 - 15	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
15 - 14	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; 4.4 Oz. PAG-46	59007
14	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.4 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 3.70-4.30 Oz. PAG-46	59007
13 - 12	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
11	8 Cyl 4.2L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46, Single Evaporator	59007
11	8 Cyl 4.2L Eng. - 33.00 Oz. R-134a; 4.40 Oz. PAG-46, Dual Evaporator	59007
11 - 09	6 Cyl 3.0L Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
11 - 08	6 Cyl 3.2L Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
10	8 Cyl 4.2L Eng. - 18.40 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	6 Cyl 2.8L Eng. - 19.00 Oz. R-134a; 4.38 Oz. PAG-46	59007
09 - 08	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
07 - 06	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05	All Eng. - 24.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
04 - 03	All Eng. - 30.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
02 - 01	All Eng. - 24.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
00 - 98	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
97 - 96	All Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
95	All Eng. - 8.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>A7 SERIES</b>		
19 - 18	6 Cyl 3.0L Eng. - HYBRID, 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 14	6 Cyl 3.0L Eng. - 4.70 Oz. PAG-46; 20.16 Oz. R-134a	59007
13 - 12	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 3.70-4.30 Oz. PAG-46	59007
<b>A8 SERIES</b>		
19	6 Cyl 3.0L Eng. - 24.00 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
19	8 Cyl 4.0L Eng. - 26.40 Oz. R-134a; 4.10 Oz. PAG-46	59007
18	6 Cyl 3.0L Eng. - 26.40 Oz. R-134a; 4.10 Oz. PAG-46	59007
18	8 Cyl 4.0L Eng. - 24.00 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
17 - 13	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46, Single Evaporator	59007
17 - 13	6 Cyl 3.0L Eng. - 34.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46, Dual Evaporator	59007
17 - 13	8 Cyl 4.0L Eng. - 28.00 Oz. R-134a; 4.10 Oz. PAG-46, Single Evaporator	59007
17 - 13	8 Cyl 4.0L Eng. - 33.00 Oz. R-134a; 4.40 Oz. PAG-46, Dual Evaporator	59007
12	12 Cyl 6.3L Eng. - 28.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46, Single Evaporator	59007
12	12 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.10-4.70 Oz. PAG-46, Dual Evaporator	59007
12 - 10	8 Cyl 4.2L Eng. - 27.00 Oz. R-134a; 4.40 Oz. PAG-46, Single Evaporator	59007
12 - 10	8 Cyl 4.2L Eng. - 33.00 Oz. R-134a; 4.40 Oz. PAG-46, Dual Evaporator	59007
09 - 08	8 Cyl 4.2L Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09 - 07	12 Cyl 6.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - 21.00 Oz. R-134a; 5.06 Oz. PAG-46	59007
06	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03 - 00	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46; w/ Yellow Restrictor	59007
03 - 00	All Eng. - 8.50 Oz. PAG-46; 25.00 Oz. R-134a; w/o Restrictor	59007
99 - 97	All Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>ALLROAD QUATTRO</b>		
16 - 14	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 22.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46	59007
05	All Eng. - 23.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
04 - 03	All Eng. - 30.00 Oz. R-134a; 9.25 Oz. PAG-46	59007
02 - 01	All Eng. - 24.50 Oz. R-134a; 9.25 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## AUDI

Year	Description	Lubricant
<b>CABRIOLET</b>		
98 - 94	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>COUPE QUATTRO</b>		
91 - 90	All Eng. - 10.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
<b>Q2 / Q2 QUATTRO</b>		
19	4 Cyl 2.0L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
<b>Q3 / Q3 QUATTRO</b>		
19	4 Cyl 2.0L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
16	4 Cyl 2.0L Eng. - Excl. Hybrid, 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - Excl. Hybrid, 21.12 Oz. R-134a; 4.60 Oz. PAG-46	59007
14 - 12	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
<b>Q5</b>		
19	4 Cyl 2.0L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
18	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
18 - 17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front and Rear	59234
17	4 Cyl 2.0L Eng. - 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	6 Cyl 3.0L Eng. - 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	4 Cyl 2.0L Eng. - Excl. Hybrid, 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - Excl. Hybrid, 21.12 Oz. R-134a; 4.60 Oz. PAG-46	59007
15	6 Cyl 3.0L Eng. - Gas, 21.12 Oz. R-134a; 4.60 Oz. PAG-46, Front	59007
15 - 13	6 Cyl 3.0L Eng. - Gas, 4.70 Oz. PAG-46; 36.80 Oz. R-134a, Front and Rear	59007
15 - 09	6 Cyl 3.0L Eng. - Diesel, 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46, Front AC	59007
15 - 09	6 Cyl 3.0L Eng. - Diesel, 4.70 Oz. PAG-46; 36.80 Oz. R-134a, Front and Rear	59007
14	6 Cyl 3.0L Eng. - Gas, 5.00 Oz. PAG-46; 21.12 Oz. R-134a, Front	59007
14 - 12	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
13	6 Cyl 3.0L Eng. - Gas, 21.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46, Front	59007
12	6 Cyl 3.2L Eng. - 5.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
11	4 Cyl 2.0L Eng. - 21.12 Oz. R-134a; 4.40 Oz. PAG-46	59007
10	6 Cyl 3.2L Eng. - 21.12 Oz. R-134a; 4.40 Oz. PAG-46	59007
<b>Q7</b>		
19	4 Cyl 2.0L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
18	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front	59234
18 - 17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity, Front and Rear	59234
17 - 16	6 Cyl 3.0L Eng. - 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	4 Cyl 2.0L Eng. - Excl. Hybrid, 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - Gas, 21.12 Oz. R-134a; 4.60 Oz. PAG-46, Front	59007
15 - 12	6 Cyl 3.0L Eng. - Gas, 4.70 Oz. PAG-46; 36.80 Oz. R-134a, Front and Rear	59007
15 - 09	6 Cyl 3.0L Eng. - Diesel, 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46, Front AC	59007
15 - 09	6 Cyl 3.0L Eng. - Diesel, 4.70 Oz. PAG-46; 36.80 Oz. R-134a, Front and Rear	59007
14	6 Cyl 3.0L Eng. - Gas, 5.00 Oz. PAG-46; 21.12 Oz. R-134a, Front	59007
14	8 Cyl 4.1L Eng. - 5.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
13	6 Cyl 3.0L Eng. - Gas, 21.00 Oz. R-134a; 4.70-5.30 Oz. PAG-46, Front	59007
13 - 12	8 Cyl 4.1L Eng. - 21.00 Oz. R-134a; 4.70 - 5.30 Oz. PAG-46	59007
12	6 Cyl 3.0L Eng. - Gas, 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46, Front AC	59007
11	8 Cyl 4.1L Eng. - 21.12 Oz. R-134a; 4.40 Oz. PAG-46	59007
10 - 09	6 Cyl 3.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
09	8 Cyl 4.2L Eng. - 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46, Front	59007
09	8 Cyl 4.2L Eng. - 4.70 Oz. PAG-46; 36.80 Oz. R-134a, Front and Rear	59007
08	6 Cyl 3.6L Eng. - w/ Denso Compressor; 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
08	8 Cyl 4.2L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
07	6 Cyl 3.6L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
07	6 Cyl 3.6L Eng. - w/ Rear AC; 37.00 Oz. R-134a; 8.28 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - w/ Rear AC; 37.00 Oz. R-134a; 8.28 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - w/o Rear AC; 19.00 Oz. R-134a; 4.90 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## AUDI

Year	Description	Lubricant
<b>Q8</b>		
19	6 Cyl 3.0L Eng. - HYBRID, 24.00 Oz. R-1234yf; 4.00 Oz. PAG Oil, Front	59234
<b>R8</b>		
18 - 17	10 Cyl 5.2L Eng. - 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
18 - 17	10 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
15 - 14	10 Cyl 5.2L Eng. - 6.70 Oz. PAG-46; 23.20 Oz. R-134a	59007
14	8 Cyl 4.2L Eng. - 6.70 Oz. PAG-46; 23.20 Oz. R-134a	59007
12 - 10	10 Cyl 5.2L Eng. - 22.00 Oz. R-134a; 4.80-5.40 Oz. PAG-46	59007
12 - 10	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 4.80-5.40 Oz. PAG-46	59007
09 - 08	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>RS4</b>		
08	8 Cyl 4.2L Eng. - 15.52 Oz. R-134a; 4.30 Oz. PAG-46	59007
07	All Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>RS6</b>		
04 - 03	8 Cyl 4.2L Eng. - 19.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>S3</b>		
04	All Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
03 - 01	All Eng. - 25.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
<b>S4</b>		
14	6 Cyl 3.0L Eng. - 19.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
13 - 10	6 Cyl 3.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 09	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - 17.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
06 - 05	8 Cyl 4.2L Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
04	All Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
03 - 01	All Eng. - 25.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
00	6 Cyl 2.7L Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
94 - 93	All Eng. - 8.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
93	All Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	All Eng. - 10.00 Oz. Mineral Oil; 38.00 Oz. R-12	59000 <sup>(1)</sup>
<b>S5</b>		
14	6 Cyl 3.0L Eng. - 19.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
13 - 10	6 Cyl 3.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12 - 09	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08	8 Cyl 4.2L Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
<b>S6</b>		
14	8 Cyl 4.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	8 Cyl 4.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 09	10 Cyl 5.2L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08	10 Cyl 5.2L Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	10 Cyl 5.2L Eng. - 17.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
04	All Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
03 - 01	All Eng. - 25.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
96 - 95	All Eng. - 8.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>S7</b>		
14	8 Cyl 4.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	8 Cyl 4.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>S8</b>		
14	8 Cyl 4.0L Eng. - 5.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	8 Cyl 4.0L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 09	10 Cyl 5.2L Eng. - 22.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08	10 Cyl 5.2L Eng. - 22.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	10 Cyl 5.2L Eng. - 17.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
03 - 01	All Eng. - 25.00 Oz. R-134a; 6.07 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## AUDI

Year	Description	Lubricant
<b>TT SERIES</b>		
16 - 14	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
14	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
14	5 Cyl 2.5L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13	5 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13	5 Cyl 2.5L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - w/ Sanden Compressor; 18.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12	5 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
12	5 Cyl 2.5L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46	59007
12 - 11	4 Cyl 1.8L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
11	5 Cyl 2.5L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
11 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
09 - 08	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09 - 08	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
09 - 08	6 Cyl 3.2L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
06 - 02	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01 - 00	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>V8 QUATTRO</b>		
94 - 93	All Eng. - 30.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
92 - 90	All Eng. - 10.00 Oz. Mineral Oil; 39.00 Oz. R-12	59000 <sup>(1)</sup>

## BMW

Year	Description	Lubricant
<b>128 SERIES</b>		
13 - 12	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 21.87 Oz. R-134a; 6.08 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 20.81 Oz. R-134a; 6.08 Oz. PAG-46	59007
09	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
08	6 Cyl 3.0L Eng. - 20.81 Oz. R-134a; 6.08 Oz. PAG-46	59007
<b>135 SERIES</b>		
14	6 Cyl 3.0L Eng. - 20.81 Oz. R-134a; 6.34 Oz. PAG-46	59007
13	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12 - 11	6 Cyl 3.0L Eng. - 21.87 Oz. R-134a; 6.34 Oz. PAG-46	59007
10 - 08	6 Cyl 3.0L Eng. - 20.81 Oz. R-134a; 6.34 Oz. PAG-46	59007
<b>228i</b>		
16 - 14	4 Cyl 2.0L Eng. - 228i, 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
<b>228i xDrive</b>		
16 - 15	4 Cyl 2.0L Eng. - 228i, 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
<b>318 SERIES</b>		
99 - 93	All Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
99 - 93	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 42.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/ Behr System; 42.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85 - 84	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>320 SERIES</b>		
16 - 14	4 Cyl 2.0L Eng. - 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
05 - 01	6 Cyl 2.2L Eng. - 26.10+/-0.88 Oz. R-134a; 5.41 Oz. PAG-46	59007
83 - 80	4 Cyl 1.8L Eng. - 45.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>323 SERIES</b>		
00	All Eng. - 29.50 Oz. R-134a; 5.50 Oz. PAG-100	59002
99 - 98	All Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>323 SERIES</b>		
99 - 98	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
<b>325 SERIES</b>		
06 - 01	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
95 - 93	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
93	All Eng. - 6.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 42.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/ Behr System; 42.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 10.00 Oz. Mineral Oil; 34.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Behr System; 34.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 2.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>328 SERIES</b>		
17	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
16 - 14	4 Cyl 2.0L Eng. - 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13 - 12	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
13 - 12	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11 - 07	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
00 - 96	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>330 SERIES</b>		
18	All Eng. - 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
06	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-46	59007
05 - 01	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-100	59002
<b>335 SERIES</b>		
16	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15 - 14	6 Cyl 3.0L Eng. - 6.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
13	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12	6 Cyl 3.0L Eng. - 21.87 Oz. R-134a; 6.34 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10 - 07	6 Cyl 3.0L Eng. - 20.81 Oz. R-134a; 6.34 Oz. PAG-46	59007
<b>525 SERIES</b>		
07	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
06 - 04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03 - 01	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
95 - 93	All Eng. - 6.00 Oz. PAG-100; 51.00 Oz. R-134a; Flat Tube Condenser	59002
95 - 93	All Eng. - 6.00 Oz. PAG-100; 53.00 Oz. R-134a; Round Tube Condenser	59002
93	6 Cyl 2.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
<b>528 SERIES</b>		
16 - 14	4 Cyl 2.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 12	4 Cyl 2.0L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	8 Cyl 4.4L Eng. - 28.00 Oz. R-134a; 5.40 - 6.80 Oz. PAG-46	59007
11 - 10	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 29.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
00 - 98	All Eng. - 26.40 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Denso Compressor; 26.40 Oz. R-134a; 4.90-5.90 Oz. PAG-46	59007
97	All Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
97	All Eng. - w/ Denso Compressor; 4.90-5.90 Oz. PAG-46; 43.00 Oz. R-134a	59007
82	6 Cyl 2.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 79	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>530 SERIES</b>		
07	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 6.00 Oz. PAG-100	59007
06 - 04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03 - 02	6 Cyl 3.0L Eng. - 26.40 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
01	6 Cyl 3.0L Eng. - 27.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>530 SERIES</b>		
01	6 Cyl 3.0L Eng. - w/ Denso Compressor; 27.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46	59007
95 - 94	All Eng. - 6.00 Oz. PAG-100; 51.00 Oz. R-134a; Flat Tube Condenser	59002
95 - 94	All Eng. - 6.00 Oz. PAG-100; 53.00 Oz. R-134a; Round Tube Condenser	59002
<b>533 SERIES</b>		
84 - 83	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>535 SERIES</b>		
17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
16 - 14	6 Cyl 3.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 29.92 Oz. R-134a	59007
13 - 12	6 Cyl 3.0L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 5.40-6.80 Oz. PAG-46; 25.00 Oz. R-134a	59007
11	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 5.40 - 6.80 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
93	All Eng. - 6.00 Oz. PAG-100; 51.00 Oz. R-134a; Flat Tube Condenser	59002
93	All Eng. - 6.00 Oz. PAG-100; 53.00 Oz. R-134a; Round Tube Condenser	59002
92 - 89	All Eng. - 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
<b>540 SERIES</b>		
03 - 01	All Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
00 - 99	All Eng. - 6.00 Oz. PAG-100; 44.00 Oz. R-134a	59002
98 - 97	All Eng. - 43.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
95 - 94	All Eng. - 6.00 Oz. PAG-100; 51.00 Oz. R-134a; Flat Tube Condenser	59002
95 - 94	All Eng. - 6.00 Oz. PAG-100; 53.00 Oz. R-134a; Round Tube Condenser	59002
<b>545 SERIES</b>		
05 - 04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
<b>550 SERIES</b>		
16	8 Cyl 4.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15 - 14	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 29.92 Oz. R-134a	59007
13 - 12	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	8 Cyl 4.4L Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10	8 Cyl 4.4L Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10	8 Cyl 4.8L Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09 - 08	8 Cyl 4.8L Eng. - 29.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
07 - 06	8 Cyl 4.8L Eng. - 27.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
07 - 06	8 Cyl 4.8L Eng. - w/ Denso Compressor; 27.00 Oz. R-134a; 4.90-5.90 Oz. PAG-46	59007
<b>633 SERIES</b>		
82 - 78	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>635 SERIES</b>		
89	All Eng. - w/ Rear AC; 5.75 Oz. Mineral Oil; 63.50 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 39.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>640 SERIES</b>		
16 - 14	6 Cyl 3.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 12	6 Cyl 3.0L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>645 SERIES</b>		
05 - 04	8 Cyl 4.4L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>650 SERIES</b>		
16 - 14	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
12	8 Cyl 4.4L Eng. - 28.48 Oz. R-134a; 6.34 Oz. PAG-46	59007
11 - 06	8 Cyl 4.8L Eng. - 28.48 Oz. R-134a; 6.34 Oz. PAG-46	59007
<b>733 SERIES</b>		
84 - 78	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>735 SERIES</b>		
92	6 Cyl 3.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 73.00 Oz. R-12, To 3/92	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 6.00 Oz. PAG-100; 60.00 Oz. R-134a, 4/92-12/92	59002
92	All Eng. - w/ Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 73.00 Oz. R-12, To 3/92	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12, To 3/92	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 55.00 Oz. R-134a; 6.00 Oz. PAG-46, 4/92-12/92	59007
92	All Eng. - w/o Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12, To 3/92	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 73.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 73.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/o Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 85	6 Cyl 3.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>740 SERIES</b>		
17	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
17 - 14	6 Cyl 3.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13	12 Cyl 6.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13	6 Cyl 3.0L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 29.92 Oz. R-134a	59007
01	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
00 - 99	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
98 - 95	All Eng. - 42.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
98 - 95	All Eng. - w/ Denso Compressor; 42.50 Oz. R-134a; 5.50 Oz. PAG-46	59007
94 - 93	All Eng. - w/ Rear AC; 6.00 Oz. PAG-100; 60.00 Oz. R-134a	59002
94 - 93	All Eng. - w/o Rear AC; 55.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>745 SERIES</b>		
05 - 04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
03 - 02	8 Cyl 4.4L Eng. - 28.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
<b>750 SERIES</b>		
15 - 14	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 12	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11 - 10	All Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	8 Cyl 4.8L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	8 Cyl 4.8L Eng. - w/ Rear AC; 41.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 06	8 Cyl 4.8L Eng. - w/ Rear AC; 37.87 Oz. R-134a; 8.46 Oz. PAG-46	59007
08 - 06	8 Cyl 4.8L Eng. - w/o Rear AC; 28.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
00 - 99	All Eng. - 43.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
98 - 95	All Eng. - w/ Denso Compressor; w/o Rear AC; 42.50 Oz. R-134a; 5.50 Oz. PAG-46	59007
98 - 95	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 6.00 Oz. PAG-100	59002
98 - 95	All Eng. - w/o Rear AC; 42.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
94 - 93	All Eng. - w/ Denso Compressor; w/o Rear AC; 5.50 Oz. PAG-46; 55.00 Oz. R-134a	59007
94 - 93	All Eng. - w/ Rear AC; 6.00 Oz. PAG-100; 60.00 Oz. R-134a	59002
94 - 93	All Eng. - w/o Rear AC; 55.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 73.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 73.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/o Rear AC; w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
<b>760 SERIES</b>		
15 - 14	12 Cyl 6.0L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 10	12 Cyl 6.0L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 07	12 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
08 - 07	12 Cyl 6.0L Eng. - w/o Rear AC; 29.00 Oz. R-134a; 6.35 Oz. PAG-46	59007
06 - 04	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
<b>840 SERIES</b>		
97 - 94	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
97 - 94	All Eng. - w/ Denso Compressor; 5.50 Oz. PAG-46; 55.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>850 SERIES</b>		
97 - 93	All Eng. - 55.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
97 - 93	All Eng. - w/ Denso Compressor; 5.50 Oz. PAG-46; 55.00 Oz. R-134a	59007
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/ Behr System; 6.75 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ACTIVEHYBRID 3</b>		
15 - 14	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
<b>ACTIVEHYBRID 5</b>		
16 - 14	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
12	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
<b>L6</b>		
87	6 Cyl 3.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>L7</b>		
87 - 86	6 Cyl 3.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>M135I SERIES</b>		
16 - 14	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M140I SERIES</b>		
17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M2</b>		
17 - 16	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M235I SERIES</b>		
16 - 14	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M240I SERIES</b>		
17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M3</b>		
17 - 15	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 4.0L Eng. - 21.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
12	8 Cyl 4.0L Eng. - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
11	8 Cyl 4.0L Eng. - 21.00 Oz. R-134a; 4.70-5.40 PAG-46	59007
10	8 Cyl 4.0L Eng. - 21.00 Oz. R-134a; 4.07-5.40 Oz. PAG-46	59007
09 - 08	8 Cyl 4.0L Eng. - 29.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
06	6 Cyl 3.2L Eng. - 26.10 Oz. R-134a; 5.40+/-0.30 Oz. PAG-46	59007
05 - 02	6 Cyl 3.2L Eng. - 26.00 Oz. R-134a; 5.10-5.70 Oz. PAG-46	59007
01	6 Cyl 3.2L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
99 - 95	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-100; Flat Tube Condenser	59002
99 - 95	All Eng. - 36.00 Oz. R-134a; 5.00 Oz. PAG-100; Round Tube Condenser	59002
91	4 Cyl Eng. - 10.00 Oz. Mineral Oil; 31.00 Oz. R-12	59000 <sup>(1)</sup>
91	4 Cyl Eng. - w/ Behr System; 31.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 10.00 Oz. Mineral Oil; 31.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Behr System; 31.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>M4</b>		
17 - 14	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M5</b>		
17	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
16 - 14	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 12	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	10 Cyl 5.0L Eng. - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10	10 Cyl 5.0L Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09 - 08	10 Cyl 5.0L Eng. - 29.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
07	10 Cyl 5.0L Eng. - 28.57 Oz. R-134a; 6.34 Oz. PAG-46	59007
06	10 Cyl 5.0L Eng. - 28.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
03 - 02	8 Cyl 5.0L Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
03 - 01	8 Cyl 5.0L Eng. - w/ Denso Compressor; 4.90-5.90 Oz. PAG-46; 43.00 Oz. R-134a	59007
00	8 Cyl 5.0L Eng. - 33.51 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
00	8 Cyl 5.0L Eng. - 43.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>M5</b>		
00	8 Cyl 5.0L Eng. - w/ Denso Compressor; 31.74 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
99	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-100; Flat Tube Condenser	59002
99	All Eng. - 36.00 Oz. R-134a; 5.00 Oz. PAG-100; Round Tube Condenser	59002
93	All Eng. - 5.41 Oz. Mineral Oil; 51.14 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - 6.00 Oz. PAG-100; 51.00 Oz. R-134a; Flat Tube Condenser	59002
93	All Eng. - 6.00 Oz. PAG-100; 53.00 Oz. R-134a; Round Tube Condenser	59002
92	All Eng. - 6.75 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
91	6 Cyl Eng. - 6.75 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
<b>M550 SERIES</b>		
17	8 Cyl 4.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>M6 SERIES</b>		
17	8 Cyl 4.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
16 - 14	8 Cyl 4.4L Eng. - 6.00 Oz. PAG-46; 30.08 Oz. R-134a	59007
13 - 12	8 Cyl 4.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	10 Cyl 5.0L Eng. - 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10	10 Cyl 5.0L Eng. - 28.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09 - 08	10 Cyl 5.0L Eng. - 29.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
07	10 Cyl 5.0L Eng. - 28.57 Oz. R-134a; 6.34 Oz. PAG-46	59007
06	10 Cyl 5.0L Eng. - 28.00 Oz. R-134a; 6.34 Oz. PAG-46	59007
<b>X1</b>		
16	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14 - 13	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
12	6 Cyl 3.0L Eng. - 18.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10	6 Cyl 2.5L Eng. - 25.00 Oz. R-134a; 4.90 - 5.60 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
<b>X3</b>		
16	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14 - 13	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
12	6 Cyl 3.0L Eng. - 18.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
10	6 Cyl 2.5L Eng. - 25.00 Oz. R-134a; 4.90 - 5.60 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
08 - 07	6 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	6 Cyl 2.5L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	6 Cyl 3.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 04	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>X4</b>		
16	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>X5</b>		
17	8 Cyl 4.4L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>X5</b>		
16	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 14	8 Cyl 4.4L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
13 - 12	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
12	6 Cyl 3.0L Eng. - 18.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
11	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 4.90-5.60 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07	8 Cyl 4.8L Eng. - 25.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	6 Cyl 3.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	8 Cyl 4.4L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	8 Cyl 4.8L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 04	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
03 - 02	6 Cyl 3.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
03 - 02	8 Cyl 4.4L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
03 - 02	8 Cyl 4.6L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
01	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
00	8 Cyl 4.4L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>X6</b>		
17	8 Cyl 4.4L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 14	8 Cyl 4.4L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
13 - 12	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 4.40-5.10 Oz. PAG-46	59007
12	6 Cyl 3.0L Eng. - 18.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.40-6.80 Oz. PAG-46	59007
11	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 4.90-5.60 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
08	8 Cyl 4.4L Eng. - 24.70 Oz. R-134a; 5.30 Oz. PAG-46	59007
<b>Z3</b>		
02	6 Cyl 3.0L Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
02	6 Cyl 3.2L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
02 - 01	6 Cyl 2.5L Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
02 - 01	6 Cyl 2.5L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
02 - 01	6 Cyl 3.0L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
02 - 01	6 Cyl 3.2L Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
01	6 Cyl 3.2L Eng. - 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
00 - 99	All Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-100; Flat Tube Condenser	59002
00 - 99	All Eng. - 36.00 Oz. R-134a; 6.00 Oz. PAG-100; Round Tube Condenser	59002
98	4 Cyl 1.9L Eng. - 29.10 Oz. R-134a; 5.29 Oz. PAG-46	59007
98	6 Cyl 2.8L Eng. - 29.10 Oz. R-134a; 5.29 Oz. PAG-46	59007
98	6 Cyl 2.8L Eng. - w/ Denso Compressor; 29.10 Oz. R-134a; 4.23 Oz. PAG-46	59007
98	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
98 - 96	4 Cyl 1.9L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BMW

Year	Description	Lubricant
<b>Z3</b>		
97	6 Cyl 2.8L Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
97	6 Cyl 2.8L Eng. - w/ Denso Compressor; 3.30-4.70 Oz. PAG-46; 36.00 Oz. R-134a	59007
97 - 96	4 Cyl 1.9L Eng. - 36.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
<b>Z4</b>		
16 - 14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 13	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 16.00 Oz. R-134a; 5.40-6.00 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12 - 10	6 Cyl 3.0L Eng. - 20.46 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11 - 10	6 Cyl 2.5L Eng. - 20.46 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	6 Cyl 3.2L Eng. - 26.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 05	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
07 - 06	6 Cyl 3.2L Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
05 - 04	6 Cyl 2.5L Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
04	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 5.29+/-0.35 Oz. PAG-46	59007
<b>Z8</b>		
03 - 02	8 Cyl 5.0L Eng. - 25.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
00	All Eng. - 26.00 Oz. R-134a	59007

## BUICK

Year	Description	Lubricant
<b>ALLURE</b>		
10	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 20.16 Oz. R-134a	59007
10	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 20.16 Oz. R-134a	59007
09	6 Cyl 3.8L Eng. - 5.00 Oz. PAG-46; 21.60-19.20 Oz. R-134a	59007
09	8 Cyl 5.3L Eng. - 5.00 Oz. PAG-46; 21.60-19.20.00 Oz. R-134a	59007
08	8 Cyl 5.3L Eng. - 5.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
08 - 06	6 Cyl 3.8L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07 - 06	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	6 Cyl 3.6L Eng. - 35.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
05	6 Cyl 3.8L Eng. - 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>APOLLO</b>		
73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## CASCADA

18 - 16	4 Cyl 1.6L Eng. - 4.50 Oz. PAG-46; 22.08 Oz. R-134a	59007
---------	---	-------

## CENTURY SEDAN / COUPE

05	All Eng. - 9.00 Oz. PAG-150; 38.00 Oz. R-134a	59003
04 - 03	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02 - 97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96 - 94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## ELECTRA SEDAN / COUPE

90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 64	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BUICK

Year	Description	Lubricant
<b>ELECTRA SEDAN / COUPE</b>		
66 - 63	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ENCLAVE</b>		
17 - 14	6 Cyl 3.6L Eng. - 40.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - 7.80 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
12 - 10	6 Cyl 3.6L Eng. - 36.80 Oz. R-134a; 6.50 Oz. PAG-46	59007
09 - 08	All Eng. - 36.80 Oz. R-134a; 6.50 Oz. PAG-46	59007
<b>ENCORE</b>		
16 - 14	4 Cyl 1.4L Eng. - 20.06 Oz. R-134a; 3.80 Oz. PAG-46	59007
<b>ESTATE WAGON (CENTURY,ELECTRA,LESABRE,REGAL,ROADMASTER)</b>		
96 - 94	8 Cyl 5.7L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
96 - 94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93 - 92	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LACROSSE</b>		
17	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
16 - 13	4 Cyl 2.4L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
16 - 13	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12 - 11	4 Cyl 2.4L Eng. - 3.70 Oz. PAG-46; 21.00 Oz. R-134a	59007
12 - 10	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
10	4 Cyl 2.4L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
10	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
09 - 06	All Eng. - 5.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
05	All Eng. - 36.96 Oz. R-134a; 6.50 Oz. PAG-46	59007
<b>LESABRE SEDAN / COUPE</b>		
05	All Eng. - 9.00 Oz. PAG-150; 38.00 Oz. R-134a	59003
04 - 03	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02 - 98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 8.00 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
64 - 63	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LUCERNE</b>		
11	6 Cyl 3.9L Eng. - 23.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
11	8 Cyl 4.6L Eng. - 23.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
10	6 Cyl 3.9L Eng. - 21.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
10	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
09 - 06	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>PARK AVENUE</b>		
05	All Eng. - 9.00 Oz. PAG-150; 38.00 Oz. R-134a	59003
04 - 00	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99 - 97	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BUICK

Year	Description	Lubricant
<b>PARK AVENUE</b>		
95 - 94	All Eng. - w/ Denso Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>RAINIER</b>		
07 - 04	All Eng. - w/ Rear AC; 8.00 Oz. PAG-46; 42.40 Oz. R-134a	59007
07 - 04	All Eng. - w/o Rear AC; 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>REATTA</b>		
91 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>REGAL SEDAN / COUPE</b>		
17 - 14	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 20.80 Oz. R-134a	59007
17 - 11	4 Cyl 2.4L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 20.80-24.00 Oz. R-134a	59007
12 - 11	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 21.00 Oz. R-134a	59007
04 - 97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 85	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RENDEZVOUS</b>		
07 - 02	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>RIVIERA</b>		
99 - 97	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96 - 95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 89	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ROADMASTER</b>		
96 - 94	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96 - 94	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 6.00 Oz. Mineral Oil; 50.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SKYHAWK</b>		
89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SKYLARK</b>		
98 - 95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - 42.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 86	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## BUICK

Year	Description	Lubricant
<b>SKYLARK</b>		
88 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SOMERSET</b>		
87 - 85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TERRAZA</b>		
07	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
07 - 06	All Eng. - w/ Rear AC; 31.66 Oz. R-134a; 7.77 Oz. PAG-46	59007
06	All Eng. - w/o Rear AC; 7.10 Oz. PAG-46; 22.88 Oz. R-134a	59007
05	All Eng. - w/ Rear AC; 35.60 Oz. R-134a; 7.77 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 7.10 Oz. PAG-46; 26.88 Oz. R-134a	59007
<b>VERANO</b>		
17 - 14	4 Cyl 2.0L Eng. - 22.88 Oz. R-134a; 4.20 Oz. PAG-46	59007
17 - 14	4 Cyl 2.4L Eng. - 22.88 Oz. R-134a; 4.20 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 4.23 Oz. PAG-46; 22.73 Oz. R-134a	59007
13	4 Cyl 2.4L Eng. - 4.23 Oz. PAG-46; 22.73 Oz. R-134a	59007
12	4 Cyl 2.4L Eng. - 3.70 Oz. PAG-46; 20.80-24.00 Oz. R-134a	59007

## CADILLAC

Year	Description	Lubricant
<b>ALLANTE</b>		
93 - 87	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ATS</b>		
17	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
16 - 14	4 Cyl 2.0L Eng. - 4.10 Oz. PAG-46; 19.20 Oz. R-134a	59007
16 - 14	4 Cyl 2.5L Eng. - 4.10 Oz. PAG-46; 19.20 Oz. R-134a	59007
<b>CALAIS</b>		
73 - 70	8 Cyl 8.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 7.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CATERA</b>		
01 - 99	All Eng. - 8.00 Oz. PAG-150; 41.00 Oz. R-134a	59003
98 - 97	All Eng. - 9.00 Oz. PAG-150; 41.50 Oz. R-134a	59003
<b>CIMARRON</b>		
88 - 86	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CT6</b>		
18 - 16	4 Cyl 2.0L Eng. - 20.80 Oz. R-1234yf; w/ CJ2 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	4 Cyl 2.0L Eng. - 38.40 Oz. R-1234yf; w/ C24 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	4 Cyl 2.0L Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ C24 Compressor	59007
18 - 16	6 Cyl 3.0L Eng. - 20.80 Oz. R-1234yf; w/ CJ2 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	6 Cyl 3.0L Eng. - 38.40 Oz. R-1234yf; w/ C24 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	6 Cyl 3.0L Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ C24 Compressor	59007
18 - 16	6 Cyl 3.6L Eng. - 20.80 Oz. R-1234yf; w/ CJ2 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	6 Cyl 3.6L Eng. - 38.40 Oz. R-1234yf; w/ C24 Compressor; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	6 Cyl 3.6L Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-46; w/ C24 Compressor	59007
<b>CTS</b>		
18 - 14	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 19.02 Oz. R-134a	59007
18 - 14	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 19.02 Oz. R-134a	59007
18 - 14	8 Cyl 6.2L Eng. - CTS-V, 3.70 Oz. PAG-46; 19.02 Oz. R-134a	59007
14	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 19.02 Oz. R-134a	59007
13	8 Cyl 6.2L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
13 - 12	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CADILLAC

Year	Description	Lubricant
<b>CTS</b>		
13 - 12	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
12 - 10	8 Cyl 6.2L Eng. - 18.20 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 10	6 Cyl 3.0L Eng. - 18.20 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 10	6 Cyl 3.6L Eng. - 18.20 Oz. R-134a; 3.72 Oz. PAG-46	59007
09 - 08	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07 - 03	All Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>DEVILLE</b>		
05 - 02	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 00	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99 - 98	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99 - 98	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 94	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97 - 94	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
73 - 71	8 Cyl 7.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 64	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
63	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>DTS</b>		
11	8 Cyl 4.6L Eng. - 22.88 Oz. R-134a; 4.75 Oz. PAG-46	59007
10 - 06	All Eng. - 22.88 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>ELDORADO</b>		
02 - 98	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02 - 98	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 94	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97 - 94	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88 - 86	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 8.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>Escalade</b>		
18	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
17 - 15	8 Cyl 6.2L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 6.2L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
13 - 10	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
13 - 10	8 Cyl 6.2L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12	8 Cyl 6.0L Eng. - Electric/Flex, w/ Rear AC; 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
11	8 Cyl 6.0L Eng. - Electric/Gas, w/ Rear AC; 48.00 Oz. R-134a; 11.00 Oz. POE Oil	59889
10	8 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
09	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
09 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
08	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.00 Oz. R-134a	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 42.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 99	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00 - 99	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CADILLAC

Year	Description	Lubricant
<b>Escalade</b>		
00 - 99	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00 - 99	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>Escalade ESV</b>		
18	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
17 - 15	8 Cyl 6.2L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 6.2L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
13 - 10	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
13 - 10	8 Cyl 6.2L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
09 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
08	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
<b>Escalade EXT</b>		
13 - 10	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
13 - 10	8 Cyl 6.2L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
09 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
08	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 03	All Eng. - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 42.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>FLEETWOOD / BROUGHAM</b>		
96 - 94	All Eng. - RWD, w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96 - 94	All Eng. - RWD, w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - RWD, 8.00 Oz. Mineral Oil; 50.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - Brougham, 8.00 Oz. Mineral Oil; 49.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - Fleetwood, FWD, 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 87	All Eng. - Brougham, 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 86	All Eng. - Fleetwood, FWD, 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - Brougham, 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
73 - 70	8 Cyl 8.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 7.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SEVILLE</b>		
04 - 01	All Eng. - w/ Mitsubishi Compressor; 35.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Mitsubishi Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
98	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 94	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97 - 94	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 4.5L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	8 Cyl 4.1L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	8 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SRX</b>		
16 - 14	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 25.76 Oz. R-134a	59007
12	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
11	6 Cyl 2.8L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
11	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
10	6 Cyl 2.8L Eng. - 3.70 Oz. PAG-46; 25.60 Oz. R-134a	59007
10	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 25.75 Oz. R-134a	59007
09	6 Cyl 3.6L Eng. - w/o Rear AC; 20.16 Oz. R-134a; 6.09 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CADILLAC

Year	Description	Lubricant
<b>SRX</b>		
09	8 Cyl 4.6L Eng. - w/ Rear AC; 28.16 Oz. R-134a; 7.44 Oz. PAG-46	59007
08 - 04	All Eng. - w/ Rear AC; 28.16 Oz. R-134a; 7.44 Oz. PAG-46	59007
08 - 04	All Eng. - w/o Rear AC; 20.16 Oz. R-134a; 6.09 Oz. PAG-46	59007
<b>STS</b>		
11 - 08	6 Cyl 3.6L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 08	8 Cyl 4.6L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
09 - 08	8 Cyl 4.4L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
07	All Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
06	8 Cyl 4.4L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
06 - 05	6 Cyl 3.6L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
06 - 05	8 Cyl 4.6L Eng. - 4.73 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>XLR</b>		
09 - 06	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 04	All Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>XT5</b>		
18 - 17	6 Cyl 3.6L Eng. - 24.64 Oz. R-1234yf; 4.02 Oz. PAG Oil	59234
<b>XTS</b>		
17	6 Cyl 3.6L Eng. - 20.80 Oz. R-1234yf; w/ KRV Compressor; See Under Hood Decal for Lubricant Capacity	59234
17	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46; w/o KRV Compressor	59007

## CHEVROLET

Year	Description	Lubricant
<b>AVEO</b>		
11	4 Cyl 1.6L Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-46	59007
10 - 09	4 Cyl 1.6L Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-150	59003
08	All Eng. - 18.00+/-1 Oz. R-134a; 6.80 Oz. PAG-46	59007
07	All Eng. - 21.00+/-1 Oz. R-134a; 7.40 Oz. PAG-46	59007
06	All Eng. - 23.68 Oz. R-134a; 7.40 Oz. PAG-46	59007
05 - 04	All Eng. - 24.00 Oz. R-134a; 8.00 Oz. PAG-150; w/ OE Harrison Compressor V5	59003
04	All Eng. - w/ Mitsubishi Compressor; 35.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
<b>BERETTA</b>		
96 - 94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93 - 92	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	4 Cyl 2.0L Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87	6 Cyl 2.8L Eng. - 8.00 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
<b>CAMARO</b>		
18 - 17	8 Cyl 6.2L Eng. - 17.60 Oz. R-134a; 4.10 Oz. PAG-46	59007
18 - 16	4 Cyl 2.0L Eng. - 19.20 Oz. R-1234yf; 4.10 Oz. PAG	59234
18 - 16	6 Cyl 3.6L Eng. - 19.20 Oz. R-1234yf; 4.10 Oz. PAG	59234
18 - 16	8 Cyl 6.2L Eng. - 19.20 Oz. R-1234yf; 4.10 Oz. PAG	59234
16	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 19.20 Oz. R-134a	59007
15 - 14	6 Cyl 3.6L Eng. - 4.10 Oz. PAG-46; 19.04 Oz. R-134a	59007
15 - 14	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 19.04 Oz. R-134a	59007
15 - 14	8 Cyl 7.0L Eng. - 4.10 Oz. PAG-46; 19.04 Oz. R-134a	59007
13	6 Cyl 3.6L Eng. - 18.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13	8 Cyl 6.2L Eng. - 18.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - 16.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 6.2L Eng. - 16.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 6.2L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl 3.6L Eng. - 4.06 Oz. PAG-46; 21.00 Oz. R-134	59007
02 - 98	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	6 Cyl 3.8L Eng. - w/ Denso Compressor; 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; 26.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>CAMARO</b>		
97 - 96	8 Cyl 5.7L Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97 - 96	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	6 Cyl 3.8L Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 93	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 93	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	6 Cyl 2.8L Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.0L Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 67	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 67	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70 - 67	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CAPRICE</b>		
14	6 Cyl 3.6L Eng. - 4.70 Oz. PAG-46; 16.96 Oz. R-134a	59007
14	8 Cyl 6.0L Eng. - 4.70 Oz. PAG-46; 16.96 Oz. R-134a	59007
13 - 12	6 Cyl 3.6L Eng. - 3.30-4.70 Oz. PAG-46; 17.00 Oz. R-134a	59007
13 - 12	8 Cyl 6.0L Eng. - 3.30-4.70 Oz. PAG-46; 17.00 Oz. R-134a	59007
11	8 Cyl 6.0L Eng. - 20.00 Oz. R-134a; 3.30-4.70 Oz. PAG-46	59007
96 - 94	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96 - 94	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 8.00 Oz. Mineral Oil; 50.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 66	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 66	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CAVALIER</b>		
05 - 03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl 2.2L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl 2.2L Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02	4 Cyl 2.4L Eng. - 21.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01 - 95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	4 Cyl 2.2L Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	6 Cyl 3.1L Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>CAVALIER</b>		
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 86	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CELEBRITY</b>		
90 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CHEVELLE</b>		
73 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70 - 65	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 66	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 65	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CHEVY II</b>		
67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 64	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 62	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CITATION</b>		
85 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CLASSIC</b>		
05 - 04	4 Cyl 2.2L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>COBALT</b>		
10 - 09	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
10 - 09	4 Cyl 2.2L Eng. - 4.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
08 - 07	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
08 - 07	All Eng. - 4.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
06	All Eng. - 5.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
05	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
05	4 Cyl 2.2L Eng. - 5.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>CORSICA</b>		
96 - 94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93	4 Cyl 2.2L Eng. - 8.00 Oz. PAG-150; 42.00 Oz. R-134	59003
93 - 92	6 Cyl 3.1L Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	4 Cyl 2.2L Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
91	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	4 Cyl 2.0L Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87	6 Cyl 2.8L Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>CORVETTE</b>		
18 - 17	8 Cyl 6.2L Eng. - 18.56 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 14	8 Cyl 6.2L Eng. - 19.20 Oz. R-134a; 4.30 Oz. PAG-46	59007
13	8 Cyl 6.2L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
13	8 Cyl 7.0L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	8 Cyl 6.2L Eng. - 5.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
12	8 Cyl 7.0L Eng. - 5.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
11	8 Cyl 6.2L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	8 Cyl 7.0L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>CORVETTE</b>		
10 - 06	All Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
04 - 02	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01 - 00	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99 - 97	All Eng. - 26.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93 - 90	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 66	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	8 Cyl Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CRUZE</b>		
18 - 17	4 Cyl 1.4L Eng. - 16.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	4 Cyl 1.4L Eng. - 18.40 Oz. R-134a; 2.03 Oz. PAG-46	59007
18 - 17	4 Cyl 1.6L Eng. - Diesel, 16.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	4 Cyl 1.6L Eng. - Diesel, 18.40 Oz. R-134a; 2.03 Oz. PAG-46	59007
16 - 14	4 Cyl 1.4L Eng. - 22.40 Oz. R-134a; 4.30 Oz. PAG-46	59007
15 - 14	4 Cyl 1.8L Eng. - 22.40 Oz. R-134a; 4.30 Oz. PAG-46	59007
15 - 14	4 Cyl 2.0L Eng. - 22.40 Oz. R-134a; 4.30 Oz. PAG-46	59007
13 - 11	4 Cyl 1.4L Eng. - 4.23 Oz. PAG-46; 22.08 Oz. R-134a	59007
13 - 10	4 Cyl 1.8L Eng. - 4.23 Oz. PAG-46; 22.08 Oz. R-134a	59007
<b>EL CAMINO</b>		
87 - 85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	8 Cyl Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>IMPALA</b>		
18	4 Cyl 2.5L Eng. - PAG-46; 20.80 Oz. R-134a	59007
18	6 Cyl 3.6L Eng. - 20.80 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 14	4 Cyl 2.5L Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
17 - 14	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
14	4 Cyl 2.4L Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
13 - 12	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11 - 08	6 Cyl 3.9L Eng. - 5.00 Oz. PAG-46; 20.40 Oz. R-134a	59007
09	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 20.40 Oz. R-134a	59007
09	8 Cyl 5.3L Eng. - 5.00 Oz. PAG-46; 20.40 Oz. R-134a	59007
08	6 Cyl Eng. - 5.00 Oz. PAG-46; 20.40 Oz. R-134a	59007
08	8 Cyl 5.3L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
07 - 06	6 Cyl 3.9L Eng. - 5.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
07 - 06	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 04	All Eng. - 8.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
03 - 00	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>IMPALA</b>		
85 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	8 Cyl 4.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 73	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 73	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 66	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>IMPALA SS</b>		
14	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
14	4 Cyl 2.5L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
14	6 Cyl 3.6L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
13 - 12	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl 3.9L Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	8 Cyl 5.3L Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96 - 94	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96 - 94	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>LUMINA</b>		
01 - 98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 9.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 90	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>LUMINA APV</b>		
96	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
96	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	6 Cyl 3.1L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
93	All Eng. - w/ Denso Compressor; w/o Rear AC; 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
93	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - w/ Rear AC; 8.00 Oz. Mineral Oil; 67.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 51.00 Oz. R-12	59000 <sup>(1)</sup>
90	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MALIBU / MALIBU MAXX</b>		
18 - 16	4 Cyl 1.5L Eng. - Malibu, 21.12 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	4 Cyl 1.8L Eng. - Electric/Gas, Malibu, 21.12 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 16	4 Cyl 2.0L Eng. - Malibu, 21.12 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
15 - 14	4 Cyl 2.0L Eng. - Malibu, 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
15 - 14	4 Cyl 2.5L Eng. - Malibu, 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
14	4 Cyl 2.4L Eng. - Malibu, 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11 - 10	4 Cyl 2.4L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
11 - 10	6 Cyl 3.6L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
09 - 04	All Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>MALIBU / MALIBU MAXX</b>		
03 - 02	All Eng. - 9.00 Oz. PAG-150; 22.00 Oz. R-134a	59003
01 - 97	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>METRO</b>		
01	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
00	3 Cyl 1.0L Eng. - 19.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
00	4 Cyl 1.3L Eng. - 19.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
99 - 98	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
92	4 Cyl 1.3L Eng. - 18.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTE CARLO</b>		
07 - 06	All Eng. - 5.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
05 - 04	All Eng. - 8.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
03 - 98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96 - 95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
88	6 Cyl 4.3L Eng. - 60.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
88	8 Cyl 5.0L Eng. - 60.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	All Eng. - 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
73 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>NOVA</b>		
88 - 87	All Eng. - 7.00 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
73 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 64	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 62	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PRIZM</b>		
02 - 98	All Eng. - 8.00 Oz. PAG-150; 26.50 Oz. R-134a	59003
<b>SONIC</b>		
18 - 14	4 Cyl 1.4L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
18 - 14	4 Cyl 1.8L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 12	4 Cyl 1.4L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 12	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 12	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
<b>SPRINT</b>		
88 - 85	3 Cyl 1.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>VECTRA</b>		
08 - 04	All Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
03	All Eng. - 9.00 Oz. PAG-150; 22.00 Oz. R-134a	59003
<b>VENTURE</b>		
05 - 01	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05 - 01	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 97	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 46.00 Oz. R-134a	59003
00 - 97	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET

Year	Description	Lubricant
<b>VOLT</b>		
13 - 11	4 Cyl 1.4L Eng. - HYBRID, 34.00 Oz. R-134a; 6.10 Oz. Hybrid Oil	59889

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>ASTRO</b>		
05 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
05 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
05 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 85	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	All Eng. - w/ Rear AC; 48.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<b>AVALANCHE</b>		
13	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
13	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 38.00 Oz. R-134a, Front and Rear	59007
12 - 09	8 Cyl 5.3L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 7.10 Oz. PAG-46	59007
11 - 09	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
09	8 Cyl 6.0L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 7.10 Oz. PAG-46	59007
09	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
08	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
08 - 07	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; 7.10 Oz. PAG-46	59007
07	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 38.00 Oz. R-134a	59007

<b>AVALANCHE 1500</b>		
06 - 03	8 Cyl 5.3L Eng. - w/o Rear AC; 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
06 - 02	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.00 Oz. R-134a	59007
02	8 Cyl 5.3L Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<b>AVALANCHE 2500</b>		
06 - 05	8 Cyl 8.1L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 02	8 Cyl 8.1L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.00 Oz. R-134a	59007
04 - 03	8 Cyl 8.1L Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	8 Cyl 8.1L Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<b>BLAZER</b>		
05 - 01	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05 - 01	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00 - 99	All Eng. - w/ Denso Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
00 - 99	All Eng. - w/ OE Harrison Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-150	59003
98 - 96	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 96	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - Blazer (Mid Size / S10 / T10), 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - FullSize Blazer, w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
94	All Eng. - FullSize Blazer, w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Blazer (Mid Size / S10 / T10), 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - FullSize Blazer, w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - FullSize Blazer, w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - FullSize Blazer, w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - Blazer (Mid Size / S10 / T10), 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 90	All Eng. - FullSize Blazer, w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - FullSize Blazer, w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - FullSize Blazer, w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - FullSize Blazer, w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - Blazer (Mid Size / S10 / T10), 8.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - FullSize Blazer, w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - FullSize Blazer, w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>BLAZER</b>		
87	8 Cyl 5.7L Eng. - FullSize Blazer, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 6.2L Eng. - FullSize Blazer, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	All Eng. - Blazer (Mid Size / S10 / T10), 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CAPTIVA / CAPTIVA SPORT</b>		
14	4 Cyl 2.4L Eng. - Captiva Sport, 21.92 Oz. R-134a; 5.30 Oz. PAG-46	59007
14	6 Cyl 3.0L Eng. - Captiva Sport, 21.92 Oz. R-134a; 5.30 Oz. PAG-46	59007
13	4 Cyl 2.4L Eng. - 22.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
13	6 Cyl 3.0L Eng. - Captiva Sport, 22.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
12	6 Cyl 3.0L Eng. - 22.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - Captiva Sport, 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>CHEYENNE</b>		
13	8 Cyl 5.3L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
12 - 11	8 Cyl 5.3L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
11 - 10	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
10	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
<b>COLORADO</b>		
18 - 16	4 Cyl 2.8L Eng. - Diesel, 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
18 - 15	4 Cyl 2.5L Eng. - 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
18 - 15	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
12	4 Cyl 2.9L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12	5 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 09	8 Cyl 5.3L Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	4 Cyl 2.9L Eng. - 4.00 Oz. PAG-46; 21.20 Oz. R-134a	59007
11	5 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 21.20 Oz. R-134a	59007
10 - 09	4 Cyl 2.9L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10 - 09	5 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07	All Eng. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
06	All Eng. - 25.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
05 - 04	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>EQUINOX</b>		
18	4 Cyl 1.5L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 1.5L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
18	4 Cyl 1.6L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 1.6L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
18	4 Cyl 2.0L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
17 - 14	4 Cyl 2.4L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
13	4 Cyl 2.4L Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
12	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>EQUINOX</b>		
11 - 10	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
11 - 10	6 Cyl 3.0L Eng. - 4.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
09	6 Cyl 3.4L Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	6 Cyl 3.6L Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007
08 - 06	All Eng. - 20.80 Oz. R-134a; 4.40 Oz. PAG-46	59007
05	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>FULLSIZE PICKUP</b>		
18 - 17	6 Cyl 4.3L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 5.3L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.0L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.0L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.2L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.6L Eng. - Diesel, 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.6L Eng. - Diesel, 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 15	6 Cyl 4.3L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 15	8 Cyl 5.3L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 15	8 Cyl 6.2L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
14 - 13	6 Cyl 4.3L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
14 - 13	8 Cyl 5.3L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
14 - 13	8 Cyl 6.0L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
14 - 13	8 Cyl 6.2L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
14 - 13	8 Cyl 6.6L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
13	8 Cyl 4.8L Eng. - 7.10 Oz. PAG-46; 24.69 Oz. R-134a	59007
12	6 Cyl 4.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a, Front and Rear	59007
12	6 Cyl 4.3L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46, Front AC	59007
12	8 Cyl 4.8L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 11	8 Cyl 5.3L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 11	8 Cyl 6.0L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 11	8 Cyl 6.2L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 11	8 Cyl 6.6L Eng. - 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
11	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11 - 09	6 Cyl 4.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007
11 - 09	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11 - 09	8 Cyl 4.8L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
11 - 07	6 Cyl 4.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11 - 07	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11 - 07	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
10	8 Cyl 6.2L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
10 - 09	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
10 - 09	8 Cyl 6.6L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
10 - 07	8 Cyl 6.0L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
08	6 Cyl 4.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
08 - 07	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007
07	6 Cyl 4.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 8.00 Oz. PAG-46	59007
07	8 Cyl 8.1L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
07	8 Cyl 8.1L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
06	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
05	6 Cyl 4.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.20 Oz. R-134a	59007
05	6 Cyl 4.3L Eng. - w/o Rear AC; 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	8 Cyl 5.3L Eng. - Flex, w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
05	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.20 Oz. R-134a	59007
05	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 28.20 Oz. R-134a	59007
04 - 03	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>FULLSIZE PICKUP</b>		
99 - 96	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Crew Cab, 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Crew Cab, 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Crew Cab, 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 90	All Eng. - C,K Pickup, 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 88	All Eng. - R,V Pickup, 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - C,K Pickup, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>G SERIES FULLSIZE VAN / EXPRESS</b>		
13	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.44 Oz. R-134a	59007
13	8 Cyl 4.8L Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 32.10 Oz. R-134a	59007
13	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.09 Oz. R-134a	59007
13	8 Cyl 5.3L Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 32.10 Oz. R-134a	59007
13	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.44 Oz. R-134a	59007
13	8 Cyl 6.0L Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 32.10 Oz. R-134a	59007
13	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.44 Oz. R-134a	59007
13	8 Cyl 6.6L Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 32.10 Oz. R-134a	59007
12	6 Cyl 4.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	6 Cyl 4.3L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 4.8L Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 5.3L Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.0L Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.6L Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
11 - 10	6 Cyl 4.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	6 Cyl 4.3L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11 - 10	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 4.8L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11 - 10	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.3L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11 - 10	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>G SERIES FULLSIZE VAN / EXPRESS</b>		
11 - 10	8 Cyl 6.0L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11 - 10	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 6.6L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
06	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
05 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
02	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
01	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 72.00 Oz. R-134a	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
00 - 97	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 97	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 78.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 78.00 Oz. R-134a	59003
96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 68.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 68.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 64.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 64.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 46.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 85	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 83	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 80	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 80	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 73	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>G SERIES FULLSIZE VAN / EXPRESS</b>		
71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>HHR</b>		
11	4 Cyl 2.4L Eng. - 14.40 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	4 Cyl Eng. - 14.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 07	All Eng. - 14.40 Oz. R-134a; 4.00 Oz. PAG-46	59007
10 - 07	All Eng. - 14.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
06	All Eng. - 14.10 Oz. R-134a; 4.00 Oz. PAG-46	59007
06	All Eng. - 14.10 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>P SERIES VAN</b>		
99 - 94	6 Cyl 4.3L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	6 Cyl 4.3L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 5.7L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 6.5L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 6.5L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 7.4L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 7.4L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 5.7L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	8 Cyl 5.7L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
92 - 90	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 89	4 Cyl 3.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>P10 SERIES VAN</b>		
79	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>P20 SERIES VAN</b>		
89 - 85	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>P30 SERIES VAN</b>		
99 - 94	6 Cyl 4.3L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	6 Cyl 4.3L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 5.7L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 6.5L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 6.5L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 7.4L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 7.4L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 5.7L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>P30 SERIES VAN</b>		
93	8 Cyl 5.7L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
92 - 90	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 89	4 Cyl 3.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>P35 VAN</b>		
99 - 94	6 Cyl 4.3L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	6 Cyl 4.3L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 5.7L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 5.7L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	8 Cyl 5.7L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
92 - 90	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 86	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>S10 PICKUP</b>		
04 - 00	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
04 - 00	All Eng. - w/ Denso Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04 - 00	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
04 - 00	All Eng. - w/ OE Harrison Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99	All Eng. - Gas, w/ Denso Compressor; 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	All Eng. - Gas, w/ Denso Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99	All Eng. - Gas, w/ OE Harrison Compressor; 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99	All Eng. - Gas, w/ OE Harrison Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98 - 97	All Eng. - Gas, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 97	All Eng. - Gas, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 90	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 8.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 85	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SSR</b>		
06	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 04	All Eng. - 19.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>SUBURBAN</b>		
17 - 15	8 Cyl 5.3L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN</b>		
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN 1500</b>		
14	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
12 - 10	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
12 - 10	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
11 - 10	8 Cyl 6.0L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 6.0L Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 6.0L Eng. - Gas, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
08 - 01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
06 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SUBURBAN 2500</b>		
12 - 11	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
12 - 10	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
11 - 10	8 Cyl 6.0L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 6.0L Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 6.0L Eng. - Gas, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
08 - 01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
06 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SUBURBAN C10</b>		
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN C1500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN C1500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN C20</b>		
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN C2500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN K10</b>		
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN K1500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN K20</b>		
86 - 85	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN K20</b>		
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN K2500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN R10</b>		
88	All Eng. - w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN R1500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN R20</b>		
88	All Eng. - w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN R2500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN V10</b>		
88	All Eng. - w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN V1500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SUBURBAN V20</b>		
88	All Eng. - w/ Rear AC; 84.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN V2500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHEVROLET LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN V2500</b>		
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>TAHOE</b>		
18	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
17 - 15	8 Cyl 5.3L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG-46; w/ Front AC	59007
12	8 Cyl 5.3L Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.10 Oz. PAG-46	59007
12	8 Cyl 6.0L Eng. - w/o Rear AC; 25.6 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
11	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.3L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
11 - 10	8 Cyl 6.0L Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 4.8L Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
09	8 Cyl 4.8L Eng. - Gas, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 6.2L Eng. - Flex, w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
09	8 Cyl 6.2L Eng. - Flex, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
08	All Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
08	All Eng. - Excl. Hybrid, w/ Rear AC; 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
07 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 43.00 Oz. R-134a	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 42.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>TRACKER</b>		
04 - 99	All Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
98 - 94	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
93 - 89	All Eng. - 5.00 Oz. Mineral Oil; 21.00 Oz. R-12	59000 <sup>(1)</sup>
<b>TRAILBLAZER, TRAILBLAZER EXT</b>		
09	All Eng. - 30.40 Oz. R-134a; 6.00 Oz. PAG-46; w/o Thermal Switch	59007
09	All Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46; w/ Thermal Switch	59007
08 - 05	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
08 - 05	All Eng. - w/o Rear AC; 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
04 - 02	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
<b>TRAVERSE</b>		
13	6 Cyl 3.6L Eng. - 39.68 Oz. R-134a; 7.80 Oz. PAG-46	59007
12 - 09	6 Cyl 3.6L Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
<b>UPLANDER</b>		
08 - 07	All Eng. - w/ Rear AC; 31.68 Oz. R-134a; 7.77 Oz. PAG-46	59007
08 - 07	All Eng. - w/o Rear AC; 7.10 Oz. PAG-46; 22.88 Oz. R-134a	59007
06 - 05	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
06 - 05	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHRYSLER

Year	Description	Lubricant
<b>200 SERIES</b>		
17 - 15	4 Cyl 2.4L Eng. - 4.60 Oz. PAG-46; 18.80 Oz. R-1234yf	59234
17 - 15	6 Cyl 3.6L Eng. - 4.60 Oz. PAG-46; 18.80 Oz. R-1234yf	59234
14 - 11	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
14 - 11	6 Cyl 3.6L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>300 SERIES</b>		
18 - 14	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 14	6 Cyl 3.6L Eng. - 6.10 Oz. PAG-46; 24.96 Oz. R-1234yf	59234
18 - 14	8 Cyl 5.7L Eng. - 6.10 Oz. PAG-46; 24.96 Oz. R-1234yf	59234
18 - 13	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
14	8 Cyl 6.4L Eng. - 6.10 Oz. PAG-46; 24.96 Oz. R-1234yf	59234
14 - 13	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	8 Cyl 6.4L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 11	6 Cyl 3.6L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 09	8 Cyl 5.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	6 Cyl 2.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	8 Cyl 6.1L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08 - 05	All Eng. - 26.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
04 - 99	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>ASPEN</b>		
09 - 07	8 Cyl Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
09 - 07	8 Cyl Eng. - w/o Rear AC; 30.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
<b>CIRRUS</b>		
10	4 Cyl 2.4L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
00	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97 - 95	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>CONCORDE</b>		
04 - 99	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
98 - 97	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 93	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CONQUEST</b>		
89	All Eng. - 29.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CORDOBA</b>		
83 - 80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 79	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 79	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CROSSFIRE</b>		
08 - 07	6 Cyl 3.2L Eng. - 30.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06 - 04	All Eng. - 30.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>DYNASTY</b>		
93 - 90	6 Cyl 3.3L Eng. - 38.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
92 - 88	4 Cyl 2.5L Eng. - 38.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
90 - 88	6 Cyl 3.0L Eng. - 38.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>E CLASS</b>		
84	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>EXECUTIVE</b>		
85 - 84	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHRYSLER

Year	Description	Lubricant
<b>FIFTH AVENUE</b>		
93 - 91	6 Cyl 3.8L Eng. - 7.25 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 90	6 Cyl 3.3L Eng. - 7.25 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 88	All Eng. - 7.25 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
83	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>IMPERIAL</b>		
93	6 Cyl 3.8L Eng. - 32.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
92 - 91	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 90	6 Cyl 3.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LASER</b>		
86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LEBARON</b>		
95	All Eng. - 24.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 32.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 7.25 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 80	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LHS</b>		
01 - 99	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
97	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>NEW YORKER</b>		
96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	6 Cyl 3.3L Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 34.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 83	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 79	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 79	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>NEWPORT</b>		
81 - 79	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PACIFICA</b>		
08 - 07	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
06 - 04	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>PROWLER</b>		
02	All Eng. - w/o Rear AC; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	6 Cyl 3.5L Eng. - w/ Rear AC; 21.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
01	6 Cyl 3.5L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>PT CRUISER</b>		
10 - 09	4 Cyl 2.4L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHRYSLER

Year	Description	Lubricant
<b>PT CRUISER</b>		
08	All Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07 - 02	All Eng. - 6.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
01	All Eng. - 5.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>SEBRING</b>		
10 - 09	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
10 - 09	6 Cyl 2.7L Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
08	All Eng. - Sedan, 16.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
08 - 07	All Eng. - Convertible, 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
07 - 06	All Eng. - Sedan, 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
06	All Eng. - Convertible, 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
05 - 01	All Eng. - Sedan / Coupe, 4.00 Oz. PAG-46; 15.00 Oz. R-134a	59007
03	6 Cyl 2.7L Eng. - 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
03	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
02 - 00	All Eng. - Convertible, 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00	All Eng. - Sedan / Coupe, 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 97	All Eng. - Convertible, 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
99 - 95	4 Cyl Eng. - Sedan / Coupe, 24.00 Oz. R-134a; w/ Denso Compressor; 4.00 Oz. PAG-46	59007
99 - 95	6 Cyl Eng. - Sedan / Coupe, 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
96	All Eng. - Convertible, 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>TC MASERATI</b>		
91 - 90	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 89	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TOWN &amp; COUNTRY</b>		
13 - 12	All Eng. - 28.96 Oz. R-134a; 4.05 Oz. PAG-46	59007
13 - 12	All Eng. - 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
11	All Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 40.50 Oz. R-134a	59007
11	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10 - 08	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 08	All Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 27.80 Oz. R-134a	59007
07 - 06	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; 6.10 Oz. PAG-46	59007
07 - 06	All Eng. - w/ Rear AC; 38.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng. - w/ Rear AC; 7.80 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
05 - 04	All Eng. - w/o Rear AC; 6.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	All Eng. - w/ Rear AC; 10.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
03	All Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/ Rear AC; 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
03	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
02	All Eng. - w/ Rear AC; 7.40 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
02	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
01 - 00	All Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
01 - 96	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95 - 93	All Eng. - w/ Rear AC; 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95 - 93	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## CHRYSLER

Year	Description	Lubricant
<b>VOYAGER / GRAND VOYAGER</b>		
03	All Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/ Rear AC; 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
03	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
02	All Eng. - w/ Rear AC; 7.40 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
02	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
01 - 00	All Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
01 - 00	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97	6 Cyl 3.3L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
97	6 Cyl 3.3L Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
96	6 Cyl 3.3L Eng. - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
96	6 Cyl 3.8L Eng. - 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
96 - 95	6 Cyl 3.3L Eng. - w/ Rear AC; 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
96 - 95	6 Cyl 3.8L Eng. - w/ Rear AC; 52.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95	6 Cyl 3.3L Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
95	6 Cyl 3.8L Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007

## DAEWOO

Year	Description	Lubricant
<b>LANOS</b>		
02 - 99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
<b>LEGANZA</b>		
02 - 99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
<b>NUBIRA</b>		
02 - 99	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002

## DAIHATSU

Year	Description	Lubricant
<b>CHARADE</b>		
92 - 89	All Eng. - 4.00 Oz. Mineral Oil; 23.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ROCKY</b>		
92 - 90	All Eng. - 4.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>

## DODGE

Year	Description	Lubricant
<b>400</b>		
83 - 82	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 82	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>600</b>		
88 - 86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 83	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ARIES</b>		
89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88 - 87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	All Eng. - 7.25 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 81	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ASPEN</b>		
80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>AVENGER</b>		
14 - 11	6 Cyl 3.6L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
14 - 09	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE

Year	Description	Lubricant
<b>AVENGER</b>		
10 - 09	6 Cyl 2.7L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
10 - 09	6 Cyl 3.5L Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
08	All Eng. - 3.40 Oz. PAG-46; 16.00 Oz. R-134a	59007
00	All Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 95	4 Cyl Eng. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
99 - 95	6 Cyl Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>CALIBER</b>		
12 - 11	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
12 - 11	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
10 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 20.00 Oz. R-134a	59007
09	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
09	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08 - 07	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
<b>CHALLENGER</b>		
20 - 18	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 18	8 Cyl 5.7L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 17	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 15	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
20 - 14	6 Cyl 3.6L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
20 - 14	8 Cyl 5.7L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
20 - 14	8 Cyl 6.4L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
19	8 Cyl 6.4L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	8 Cyl 6.4L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
16	8 Cyl 5.7L Eng. - 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
16	8 Cyl 6.4L Eng. - 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
16 - 15	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
15 - 14	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
15 - 14	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
15 - 14	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13 - 12	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13 - 12	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	8 Cyl 6.4L Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
11	6 Cyl 3.6L Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
11	8 Cyl 5.7L Eng. - 23.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
11	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	8 Cyl 5.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 08	8 Cyl 6.1L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
83 - 81	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CHARGER</b>		
20 - 18	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 18	8 Cyl 5.7L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 18	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
20 - 18	8 Cyl 6.4L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 16	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
20 - 14	6 Cyl 3.6L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
20 - 14	8 Cyl 5.7L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
20 - 14	8 Cyl 6.4L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 16	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE

Year	Description	Lubricant
<b>CHARGER</b>		
17 - 16	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 15	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 15	8 Cyl 6.2L Eng. - 24.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
15	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
15 - 14	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
15 - 14	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
14	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13	8 Cyl 6.4L Eng. - 24.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	8 Cyl 6.4L Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 11	6 Cyl 3.6L Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 11	8 Cyl 5.7L Eng. - 24.96 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	6 Cyl 2.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	8 Cyl 5.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
10 - 09	8 Cyl 6.1L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08 - 07	All Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
06	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
87 - 85	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## COLT

94 - 93	4 Cyl 1.5L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
94 - 93	4 Cyl 1.8L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
92 - 85	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 89	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 89	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## CONQUEST

86 - 85	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
---------	---	----------------------

## DART

16 - 15	4 Cyl 1.4L Eng. - 6.00 Oz. PAG-46; 19.04 Oz. R-1234yf	59234
16 - 15	4 Cyl 2.0L Eng. - 6.00 Oz. PAG-46; 19.04 Oz. R-1234yf	59234
16 - 15	4 Cyl 2.4L Eng. - 6.00 Oz. PAG-46; 19.04 Oz. R-1234yf	59234
16 - 14	4 Cyl 1.4L Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
16 - 14	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
16 - 14	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
13	4 Cyl 1.4L Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007
13	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 5.90 Oz. PAG-46	59007

## DAYTONA

93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## DIPLOMAT

89 - 79	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## DYNASTY

93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
93 - 91	All Eng. - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE

Year	Description	Lubricant
<b>INTREPID</b>		
04 - 99	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
98 - 96	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95 - 93	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LANCER</b>		
89 - 86	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 85	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MAGNUM</b>		
08 - 06	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
05	6 Cyl 2.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
05	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
05	8 Cyl 5.7L Eng. - 26.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>MIRADA</b>		
83 - 80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 80	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONACO</b>		
92 - 90	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>NEON</b>		
05 - 02	All Eng. - 30.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01 - 00	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
98 - 97	All Eng. - 6.75 Oz. PAG-46; 25.00 Oz. R-134a	59007
96 - 95	All Eng. - 29.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>OMNI</b>		
90 - 89	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 34.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 84	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 81	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 78	4 Cyl 1.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SHADOW</b>		
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SPIRIT</b>		
95	All Eng. - 24.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>STEALTH</b>		
96	All Eng. - 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
95 - 94	All Eng. - 28.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
93	All Eng. - 29.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 5.50 Oz. Mineral Oil; 18.00 Oz. R-12	59000 <sup>(1)</sup>
<b>STRATUS</b>		
06 - 05	All Eng. - 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04 - 02	All Eng. - 4.00 Oz. PAG-46; 15.00 Oz. R-134a	59007
01 - 99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97 - 95	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>VIPER</b>		
17 - 14	10 Cyl 8.4L Eng. - 17.60 Oz. R-134a; 6.00 Oz. PAG-46	59007
10 - 09	10 Cyl 8.4L Eng. - 16.00 Oz. R-134a; 6.10 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE

Year	Description	Lubricant
<b>VIPER</b>		
08	All Eng. - 6.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
06 - 03	All Eng. - 6.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
02 - 94	All Eng. - 30.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

## DODGE HD

Year	Description	Lubricant
<b>RAM 4000 SERIES</b>		
10	6 Cyl 6.7L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 05	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
09 - 07	6 Cyl 5.9L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
06	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
02 - 00	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
99 - 98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 95	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002

### RAM 4500 SERIES

10	6 Cyl 6.7L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
----	---	-------

### RAM 5500 SERIES

10	6 Cyl 6.7L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
----	---	-------

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>B150 SERIES VAN</b>		
94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 49.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/ Rear AC; 64.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 64.00 Oz. R-12; 8.00 Oz. Mineral Oil, w/ Front and Rear AC	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### B1500 VAN

98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 95	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 95	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007

### B250 SERIES VAN

94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 49.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/ Rear AC; 64.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 64.00 Oz. R-12; 8.00 Oz. Mineral Oil, w/ Front and Rear AC	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>B2500 VAN</b>		
98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 95	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 95	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>B350 SERIES VAN</b>		
94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 9.00 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 49.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 65.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/ Rear AC; 64.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 64.00 Oz. R-12; 8.00 Oz. Mineral Oil, w/ Front and Rear AC	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B3500 VAN</b>		
98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 95	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 95	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>CARAVAN</b>		
07 - 06	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; 6.10 Oz. PAG-46	59007
07 - 06	All Eng. - w/ Rear AC; 38.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng. - w/ Rear AC; 7.80 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
05 - 04	All Eng. - w/o Rear AC; 6.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	All Eng. - w/ Rear AC; 10.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
03	All Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/o Rear AC; 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
02	All Eng. - w/ Rear AC; 7.40 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
02	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
01 - 00	All Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
01 - 96	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95 - 94	All Eng. - w/ Rear AC; 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
93	4 Cyl 2.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 50.00 Oz. R-134a	59007
93	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>CARAVAN</b>		
85 - 84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>D100 SERIES</b>		
89 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>D150 SERIES</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>D250 SERIES</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>D350 SERIES</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>DAKOTA</b>		
11	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 09	All Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07 - 01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
00	All Eng. - 32.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
93 - 92	All Eng. - 40.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 87	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>DURANGO</b>		
14	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a; w/ Front AC	59007
14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 32.48 Oz. R-134a; w/ Front and Rear AC	59007
14	6 Cyl 5.7L Eng. - 5.00 Oz. PAG-46; 32.48 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.7L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a; w/ Front AC	59007
13	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
13	8 Cyl 5.7L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
12	6 Cyl 3.6L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
12 - 11	6 Cyl 3.6L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
12 - 11	8 Cyl 5.7L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
12 - 11	8 Cyl 5.7L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
11	6 Cyl 3.6L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 31.68 Oz. R-134a	59007
09	6 Cyl 3.7L Eng. - w/ Rear AC; 41.00 Oz. R-134a; 6.90 Oz. PAG-46	59007
09	8 Cyl 5.7L Eng. - w/ Rear AC; 45.00 Oz. R-134a; 6.25 Oz. PAG-46	59007
09 - 08	6 Cyl 3.7L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
09 - 08	8 Cyl 4.7L Eng. - w/ Rear AC; 41.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
09 - 08	8 Cyl 4.7L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
09 - 08	8 Cyl 5.7L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
09 - 08	8 Cyl 5.7L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
08	6 Cyl 3.7L Eng. - w/ Rear AC; 41.00 Oz. R-134a; 6.09 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>DURANGO</b>		
07	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 30.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
06 - 05	All Eng. - w/ R134a; w/ Rear AC; 7.50 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
06 - 05	All Eng. - w/ R134a; w/o Rear AC; 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	All Eng. - w/ R134a; w/ Rear AC; 10.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	All Eng. - w/ R134a; w/o Rear AC; 7.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
03 - 01	All Eng. - w/ R134a; w/ Rear AC; 10.00 Oz. PAG-100; See Under Hood Decal for Refrigerant Capacity	59002
03 - 01	All Eng. - w/ R134a; w/o Rear AC; 7.00 Oz. PAG-100; See Under Hood Decal for Refrigerant Capacity	59002
00	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
00 - 98	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 5.50 Oz. PAG-100	59002
99 - 98	All Eng. - w/ Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
<b>GRAND CARAVAN</b>		
18 - 14	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 28.96 Oz. R-134a; w/ Front AC	59007
18 - 14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 40.48 Oz. R-134a; w/ Front and Rear AC	59007
13	6 Cyl 3.6L Eng. - w/o Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13 - 12	6 Cyl 3.6L Eng. - w/ Rear AC; 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
11	All Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 40.50 Oz. R-134a	59007
11	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10 - 08	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 08	All Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 27.80 Oz. R-134a	59007
07 - 06	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; 6.10 Oz. PAG-46	59007
07 - 06	All Eng. - w/ Rear AC; 38.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
05	All Eng. - w/ Rear AC; 7.80 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
05 - 04	All Eng. - w/o Rear AC; 6.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	All Eng. - w/ Rear AC; 10.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
03	All Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 5.00 Oz. PAG-46; w/ Single or Dual Zone	59007
03	All Eng. - w/o Rear AC; 43.00 Oz. R-134a; 6.40 Oz. PAG-46; w/ 3 Zone	59007
02	All Eng. - w/ Rear AC; 7.40 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
02	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
01 - 00	All Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
01 - 96	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95 - 94	All Eng. - w/ Rear AC; 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
93	6 Cyl 3.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 50.00 Oz. R-134a	59007
93	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>JOURNEY</b>		
18 - 16	4 Cyl 2.4L Eng. - 20.00 Oz. R-1234yf; 3.40 Oz. PAG; Single Zone Climate Control System	59234
18 - 16	4 Cyl 2.4L Eng. - 3.40 Oz. PAG; 31.20 Oz. R-1234yf; Dual Zone Climate Control System	59234
18 - 16	4 Cyl 3.6L Eng. - 20.00 Oz. R-1234yf; 3.40 Oz. PAG; Single Zone Climate Control System	59234
18 - 16	4 Cyl 3.6L Eng. - 3.40 Oz. PAG; 31.20 Oz. R-1234yf; Dual Zone Climate Control System	59234

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>JOURNEY</b>		
15	4 Cyl 3.6L Eng. - 22.08 Oz. R-134a; 3.40 Oz. PAG-100; Single Zone Climate Control System	59002
15	4 Cyl 3.6L Eng. - 32.00 Oz. R-134a; 3.40 Oz. PAG-100; Dual Zone Climate Control System	59002
14	4 Cyl 2.4L Eng. - 32.00 Oz. R-134a; 3.40 Oz. PAG-100; Dual Zone Climate Control System	59002
14	6 Cyl 3.6L Eng. - 22.08 Oz. R-134a; 3.40 Oz. PAG-100; Single Zone Climate Control System	59002
13 - 11	6 Cyl 3.6L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
13 - 11	6 Cyl 3.6L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
13 - 09	4 Cyl 2.4L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
13 - 09	4 Cyl 2.4L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
10 - 09	6 Cyl 3.5L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
10 - 09	6 Cyl 3.5L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 3.40 Oz. PAG-100	59002
<b>NITRO</b>		
11	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl 4.0L Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 07	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>RAIDER</b>		
89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAM 100</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>RAM 150</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>RAM 1500 SERIES TRUCK</b>		
10 - 04	6 Cyl 3.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 04	8 Cyl 4.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 04	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
06	10 Cyl 8.3L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 04	10 Cyl 8.3L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
03	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59007
02 - 00	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
99 - 98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
<b>RAM 1500 VAN</b>		
03 - 98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
03 - 98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>RAM 250</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAM 2500 SERIES TRUCK</b>		
10 - 09	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 07	6 Cyl 5.9L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 04	8 Cyl 4.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 04	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 07	6 Cyl 6.7L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 04	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
03	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59007
02 - 00	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
99 - 98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>RAM 2500 VAN</b>		
03 - 98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
03 - 98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>RAM 350</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>RAM 3500 SERIES TRUCK</b>		
10 - 09	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 07	6 Cyl 5.9L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 04	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 07	6 Cyl 6.7L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 04	6 Cyl 5.9L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
03	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59007
02 - 00	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
99 - 98	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
<b>RAM 3500 VAN</b>		
03 - 98	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
03 - 98	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
97 - 94	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
97 - 94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>RAM 50 / POWER RAM 50</b>		
93 - 90	All Eng. - 30.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMCHARGER</b>		
01 - 00	All Eng. - 32.00 Oz. R-134a; 6.25 Oz. PAG-100	59002
99	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
96 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMCHARGER AD100</b>		
88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMCHARGER AD150</b>		
96 - 94	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMCHARGER AW100</b>		
88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMCHARGER AW150</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## DODGE LIGHT TRUCK

Year	Description	Lubricant
<b>RAMCHARGER AW150</b>		
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RAMPAGE</b>		
84 - 82	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>Sprinter 2500</b>		
09 - 08	6 Cyl 3.0L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
09 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
08	6 Cyl 3.5L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
08	6 Cyl 3.5L Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
06 - 05	5 Cyl 2.7L Eng. - 13.90 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	5 Cyl 2.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
03	5 Cyl 2.7L Eng. - 13.90 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
<b>Sprinter 3500</b>		
09 - 08	6 Cyl 3.0L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
09 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
08	6 Cyl 3.5L Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 32.48 Oz. R-134a	59007
08	6 Cyl 3.5L Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	All Eng. - w/o Rear AC; 28.16 Oz. R-134a; 6.40 Oz. PAG-46	59007
06 - 05	5 Cyl 2.7L Eng. - 13.90 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04	5 Cyl 2.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
03	5 Cyl 2.7L Eng. - 13.90 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
<b>W100 SERIES</b>		
89 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>W150</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>W250</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>W350</b>		
93	All Eng. - 4.75 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 88	All Eng. - 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 42.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 82	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## EAGLE

Year	Description	Lubricant
<b>MEDALLION</b>		
89	All Eng. - 29.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## EAGLE

Year	Description	Lubricant
------	-------------	-----------

### PREMIER

92 - 89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### SUMMIT

96 - 95	4 Cyl 1.5L Eng. - Coupe, 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
96 - 95	4 Cyl 1.5L Eng. - Sedan, 27.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
96 - 94	4 Cyl 1.8L Eng. - 27.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
96 - 94	4 Cyl 2.4L Eng. - 27.00 Oz. R-134a; 2.70 Oz. PAG-46	59007
94	4 Cyl 1.5L Eng. - 27.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
93	4 Cyl 1.5L Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	4 Cyl 1.8L Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	4 Cyl 2.4L Eng. - 28.00 Oz. R-12; 5.60 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	4 Cyl 1.8L Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	4 Cyl 2.4L Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	4 Cyl 1.5L Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	4 Cyl 1.6L Eng. - 36.00 Oz. R-12; 5.70 Oz. Mineral Oil	59000 <sup>(1)</sup>

### TALON

98 - 95	All Eng. - 25.50 Oz. R-134a; 6.50 Oz. PAG-100	59002
94 - 90	All Eng. - 33.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

### VISION

97 - 96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 93	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	6 Cyl 3.3L Eng. - 28.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
94	6 Cyl 3.5L Eng. - 28.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
93	6 Cyl 3.3L Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
93	6 Cyl 3.5L Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

## FIAT

Year	Description	Lubricant
------	-------------	-----------

### 124

18 - 17	4 Cyl 1.4L Eng. - Spider, 14.40 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
---------	---	-------

### 500 / 500e

18 - 17	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.00 Oz. R-134a	59007
17	4 Cyl 1.4L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17	All Eng. - Electric, 16.96 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
16	All Eng. - Electric, 16.96 Oz. R-134a; 1.70 Oz. POE Oil	59889
16 - 14	4 Cyl 1.4L Eng. - 1.70 Oz. PAG Oil; 16.00 Oz. R-1234yf	59234
15	All Eng. - Electric, 16.96 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 14	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.96 Oz. R-134a	59007
14	All Eng. - Electric, 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59889
13 - 12	4 Cyl 1.4L Eng. - 17.00 Oz. R-134a; 3.80 Oz. PAG-46	59007
11	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.96 Oz. R-134a	59007

### 500L

18 - 17	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.00 Oz. R-134a	59007
17	4 Cyl 1.4L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16 - 14	4 Cyl 1.4L Eng. - 1.70 Oz. PAG Oil; 16.00 Oz. R-1234yf	59234
15 - 14	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.96 Oz. R-134a	59007

### 500X

18 - 17	4 Cyl 1.4L Eng. - 1.70 Oz. PAG-46; 16.00 Oz. R-134a	59007
17	4 Cyl 1.4L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 16	4 Cyl 2.4L Eng. - 1.70 Oz. PAG-46; 16.00 Oz. R-134a	59007
16	4 Cyl 1.4L Eng. - 1.70 Oz. PAG Oil; 16.00 Oz. R-1234yf	59234

### STRADA

11	4 Cyl 1.8L Eng. - 1.70 Oz. PAG-46; 16.96 Oz. R-134a	59007
----	---	-------

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD

Year	Description	Lubricant
<b>ASPIRE</b>		
97	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
96 - 94	All Eng. - 6.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>C-MAX</b>		
18 - 14	4 Cyl 2.0L Eng. - 26.08 Oz. R-134a; 5.20 Oz. Hybrid Oil	59889
<b>CONTOUR</b>		
00 - 95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>COUNTRY SQUIRE</b>		
91 - 88	8 Cyl 5.0L Eng. - w/ Denso Compressor; 54.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 5.0L Eng. - 10.00 Oz. Mineral Oil; 54.00 Oz. R-12	59000 <sup>(1)</sup>
<b>CROWN VICTORIA</b>		
11 - 09	8 Cyl 4.6L Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 06	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 97	All Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
96 - 95	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
94	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
93	8 Cyl 4.6L Eng. - 38.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
93	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 13.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12, To 9/86	59000 <sup>(1)</sup>
87	All Eng. - 13.00 Oz. Mineral Oil; 52.00 Oz. R-12, From 9/86	59000 <sup>(1)</sup>
<b>EDGE</b>		
14	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 16.96 Oz. R-134a	59007
14	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 16.96 Oz. R-134a	59007
14	6 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 20.32 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13	6 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
12 - 11	6 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
12 - 09	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>ESCORT</b>		
02 - 98	4 Cyl 2.0L Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
02 - 97	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96 - 94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 34.08 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 8.00 Oz. Mineral Oil; 33.92 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 8.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 81	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>EXP</b>		
88 - 86	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FAIRMONT</b>		
82 - 80	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 78	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FESTIVA</b>		
93 - 88	All Eng. - 10.00 Oz. Mineral Oil; 25.00 Oz. R-12	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD

Year	Description	Lubricant
<b>FIESTA</b>		
14	3 Cyl 1.0L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
14	4 Cyl 1.6L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13 - 10	4 Cyl 1.6L Eng. - 3.40 Oz. PAG-46; 19.00 Oz. R-134a	59007
<b>FIVE HUNDRED</b>		
07 - 05	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
07 - 05	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>FOCUS</b>		
14	All Eng. - Gas, 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
13	All Eng. - Electric/Gas, 21.12 Oz. R-134a; 4.00 Oz. POE Oil	59889
13	All Eng. - Gas, 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
12 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07 - 00	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>FUSION</b>		
14	4 Cyl 1.5L Eng. - Gas, 4.90 Oz. PAG-46; 19.68 Oz. R-134a	59007
14	4 Cyl 1.6L Eng. - 4.90 Oz. PAG-46; 19.68 Oz. R-134a	59007
14	4 Cyl 2.0L Eng. - Gas, 4.90 Oz. PAG-46; 19.68 Oz. R-134a	59007
14	4 Cyl 2.5L Eng. - Gas, 4.90 Oz. PAG-46; 19.68 Oz. R-134a	59007
14 - 13	4 Cyl 2.0L Eng. - Electric/Gas, 20.00 Oz. R-134a; 4.90 Oz. Hybrid Oil	59889
13	4 Cyl 1.6L Eng. - 20.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - Gas, 20.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
13	4 Cyl 2.5L Eng. - Gas, 24.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
12 - 10	4 Cyl 2.5L Eng. - Electric/Gas, 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
12 - 10	4 Cyl 2.5L Eng. - Gas, 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
12 - 10	6 Cyl 3.0L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
12 - 10	6 Cyl 3.5L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
09	4 Cyl 2.3L Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>GRANADA</b>		
82	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 80	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 76	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
77 - 76	6 Cyl 3.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
77 - 75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LTD</b>		
86 - 85	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LTD II</b>		
79 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MAVERICK</b>		
77 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MUSTANG</b>		
18	4 Cyl 2.3L Eng. - 19.20 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
18	4 Cyl 2.3L Eng. - 3.40 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
18	8 Cyl 5.0L Eng. - 19.20 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
18	8 Cyl 5.2L Eng. - 24.00 Oz. R-1234yf; 4.00 Oz. PAG Oil	59234
17 - 15	4 Cyl 2.3L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
17 - 15	6 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
17 - 15	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
17 - 15	8 Cyl 5.2L Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD

Year	Description	Lubricant
<b>MUSTANG</b>		
14	6 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
14	8 Cyl 5.0L Eng. - 4.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
14	8 Cyl 5.8L Eng. - 4.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
13	8 Cyl 5.8L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13 - 11	6 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.0L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 10	8 Cyl 5.4L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl 4.0L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09	6 Cyl 4.0L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09	8 Cyl 4.6L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09	8 Cyl 5.4L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 07	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 05	All Eng. - 31.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04 - 97	All Eng. - 8.50 Oz. PAG-46; 34.00 Oz. R-134a	59007
96 - 94	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
93 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
85 - 83	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 71	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PINTO</b>		
73	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PROBE</b>		
97	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
96 - 94	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 28.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SPECIAL SERVICE POLICE SEDAN</b>		
17 - 14	4 Cyl 2.0L Eng. - 25.92 Oz. R-134a; 5.20 Oz. PAG-46	59007
<b>TAURUS</b>		
18	6 Cyl 3.5L Eng. - 22.88 Oz. R-134a; 5.24 Oz. PAG-46	59007
18 - 14	4 Cyl 2.0L Eng. - 25.92 Oz. R-134a; 5.24 Oz. PAG-46	59007
17 - 14	6 Cyl 3.5L Eng. - 26.08 Oz. R-134a; 5.24 Oz. PAG-46	59007
14	6 Cyl 3.7L Eng. - 7.00 Oz. PAG-46; 26.08 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
13 - 11	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
09 - 08	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07 - 96	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
95	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - Excl. SHO, 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - SHO, 8.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
93	All Eng. - Excl. SHO, 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - SHO, 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - Excl. SHO, 7.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
92	All Eng. - SHO, 8.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
91	6 Cyl Eng. - Excl. SHO, 7.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	4 Cyl 2.5L Eng. - 10.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	6 Cyl Eng. - SHO, 8.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
90	6 Cyl Eng. - Excl. SHO, 8.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
89	6 Cyl Eng. - Excl. SHO, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD

Year	Description	Lubricant
------	-------------	-----------

### TAURUS

89	6 Cyl Eng. - SHO, 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 87	4 Cyl 2.5L Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
88	6 Cyl 3.8L Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 3.0L Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>

### TEMPO

94	4 Cyl 2.3L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	6 Cyl 3.0L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
93 - 92	4 Cyl 2.3L Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	6 Cyl 3.0L Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 41.00 Oz. R-12	59000 <sup>(1)</sup>
84	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### THUNDERBIRD

05	8 Cyl 3.9L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04 - 02	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97 - 95	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93 - 89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	4 Cyl Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	6 Cyl Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12, To 1/86	59000 <sup>(1)</sup>
86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil, From 1/86	59000 <sup>(1)</sup>
85 - 83	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 72	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 72	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 72	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### TORINO

76 - 72	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 71	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### ZX2

03 - 01	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
00 - 98	4 Cyl 2.0L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

## FORD HD

Year	Description	Lubricant
------	-------------	-----------

### E SUPER DUTY

99 - 97	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
99 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
96	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007

### E450 SERIES VAN

18 - 17	8 Cyl 6.2L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
18 - 16	10 Cyl 6.8L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
16	8 Cyl 5.4L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	10 Cyl 6.8L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD HD

Year	Description	Lubricant
<b>E450 SERIES VAN</b>		
13 - 11	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - Diesel, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10 - 09	All Eng. - Gas, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10 - 08	All Eng. - Gas, w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10 - 08	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10 - 07	All Eng. - Gas, w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
08	All Eng. - Diesel, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
08	All Eng. - Diesel, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 07	All Eng. - Diesel, w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
07	10 Cyl 6.8L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
07	10 Cyl 6.8L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
07	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07	8 Cyl 6.0L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	All Eng. - Diesel, w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07	All Eng. - Gas, w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
07 - 04	8 Cyl 6.0L Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06	8 Cyl 5.4L Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06	8 Cyl 5.4L Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
06	8 Cyl 6.0L Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
06 - 04	10 Cyl 6.8L Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 04	10 Cyl 6.8L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06 - 02	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 02	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 04	8 Cyl 6.0L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
04	8 Cyl 5.4L Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
04	8 Cyl 5.4L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	10 Cyl 6.8L Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	10 Cyl 6.8L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 5.4L Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	8 Cyl 5.4L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 7.3L Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	8 Cyl 7.3L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02	8 Cyl 5.4L Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 46.00 Oz. R-134a	59007
02	8 Cyl 5.4L Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
01 - 99	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01 - 99	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
<b>E550 SERIES VAN</b>		
03	10 Cyl 6.8L Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	10 Cyl 6.8L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 7.3L Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03	8 Cyl 7.3L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>F SUPER DUTY</b>		
97	8 Cyl 7.3L Eng. - 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
97	8 Cyl 7.5L Eng. - 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
96	8 Cyl 7.3L Eng. - 11.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	8 Cyl 7.3L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
95	8 Cyl 7.5L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	8 Cyl 7.3L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	8 Cyl 7.5L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	8 Cyl 7.3L Eng. - 44.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
93	8 Cyl 7.5L Eng. - 44.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
92 - 90	8 Cyl 7.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 90	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F450 SERIES</b>		
15 - 11	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD HD

Year	Description	Lubricant
<b>F450 SERIES</b>		
13	10 Cyl 6.8L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
13 - 11	8 Cyl 6.7L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
12	10 Cyl 6.8L Eng. - 4.10 Oz. PAG-46; 27.20 Oz. R-134a	59007
11 - 10	10 Cyl 6.8L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
10	8 Cyl 6.4L Eng. - 9.00 Oz. PAG-46; 27.20 Oz. R-134a	59007
09	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	10 Cyl 6.8L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07	8 Cyl 6.0L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	10 Cyl 6.8L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06 - 04	10 Cyl 6.8L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05	8 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
05 - 04	10 Cyl 6.8L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl 6.0L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	10 Cyl 6.8L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03 - 00	10 Cyl 6.8L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 00	10 Cyl 6.8L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	10 Cyl 6.8L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	8 Cyl 7.3L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	8 Cyl 7.5L Eng. - 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
<b>F500</b>		
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F53</b>		
18 - 17	10 Cyl 6.8L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-134a	59007
16 - 14	10 Cyl 6.8L Eng. - 28.96 Oz. R-134a; 4.20 Oz. PAG-46	59007
13 - 11	10 Cyl 6.8L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
<b>F550 SERIES</b>		
15 - 11	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	10 Cyl 6.8L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
13 - 11	8 Cyl 6.7L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
12	10 Cyl 6.8L Eng. - 4.10 Oz. PAG-46; 27.20 Oz. R-134a	59007
11 - 10	10 Cyl 6.8L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
10	8 Cyl 6.4L Eng. - 9.00 Oz. PAG-46; 27.20 Oz. R-134a	59007
09	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	10 Cyl 6.8L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07	8 Cyl 6.0L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	10 Cyl 6.8L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06 - 04	10 Cyl 6.8L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05	8 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
05 - 04	10 Cyl 6.8L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD HD

Year	Description	Lubricant
<b>F550 SERIES</b>		
04	8 Cyl 6.0L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	10 Cyl 6.8L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03 - 00	10 Cyl 6.8L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 00	10 Cyl 6.8L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	10 Cyl 6.8L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
99	8 Cyl 7.3L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>F59</b>		
18 - 17	10 Cyl 6.8L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-134a	59007
16 - 14	10 Cyl 6.8L Eng. - 28.96 Oz. R-134a; 4.20 Oz. PAG-46	59007
13 - 11	10 Cyl 6.8L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
<b>F650 SERIES</b>		
15	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	10 Cyl 6.8L Eng. - 3.40 Oz. PAG-46; 26.08 Oz. R-134a	59007
13 - 11	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12	10 Cyl 6.8L Eng. - 4.10 Oz. PAG-46; 27.20 Oz. R-134a	59007
09	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	8 Cyl 6.0L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05	8 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
04	8 Cyl 6.0L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>F750 SERIES</b>		
15	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 11	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	All Eng. - 44.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	8 Cyl 6.0L Eng. - 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
06	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05	8 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
04	8 Cyl 6.0L Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
04	8 Cyl 6.0L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03	8 Cyl 6.0L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 00	8 Cyl 7.3L Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>AEROSTAR</b>		
97	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
96 - 94	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
96 - 94	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
93	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 64.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 46.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - w/o Rear AC; 56.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - w/ Rear AC; 13.00 Oz. Mineral; 60.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 13.00 Oz. Mineral; 56.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12, To 9/22/86	59000 <sup>(1)</sup>
87	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 60.00 Oz. R-12, From 9/22/86	59000 <sup>(1)</sup>
87	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12, To 9/22/86	59000 <sup>(1)</sup>
87	All Eng. - w/o Rear AC; 13.00 Oz. Mineral Oil; 56.00 Oz. R-12, From 9/22/86	59000 <sup>(1)</sup>
86	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>BRONCO</b>		
96	All Eng. - 8.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 11.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 91	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 52.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 80	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 78	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 78	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
77 - 76	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>BRONCO II</b>		
90	All Eng. - 10.00 Oz. Mineral Oil; 32.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 88	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
84	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CLUB WAGON</b>		
98 - 97	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
98 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 95	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
96 - 95	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
<b>E100 SERIES VAN</b>		
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 87	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
83 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 75	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>E150 SERIES VAN</b>		
13 - 11	8 Cyl 4.6L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 4.6L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>E150 SERIES VAN</b>		
10 - 09	All Eng. - Gas, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10 - 08	All Eng. - Gas, w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10 - 07	All Eng. - Gas, w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
07	All Eng. - Gas, w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
06 - 02	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 02	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 95	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 94	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
94	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 92	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 55.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 85	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 85	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
84	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 76	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>E250 SERIES VAN</b>		
13 - 11	8 Cyl 4.6L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 4.6L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
09	All Eng. - Gas, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
09 - 08	All Eng. - Gas, w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
09 - 07	All Eng. - Gas, w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07	All Eng. - Gas, w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
06 - 02	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 02	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 95	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 94	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
94	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 92	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 55.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 85	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 85	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>E300 SERIES VAN</b>		
88 - 86	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 86	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
<b>E350 SERIES VAN</b>		
18 - 17	8 Cyl 6.2L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>E350 SERIES VAN</b>		
18 - 16	10 Cyl 6.8L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
16	8 Cyl 5.4L Eng. - 30.40 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	10 Cyl 6.8L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - Diesel, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10 - 09	All Eng. - Gas, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10 - 08	All Eng. - Gas, w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10 - 07	All Eng. - Gas, w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - Gas, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
08	All Eng. - Diesel, w/ Rear AC; 11.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
08	All Eng. - Diesel, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 07	All Eng. - Diesel, w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
07	All Eng. - Diesel, w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07	All Eng. - Gas, w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
06 - 02	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 02	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 95	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96 - 94	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
94	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 92	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 55.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 85	All Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 85	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ECONOLINE, ECONOLINE VAN, ECONOLINE WAGON</b>		
13 - 11	8 Cyl 4.6L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 4.6L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 11	8 Cyl 5.4L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.4L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - Gas, w/ Rear AC; 16.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
10	All Eng. - Gas, w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - Gas, w/o Rear AC; 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 02	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 60.00 Oz. R-134a	59007
06 - 02	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
01 - 99	All Eng. - w/ Rear AC; 64.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
01 - 99	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
<b>ECOSPORT</b>		
18	4 Cyl 1.0L Eng. - Gas, 4.10 Oz. PAG-46; 26.40 Oz. R-1234yf	59234
18	4 Cyl 2.0L Eng. - Gas, 4.10 Oz. PAG-46; 15.20 Oz. R-1234yf	59234
<b>ESCAPE</b>		
14	4 Cyl 2.5L Eng. - 4.50 Oz. PAG-46; 27.20 Oz. R-134a	59007
14 - 13	4 Cyl 1.6L Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
14 - 13	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - w/ Tow Package; 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
13	4 Cyl 2.5L Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
12	2.5L Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
12	4 Cyl Eng. - Excl. Electric/Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>ESCAPE</b>		
11 - 10	4 Cyl 2.5L Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
11 - 10	All Eng. - Excl. Electric/Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
09	All Eng. - HYBRID, 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09 - 08	All Eng. - Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
08	All Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
07 - 05	4 Cyl 2.3L Eng. - Gas, 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 05	6 Cyl 3.0L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 05	4 Cyl 2.3L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04 - 01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>EXCURSION</b>		
05 - 01	All Eng. - w/o Rear AC; 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 00	All Eng. - w/ Rear AC; 68.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
00	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>EXPEDITION</b>		
18	6 Cyl 3.5L Eng. - 36.96 Oz. R-1234yf; 6.10 Oz. PAG Oil	59234
17 - 15	6 Cyl 3.5L Eng. - 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
14 - 11	8 Cyl 5.4L Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
09 - 08	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
08 - 07	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
07	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
06	All Eng. - w/ Rear AC; 14.00 Oz. PAG-46; 58.00 Oz. R-134a	59007
06	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 03	All Eng. - w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
05 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02 - 98	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 62.00 Oz. R-134a	59007
02 - 97	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
97	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 62.00 Oz. R-134a	59007
<b>EXPLORER</b>		
18	4 Cyl 2.3L Eng. - 44.96 Oz. R-134a; 7.30 Oz. PAG-46	59007
17 - 16	4 Cyl 2.3L Eng. - 44.96 Oz. R-134a; 8.80 Oz. PAG-46	59007
13 - 12	4 Cyl 2.0L Eng. - 47.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
13 - 11	6 Cyl 3.5L Eng. - 47.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
10	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
10 - 09	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
08 - 06	All Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 47.00 Oz. R-134a	59007
08 - 06	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
01 - 98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	All Eng. - 9.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
96 - 95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>EXPLORER SPORT</b>		
03 - 02	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
03 - 02	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
01	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>EXPLORER SPORT TRAC</b>		
10	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
10 - 09	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 47.00 Oz. R-134a	59007
08 - 07	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 34.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>EXPLORER SPORT TRAC</b>		
01	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>F100 SERIES</b>		
83 - 82	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 73	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 81	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 76	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 3.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F150, LOBO SERIES</b>		
18	6 Cyl 2.7L Eng. - 2.70 Oz. PAG-46; 28.96 Oz. R-1234yf	59234
18	6 Cyl 3.3L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
18	6 Cyl 3.3L Eng. - 28.96 Oz. R-1234yf; 3.40 Oz. PAG Oil	59234
18	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59234
18	6 Cyl 3.5L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-1234yf	59234
18	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
18	8 Cyl 5.0L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-1234yf	59234
18	8 Cyl 5.0L Eng. - 4.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59234
17	6 Cyl 2.7L Eng. - 4.10 Oz. PAG-46; w/ R134a Service Port; See Under Hood Decal for Refrigerant Capacity	59007
17	6 Cyl 2.7L Eng. - w/ R1234yf; 4.10 Oz. PAG; w/ R1234yf Service Port; See Under Hood Decal for Refrigerant Capacity	59234
17	6 Cyl 3.5L Eng. - 4.10 Oz. PAG-46; w/ R134a Service Port; See Under Hood Decal for Refrigerant Capacity	59007
17	6 Cyl 3.5L Eng. - 4.10 Oz. PAG; w/ R1234yf Service Port; See Under Hood Decal for Refrigerant Capacity	59234
17	8 Cyl 5.0L Eng. - 28.96 Oz. R-1234yf; 4.10 Oz. PAG; w/ R1234yf Service Port	59234
17	8 Cyl 5.0L Eng. - 4.10 Oz. PAG-46; w/ R134a Service Port; See Under Hood Decal for Refrigerant Capacity	59007
16	6 Cyl 2.7L Eng. - 31.00 Oz. R-134a; 3.38 Oz. PAG-46	59007
16	6 Cyl 3.5L Eng. - 31.00 Oz. R-134a; 3.38 Oz. PAG-46	59007
16	8 Cyl 5.0L Eng. - 31.00 Oz. R-134a; 3.38 Oz. PAG-46	59007
15	6 Cyl 2.7L Eng. - 4.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
15	6 Cyl 3.5L Eng. - 4.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
15	8 Cyl 5.0L Eng. - 4.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
14	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
14	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
14	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
14	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13 - 12	8 Cyl 6.2L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
12 - 11	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
12 - 11	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
12 - 11	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	All Eng. - F-150 Light Duty, 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	All Eng. - F-150 Light Duty, F-250 Light Duty, 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 06	All Eng. - F-150 Light Duty, F-250 Light Duty, 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
05	All Eng. - F-150 Light Duty, F-250 Light Duty, 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
04	All Eng. - F-150 Light Duty, 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
03 - 98	All Eng. - F-150 Light Duty, F-250 Light Duty, 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>F150, LOBO SERIES</b>		
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 86	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
84	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 76	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F200</b>		
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 86	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F250 SERIES</b>		
18 - 17	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 27.20 Oz. R-134a	59007
18 - 16	8 Cyl 6.7L Eng. - Diesel, 27.20 Oz. R-134a; 3.50 Oz. PAG-46	59007
15	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-134a	59007
15 - 14	8 Cyl 6.7L Eng. - Diesel, 4.10 Oz. PAG-46; 26.08 Oz. R-134a	59007
14	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 12	8 Cyl 6.2L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 11	8 Cyl 6.7L Eng. - 3.40 Oz. PAG-46; 26.00 Oz. R-134a	59007
11	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10 - 09	All Eng. - Super Duty, 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	All Eng. - F-150 Light Duty, F-250 Light Duty, 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08	All Eng. - Super Duty, 26.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
08 - 06	All Eng. - F-150 Light Duty, F-250 Light Duty, 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
07 - 06	All Eng. - Super Duty, 9.00 Oz. PAG-46; 45.00 Oz. R-134a	59007
05	All Eng. - F-150 Light Duty, F-250 Light Duty, 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 99	All Eng. - Super Duty, 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
03 - 98	All Eng. - F-150 Light Duty, F-250 Light Duty, 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 86	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 73	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 76	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 3.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>F250 SERIES</b>		
72 - 70	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>F350 SERIES</b>		
18 - 17	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 27.20 Oz. R-134a	59007
18 - 16	8 Cyl 6.7L Eng. - Diesel, 27.20 Oz. R-134a; 3.50 Oz. PAG-46	59007
15	8 Cyl 6.2L Eng. - 4.10 Oz. PAG-46; 28.96 Oz. R-134a	59007
15 - 14	8 Cyl 6.7L Eng. - Diesel, 4.10 Oz. PAG-46; 26.08 Oz. R-134a	59007
14	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 12	8 Cyl 6.2L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 11	8 Cyl 6.7L Eng. - 3.40 Oz. PAG-46; 26.00 Oz. R-134a	59007
11	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10 - 09	All Eng. - Super Duty, 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
08	All Eng. - Super Duty, 26.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
07 - 06	All Eng. - Super Duty, 9.00 Oz. PAG-46; 45.00 Oz. R-134a	59007
05 - 98	All Eng. - Super Duty, 42.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
95	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 44.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 86	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	8 Cyl 6.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 77	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 73	6 Cyl 4.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 76	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 3.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FLEX</b>		
13 - 11	6 Cyl 3.5L Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
10	All Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
09	6 Cyl 3.5L Eng. - 11.00 Oz. PAG-46; 36.00 Oz. R-134a	59007
<b>FREESTAR</b>		
07 - 04	All Eng. - w/ Rear AC; 13.00 Oz. PAG-46; 53.00 Oz. R-134a	59007
07 - 04	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
<b>FREESTYLE</b>		
07 - 05	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
07 - 05	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>LOBO</b>		
13	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13 - 12	8 Cyl 6.2L Eng. - 29.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
12 - 11	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11	8 Cyl 6.2L Eng. - 24.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	All Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 06	All Eng. - 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
05 - 01	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
<b>POLICE INTERCEPTOR UTILITY</b>		
17 - 16	6 Cyl 3.7L Eng. - 26.08 Oz. R-134a; 5.20 Oz. PAG-46; w/ Front AC	59007
17 - 16	6 Cyl 3.7L Eng. - 38.08 Oz. R-134a; 7.90 Oz. PAG-46; w/ Front and Rear AC	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## FORD LIGHT TRUCK

Year	Description	Lubricant
<b>RANGER</b>		
10	4 Cyl 2.3L Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
10	6 Cyl 4.0L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	4 Cyl 2.3L Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
09	6 Cyl 4.0L Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
08 - 06	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 03	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02 - 98	All Eng. - Gas, 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97 - 95	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
94	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	4 Cyl 2.3L Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	6 Cyl 2.9L Eng. - 10.00 Oz. Mineral Oil; 32.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	6 Cyl 3.0L Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	6 Cyl 4.0L Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
90	All Eng. - 10.00 Oz. Mineral Oil; 32.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 88	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 83	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## TAURUS X

09 - 08	All Eng. - w/ Rear AC; 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
09 - 08	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

## Transit Connect

12	4 Cyl 2.0L Eng. - 29.06 Oz. R-134a; 6.09 Oz. PAG-46	59007
12	All Eng. - Electric, 29.00 Oz. R-134a	59889
11	4 Cyl 2.0L Eng. - 29.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
10	4 Cyl 2.0L Eng. - 29.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

## WINDSTAR

03 - 01	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
03 - 01	All Eng. - w/o Rear AC; 10.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
00 - 99	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
00 - 98	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
98 - 97	All Eng. - w/o Rear AC; 10.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
97	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 14.00 Oz. PAG-46	59007
96 - 95	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
96 - 95	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 44.00 Oz. R-134a	59007

## GEO

Year	Description	Lubricant
<b>METRO</b>		
97	All Eng. - 21.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
96 - 94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
94	3 Cyl 1.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
94	4 Cyl 1.3L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
93 - 90	All Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	3 Cyl 1.0L Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>PRIZM</b>		
97	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
96 - 95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
94	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
93	All Eng. - 24.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 6.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90	All Eng. - 18.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	4 Cyl 1.6L Eng. - 24.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GEO

Year	Description	Lubricant
<b>SPECTRUM</b>		
89	All Eng. - 29.00 Oz. R-12; 3.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>STORM</b>		
93 - 92	All Eng. - 21.00 Oz. R-12; 5.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 90	All Eng. - 24.00 Oz. R-12; 5.25 Oz. Mineral Oil	59000 <sup>(1)</sup>

## GMC HD

Year	Description	Lubricant
<b>C3500HD</b>		
02 - 00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 91	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>1000</b>		
66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>1500</b>		
66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>2500</b>		
66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>3000</b>		
66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>3500</b>		
66	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
65	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ACADIA</b>		
16 - 14	6 Cyl 3.6L Eng. - 40.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
12 - 08	6 Cyl 3.6L Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
07	All Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>C15, C1500 SERIES</b>		
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 67	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>C25, C2500 SERIES</b>		
00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 67	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>C35, C3500 SERIES</b>		
02 - 00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Crew Cab, 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Crew Cab, 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Crew Cab, 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 67	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CABALLERO</b>		
87 - 85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CANYON</b>		
18 - 16	4 Cyl 2.8L Eng. - Diesel, 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
18 - 15	4 Cyl 2.5L Eng. - 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
18 - 15	6 Cyl 3.6L Eng. - 28.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
12 - 09	4 Cyl 2.9L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 09	5 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 09	8 Cyl 5.3L Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07 - 06	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 04	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>ENVOY</b>		
09	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09 - 08	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
08	All Eng. - w/ Rear AC; 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
07 - 06	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
07 - 05	All Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>ENVOY XL</b>		
06	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
06 - 05	All Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
<b>ENVOY XUV</b>		
05	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
04	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
<b>G15, G1500 SERIES VAN</b>		
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 68.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 68.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 80	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>G20, G2500 SERIES VAN</b>		
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 68.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 68.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.0L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>G20, G2500 SERIES VAN</b>		
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 80	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 74	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 75	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>G35, G3500 SERIES VAN</b>		
96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 78.00 Oz. R-134a	59007
96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 78.00 Oz. R-134a	59003
96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 68.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 68.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	6 Cyl 4.3L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/ Rear AC; 72.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 6.2L Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 64.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/ Rear AC; 64.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 10.00 Oz. Mineral Oil; 46.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	8 Cyl 7.4L Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ HR6/DA6 Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 72.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 80	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>G35, G3500 SERIES VAN</b>		
84 - 82	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 74	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>JIMMY</b>		
05 - 04	6 Cyl 4.3L Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05 - 02	6 Cyl 4.3L Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
03 - 01	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00 - 99	All Eng. - w/ Denso Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
00 - 99	All Eng. - w/ OE Harrison Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-150	59003
98 - 96	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 96	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 90	All Eng. - FullSize Jimmy, w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - FullSize Jimmy, w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - Jimmy (Mid Size / S15 / T15), 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - FullSize Jimmy, w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - FullSize Jimmy, w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - Jimmy (Mid Size / S15 / T15), 8.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - Jimmy (Mid Size / S15 / T15), 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>K1000 SERIES</b>		
66	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>K15, K1500 SERIES</b>		
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>K15, K1500 SERIES</b>		
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 66	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 66	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>K25, K2500 SERIES</b>		
00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 67	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 67	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 67	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>K35 / K3500 SERIES</b>		
00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Crew Cab, w/ Denso Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Crew Cab, w/ OE Harrison Compressor; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>K35 / K3500 SERIES</b>		
95 - 94	All Eng. - Crew Cab, 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - Std Cab / Ext Cab, 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Crew Cab, 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Crew Cab, 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Std Cab / Ext Cab, 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 70	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 69	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 68	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	6 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	6 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>P SERIES VAN</b>		
99 - 94	6 Cyl 4.3L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	6 Cyl 4.3L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 5.7L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 6.5L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 6.5L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
99 - 94	8 Cyl 7.4L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
99 - 94	8 Cyl 7.4L Eng. - w/ OE Harrison Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 5.7L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	8 Cyl 5.7L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
93	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
<b>R1500 SERIES</b>		
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>R2500 SERIES</b>		
89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>R3500 SERIES</b>		
91 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>S15 - PICKUP</b>		
90 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SAFARI</b>		
05 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
05 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
05 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
05 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 60.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 86	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - w/ Rear AC; 48.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SAVANA 1500</b>		
12	6 Cyl 4.3L Eng. - 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 5.3L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 5.3L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11	All Eng. - 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
10	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/o Rear AC; 11.00 Oz. PAG-46; 32.00 Oz. R-134a	59007
08 - 06	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
08 - 05	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 28.80 Oz. R-134a	59007
05 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
04 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
02	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
01	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 72.00 Oz. R-134a	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
00 - 97	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 97	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 78.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 78.00 Oz. R-134a	59003
96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SAVANA 2500</b>		
12	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 4.8L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.0L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.6L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11	All Eng. - 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
10	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/o Rear AC; 11.00 Oz. PAG-46; 32.00 Oz. R-134a	59007
08 - 06	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
08 - 05	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 28.80 Oz. R-134a	59007
05 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
04 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
02	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SAVANA 2500</b>		
01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
01	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 72.00 Oz. R-134a	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
00 - 97	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 97	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 78.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 78.00 Oz. R-134a	59003
96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SAVANA 3500</b>		
12	8 Cyl 4.8L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 4.8L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.0L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.0L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12	8 Cyl 6.6L Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
12	8 Cyl 6.6L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
11	All Eng. - 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
10	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
10	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	All Eng. - w/o Rear AC; 11.00 Oz. PAG-46; 32.00 Oz. R-134a	59007
08 - 06	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
08 - 05	All Eng. - w/o Rear AC; 8.00 Oz. PAG-46; 28.80 Oz. R-134a	59007
05 - 03	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
04 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
02	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
01	All Eng. - w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 72.00 Oz. R-134a	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 72.00 Oz. R-134a	59003
00 - 97	All Eng. - w/ Denso Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 97	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 78.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 78.00 Oz. R-134a	59003
96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SIERRA</b>		
18 - 17	8 Cyl 5.3L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.2L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 15	8 Cyl 5.3L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 15	8 Cyl 6.2L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 09	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
<b>SIERRA 1500</b>		
18 - 17	6 Cyl 4.3L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 5.3L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.2L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 15	6 Cyl 4.3L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 15	8 Cyl 5.3L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 15	8 Cyl 6.2L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 09	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SIERRA 1500</b>		
06 - 03	All Eng. - w/ Denso Compressor; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SIERRA 2500</b>		
18 - 17	8 Cyl 6.0L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.0L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.6L Eng. - Diesel, 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.6L Eng. - Diesel, 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
12 - 09	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	8 Cyl 8.1L Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Denso Compressor; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
99	All Eng. - Std Cab / Ext Cab, w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99	All Eng. - Std Cab / Ext Cab, w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SIERRA 3500</b>		
18 - 17	8 Cyl 6.0L Eng. - 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.0L Eng. - 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 17	8 Cyl 6.6L Eng. - Diesel, 22.40 Oz. R-134a; 6.10 Oz. PAG-46	59007
18 - 17	8 Cyl 6.6L Eng. - Diesel, 6.10 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
12 - 09	All Eng. - w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 07	All Eng. - w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
07	8 Cyl 8.1L Eng. - w/ Denso Compressor; w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Denso Compressor; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 01	All Eng. - w/ Denso Compressor; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 01	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 01	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>SONOMA</b>		
04 - 99	All Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04 - 99	All Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98 - 96	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 96	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SUBURBAN C15, C1500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN C15, C1500</b>		
72 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN C25, C2500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 7.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN K15, K1500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN K25, K2500</b>		
99 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
99 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
99 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	6 Cyl 4.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN K25, K2500</b>		
72 - 71	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUBURBAN R1500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/o Rear AC; 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.0L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.0L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SUBURBAN R2500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/o Rear AC; 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 7.4L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 7.4L Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 7.4L Eng. - w/o Rear AC; 11.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 7.4L Eng. - w/o Rear AC; 52.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SUBURBAN V1500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/o Rear AC; 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SUBURBAN V2500</b>		
91 - 90	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 84.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 60.00 Oz. R-12	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>SUBURBAN V2500</b>		
88	8 Cyl 5.7L Eng. - 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
88	8 Cyl 5.7L Eng. - w/o Rear AC; 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, 54.40 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	8 Cyl 6.2L Eng. - Diesel, w/ Rear AC; 6.00 Oz. Mineral Oil; 86.40 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 5.7L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 88.00 Oz. R-12	59000 <sup>(1)</sup>
87	8 Cyl 6.2L Eng. - w/o Rear AC; 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SYCLONE</b>		
92 - 91	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>TERRAIN</b>		
18	4 Cyl 1.5L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 1.5L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
18	4 Cyl 1.6L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 1.6L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
18	4 Cyl 2.0L Eng. - 14.56 Oz. R-1234yf; 5.01 Oz. PAG Oil	59234
18	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; 5.01 Oz. PAG-46	59007
17 - 14	4 Cyl 2.4L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 22.88 Oz. R-134a	59007
12 - 10	4 Cyl 2.4L Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 10	6 Cyl 3.0L Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>TYPHOON</b>		
93 - 92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>V1500 SERIES</b>		
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>V2500 SERIES</b>		
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>V3500 SERIES</b>		
91 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 48.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
68	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>YUKON</b>		
18 - 17	8 Cyl 5.3L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
16 - 15	8 Cyl 6.2L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 6.2L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
14	8 Cyl 6.2L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
12	6.0L Eng. - Electric/Gas, 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
12	8 Cyl 5.3L Eng. - Yukon, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
12	8 Cyl 6.2L Eng. - Yukon DENALI, AWD, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
12 - 10	8 Cyl 5.3L Eng. - Yukon, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
11	8 Cyl 6.0L Eng. - Electric/Gas, Yukon, 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
11	8 Cyl 6.2L Eng. - Yukon DENALI, AWD, w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
10 - 09	8 Cyl 6.0L Eng. - HYBRID, Yukon, 40.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
09	8 Cyl 4.8L Eng. - Gas, Yukon, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, Yukon, w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
09	8 Cyl 5.3L Eng. - Excl. Hybrid, Yukon, w/o Rear AC; 25.60 Oz. R-134a; 7.10 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>YUKON</b>		
08	6.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
08	All Eng. - Excl. Hybrid, Yukon, w/ Rear AC; 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
07	All Eng. - Yukon, w/ Rear AC; 40.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
07 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
06 - 03	All Eng. - Yukon, w/ Rear AC; 11.00 Oz. PAG-46; 43.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02	All Eng. - Yukon, w/ Rear AC; 11.00 Oz. PAG-46; 42.00 Oz. R-134a	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - Yukon, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
00 - 96	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00 - 96	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 96	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00 - 96	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
95 - 94	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 68.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 6.00 Oz. Mineral Oil; 44.80 Oz. R-12	59000 <sup>(1)</sup>
<b>YUKON XL</b>		
18 - 17	8 Cyl 5.3L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
16 - 15	8 Cyl 6.2L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 6.2L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
<b>Yukon XL 1500 ( 1/2 Ton)</b>		
18 - 17	8 Cyl 5.3L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	8 Cyl 6.2L Eng. - 28.80 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 5.3L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
16 - 15	8 Cyl 6.2L Eng. - 29.92 Oz. R-1234yf; w/ Front and Rear AC; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	8 Cyl 6.2L Eng. - 32.48 Oz. R-134a; 6.60 Oz. PAG-46; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 5.3L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
14	8 Cyl 6.2L Eng. - 11.00 Oz. PAG-46; 40.00 Oz. R-134a; w/ Front and Rear AC	59007
14	8 Cyl 6.2L Eng. - 25.60 Oz. R-134a; 7.10 Oz. PAG -46; w/ Front AC	59007
12	8 Cyl 6.2L Eng. - Yukon DENALI XL, AWD, w/ Rear AC; 11.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.3L Eng. - Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
11 - 10	8 Cyl 6.2L Eng. - Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 6.0L Eng. - Gas, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 6.2L Eng. - Flex, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08	8 Cyl 6.0L Eng. - Gas, w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
08	All Eng. - Excl. Hybrid, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
07 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
07 - 01	All Eng. - Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>Yukon XL 2500 (3/4 Ton)</b>		
12 - 11	8 Cyl 6.0L Eng. - Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
10	8 Cyl 6.0L Eng. - Flex, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
09	8 Cyl 6.0L Eng. - Gas, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
08	8 Cyl 6.0L Eng. - Gas, w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
08	All Eng. - Excl. Hybrid, Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## GMC LIGHT TRUCK

Year	Description	Lubricant
<b>Yukon XL 2500 (3/4 Ton)</b>		
07 - 03	All Eng. - w/o Rear AC; 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
07 - 01	All Eng. - Yukon XL, w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
02	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 64.00 Oz. R-134a	59007
00	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 64.00 Oz. R-134a	59003
00	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

## HONDA

Year	Description	Lubricant
<b>ACCORD</b>		
18	4 Cyl 1.5L Eng. - 14.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18	4 Cyl 2.0L Eng. - Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
17	4 Cyl 2.0L Eng. - 16.80 Oz. R-134a; 2.30 Oz. Hybrid Oil	59889
17 - 14	4 Cyl 2.4L Eng. - 16.80 Oz. R-134a; 2.30 Oz. PAG-46	59007
17 - 14	6 Cyl 3.5L Eng. - 16.80 Oz. R-134a; 2.30 Oz. PAG-46	59007
15	4 Cyl 2.0L Eng. - 16.80 Oz. R-134a; 2.30 Oz. Hybrid Oil	59889
14	4 Cyl 2.0L Eng. - Electric/Gas, 16.80 Oz. R-134a; 2.30 Oz. Hybrid Oil	59889
13	4 Cyl 2.4L Eng. - 17.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - 17.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
12	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
11	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
10	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
10	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 05	All Eng. - Gas, 19.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
07 - 05	All Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
04 - 03	All Eng. - 19.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
02 - 98	All Eng. - 23.00 Oz. R-134a; 8.45 Oz. PAG-46	59007
97 - 94	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 90	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 30.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	All Eng. - 7.50 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 8.00 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 79	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CIVIC</b>		
17 - 16	4 Cyl 1.5L Eng. - 15.04 Oz. R-1234yf; 2.50 Oz. PAG Oil	59234
17 - 16	4 Cyl 2.0L Eng. - 15.04 Oz. R-1234yf; 2.50 Oz. PAG Oil	59234
15 - 14	4 Cyl 1.5L Eng. - 2.30 Oz. Hybrid Oil; See Under Hood Decal for Refrigerant Capacity	59889
15 - 14	4 Cyl 1.8L Eng. - 15.04 Oz. R-134a; 2.50 Oz. PAG-46	59007
15 - 14	4 Cyl 2.4L Eng. - 15.04 Oz. R-134a; 2.50 Oz. PAG-46	59007
13 - 12	4 Cyl 1.5L Eng. - HYBRID, 15.00 Oz. R-134a; 8.10 Oz. Hybrid Oil	59889
13 - 12	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 15.00 Oz. R-134a	59007
13 - 12	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 15.00 Oz. R-134a	59007
11	4 Cyl 1.3L Eng. - HYBRID, 16.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
11	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
11	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
10	4 Cyl 1.3L Eng. - HYBRID, 16.00 Oz. R-134a; 8.11-8.45 Oz. Hybrid Oil	59889
10	4 Cyl 1.8L Eng. - 5.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
10	4 Cyl 2.0L Eng. - 5.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
09 - 06	All Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
09 - 06	All Eng. - Excl. Hybrid, 5.50 Oz. PAG-46; 15.00 Oz. R-134a	59007
05 - 02	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01 - 96	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95 - 94	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HONDA

Year	Description	Lubricant
<b>CIVIC</b>		
93	All Eng. - 5.00 Oz. Mineral Oil; 22.00 Oz. R-12	59000 <sup>(1)</sup>
92	All Eng. - 5.00 Oz. Mineral Oil; 23.00 Oz. R-12	59000 <sup>(1)</sup>
91	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - w/ Matsushita Compressor; 33.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 31.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 31.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 24.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - w/ Matsushita Compressor; 34.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 7.50 Oz. Mineral Oil; 25.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 30.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 7.50 Oz. Mineral Oil; 20.00 Oz. R-12	59000 <sup>(1)</sup>
84	4 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CIVIC DEL SOL</b>		
97 - 94	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 5.00 Oz. Mineral Oil; 23.00 Oz. R-12	59000 <sup>(1)</sup>
<b>CR-V</b>		
18 - 17	4 Cyl 1.5L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	4 Cyl 2.4L Eng. - 16.80 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16 - 14	4 Cyl 2.4L Eng. - 15.04 Oz. R-134a; 2.70 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
10	4 Cyl 2.4L Eng. - 17.00 Oz. R-134a; 6.42-6.76 Oz. PAG-46	59007
09	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 4.33-5.00 Oz. PAG-46	59007
03 - 02	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01 - 97	All Eng. - 4.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>CR-Z</b>		
16 - 14	4 Cyl 1.5L Eng. - 16.64 Oz. R-134a; 2.70 Oz. PAG-46	59007
13 - 12	4 Cyl 1.5L Eng. - HYBRID, 18.00 Oz. R-134a; 2.70 Oz. Hybrid Oil	59889
11	4 Cyl 1.5L Eng. - 18.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>CROSSTOUR</b>		
15 - 14	4 Cyl 2.4L Eng. - 15.04 Oz. R-134a; 2.40 Oz. PAG-46	59007
15 - 14	6 Cyl 3.5L Eng. - 15.04 Oz. R-134a; 2.40 Oz. PAG-46	59007
13 - 12	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
13 - 12	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; 2.37-2.77 Oz. PAG-46	59007
<b>CRX</b>		
14	4 Cyl 1.5L Eng. - 4.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
91 - 90	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - w/ Matsushita Compressor; 32.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 30.00 Oz. R-12; 7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 7.50 Oz. Mineral Oil; 20.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ELEMENT</b>		
11	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 8.11-8.45 Oz. PAG-46	59007
09	4 Cyl 2.4L Eng. - 17.60-19.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 03	All Eng. - 18.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>FIT</b>		
18 - 15	4 Cyl 1.5L Eng. - 14.40 Oz. R-134a; 4.80 Oz. PAG-46	59007
13 - 12	4 Cyl 1.5L Eng. - 15.00 Oz. R-134a; 2.71-3.04 Oz. PAG-46	59007
11	4 Cyl 1.5L Eng. - 4.00 Oz. PAG-46; 14.00 Oz. R-134a	59007
10 - 07	All Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>INSIGHT</b>		
14	4 Cyl 1.3L Eng. - 16.64 Oz. R-134a; 5.80 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HONDA

Year	Description	Lubricant
<b>INSIGHT</b>		
13 - 12	4 Cyl 1.3L Eng. - HYBRID, 18.00 Oz. R-134a; 2.71-3.04 Hybrid Oil	59889
11	4 Cyl 1.3L Eng. - HYBRID, 18.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
10	4 Cyl 1.3L Eng. - HYBRID, 17.00 Oz. R-134a; 5.41-5.74 Oz. Hybrid Oil	59889
06 - 00	All Eng. - 19.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>ODYSSEY</b>		
18	6 Cyl 3.5L Eng. - 20.96 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 14	6 Cyl 3.5L Eng. - PAG-46; 25.96 Oz. R-134a	59007
13 - 12	6 Cyl 3.5L Eng. - 27.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 24.70-26.50 Oz. R-134a	59007
10	6 Cyl 3.5L Eng. - 24.70-26.50 Oz. R-134a; 7.60-8.01 Oz. PAG-46	59007
09	6 Cyl 3.5L Eng. - 24.70-26.50 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 07	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
06 - 99	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 99	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98 - 95	All Eng. - w/ Rear AC; 30.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
98 - 95	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
<b>PASSPORT</b>		
02 - 94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>PILOT</b>		
18 - 16	6 Cyl 3.5L Eng. - 1.40 Oz. PAG Oil; 24.80 Oz. R-1234yf	59234
15 - 14	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 22.40 Oz. R-134a	59007
13 - 12	6 Cyl 3.5L Eng. - 23.00 Oz. R-134a; 4.23-4.63 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 21.10-2.90 Oz. R-134a; 8.62 Oz. PAG-46	59007
09	6 Cyl 3.5L Eng. - 21.20-22.90 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 03	All Eng. - 9.00 Oz. PAG-46; 24.70-26.50 Oz. R-134a	59007
<b>PRELUDE</b>		
01 - 97	All Eng. - 4.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
96 - 95	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94 - 93	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	4 Cyl 2.2L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	4 Cyl 2.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	All Eng. - 5.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
91	All Eng. - 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 32.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 8.00 Oz. Mineral Oil; 25.00 Oz. R-12	59000 <sup>(1)</sup>
<b>RIDGELINE</b>		
18 - 17	6 Cyl 3.5L Eng. - 21.60 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
14	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
13 - 11	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 7.60-8.01 Oz. PAG-46	59007
09	6 Cyl 3.5L Eng. - 20.30-22.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
07 - 06	All Eng. - 23.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>S2000</b>		
09	4 Cyl 2.2L Eng. - 14.10-15.90 Oz. R-134a; 6.90 Oz. PAG-46	59007
08	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
07 - 06	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05 - 00	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>WAGOVAN</b>		
89 - 86	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HUMMER (AM GENERAL)

Year	Description	Lubricant
<b>H2</b>		
08 - 06	All Eng. - 25.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 03	All Eng. - 25.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>H3</b>		
09	5 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

## HYUNDAI

Year	Description	Lubricant
<b>ACCENT</b>		
17 - 14	4 Cyl 1.6L Eng. - 4.50 Oz. PAG-46; 14.72 Oz. R-134a	59007
12	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11 - 08	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
07 - 06	All Eng. - 4.50 Oz. PAG-46; 18.50 Oz. R-134a	59007
05 - 02	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01 - 96	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007

## AZERA

17 - 14	6 Cyl 3.3L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12	6 Cyl 3.3L Eng. - 18.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	6 Cyl 3.3L Eng. - 18.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
11	6 Cyl 3.8L Eng. - 18.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10 - 08	6 Cyl 3.8L Eng. - 17.60+/-0.88 Oz. R-134a; 5.70+/-0.33 Oz. PAG-46	59007
10 - 07	6 Cyl 3.3L Eng. - 17.60+/-0.88 Oz. R-134a; 5.70+/-0.33 Oz. PAG-46	59007
07	6 Cyl 3.8L Eng. - 18.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06	All Eng. - 4.50 Oz. PAG-46; 18.50 Oz. R-134a	59007

## ELANTRA

17	4 Cyl 1.4L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
17	4 Cyl 1.6L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
17 - 14	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
16 - 14	4 Cyl 1.8L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 11	4 Cyl 1.8L Eng. - 18.50 Oz. R-134a; 3.52-4.20 Oz. PAG-46	59007
12 - 11	4 Cyl 2.0L Eng. - 18.50 Oz. R-134a; 3.52-4.20 Oz. PAG-46	59007
10 - 08	4 Cyl 2.0L Eng. - 17.60+/-0.88 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
07	All Eng. - 4.50 Oz. PAG-46; 18.50 Oz. R-134a	59007
06 - 01	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 96	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95 - 94	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93 - 92	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## ENTOURAGE

08	6 Cyl 3.8L Eng. - 7.10 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	All Eng. - 4.50 Oz. PAG-46; 18.50 Oz. R-134a	59007

## EQUUS

16 - 14	8 Cyl 5.0L Eng. - 4.40 Oz. PAG-46; 22.88 Oz. PAG-46	59007
13 - 12	8 Cyl 5.0L Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	8 Cyl 4.6L Eng. - 23.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007

## EXCEL

94	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 33.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 5.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## GENESIS

16 - 15	8 Cyl 5.0L Eng. - 22.88 Oz. R-134a; 4.30 Oz. PAG-46	59007
16 - 14	6 Cyl 3.8L Eng. - 22.88 Oz. R-134a; 4.30 Oz. PAG-46	59007
13	6 Cyl 3.8L Eng. - 20.10+/-0.88 Oz. R-134a; 5.07 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HYUNDAI

Year	Description	Lubricant
<b>GENESIS</b>		
13	8 Cyl 5.0L Eng. - 22.90+/-0.88 Oz. R-134a; 4.05 Oz. PAG-46	59007
12	6 Cyl 3.8L Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
12	8 Cyl 4.6L Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
12	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
11	6 Cyl 3.8L Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	8 Cyl 4.6L Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10 - 09	6 Cyl 3.8L Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10 - 09	8 Cyl 4.6L Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
<b>GENESIS COUPE</b>		
16 - 14	6 Cyl 3.8L Eng. - 20.00 Oz. R-134a; 5.60 Oz. PAG-46	59007
14	6 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 5.60 Oz. PAG-46	59007
13 - 11	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.60-5.60 Oz. PAG-46	59007
13 - 11	6 Cyl 3.8L Eng. - 20.00 Oz. R-134a; 4.60-5.60 Oz. PAG-46	59007
10	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.56-5.78 Oz. PAG-46	59007
10	6 Cyl 3.8L Eng. - 20.00 Oz. R-134a; 3.80 Oz. PAG-46	59007
<b>SANTA FE / SANTA FE Sport / SANTA FE 7</b>		
18 - 17	4 Cyl 2.0L Eng. - SPORT, 4.23 Oz. PAG-46; 21.60 Oz. R-134a	59007
18 - 17	4 Cyl 2.4L Eng. - SPORT, 4.23 Oz. PAG-46; 21.60 Oz. R-134a	59007
16 - 14	4 Cyl 2.0L Eng. - SPORT, 21.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
16 - 14	4 Cyl 2.4L Eng. - SPORT, 21.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
16 - 14	6 Cyl 3.3L Eng. - 21.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
12	6 Cyl 3.5L Eng. - 23.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
09	6 Cyl 2.7L Eng. - w/ Rear AC; 30.00 Oz. R-134a; 6.62-7.43 Oz. PAG-46	59007
09	6 Cyl 2.7L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
09	6 Cyl 3.3L Eng. - 22.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
09	6 Cyl 3.3L Eng. - w/ Rear AC; 30.00 Oz. R-134a; 6.62-7.43 Oz. PAG-46	59007
08	6 Cyl 2.7L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 7.10+/-0.33 Oz. PAG-46	59007
08	6 Cyl 2.7L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
08	6 Cyl 3.3L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 7.10+/-0.33 Oz. PAG-46	59007
08	6 Cyl 3.3L Eng. - w/o Rear AC; 22.00 Oz. R-134a; 5.07+/-0.33 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 7.50 Oz. PAG-46; 30.50 Oz. R-134a	59007
07	All Eng. - w/o Rear AC; 5.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
06 - 01	All Eng. - 5.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>SANTA FE XL</b>		
16 - 14	6 Cyl 3.3L Eng. - 21.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
<b>SCOUPE</b>		
95 - 94	All Eng. - 5.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
93	All Eng. - 30.00 Oz. R-12; 3.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 33.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SONATA</b>		
18	4 Cyl 1.6L Eng. - 16.80 Oz. R-1234yf; 3.00 Oz. PAG Oil	59234
18	4 Cyl 2.0L Eng. - 16.80 Oz. R-1234yf; 3.00 Oz. PAG Oil	59234
18	4 Cyl 2.4L Eng. - 16.80 Oz. R-1234yf; 3.00 Oz. PAG Oil	59234
17	4 Cyl 1.6L Eng. - 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	4 Cyl 2.0L Eng. - Gas, 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 3.00 Oz. PAG Oil	59007
17 - 16	4 Cyl 2.0L Eng. - Electric/Gas, 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
16	4 Cyl 1.6L Eng. - 3.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
16	4 Cyl 2.0L Eng. - Gas, 3.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
16	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 3.00 Oz. PAG-46	59007
15	4 Cyl 1.6L Eng. - 3.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
15	4 Cyl 2.0L Eng. - 3.00 Oz. PAG-46; 19.36 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HYUNDAI

Year	Description	Lubricant
<b>SONATA</b>		
15	4 Cyl 2.4L Eng. - Electric/Gas, 19.36 Oz. R-134a; 3.00 Oz. POE Oil	59889
15	4 Cyl 2.4L Eng. - Gas, 3.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
14	4 Cyl 2.0L Eng. - 19.36 Oz. R-134a; 5.40 Oz. PAG-46	59007
14	4 Cyl 2.4L Eng. - Electric/Gas, 19.36 Oz. R-134a; 5.40 Oz. POE Oil	59889
14	4 Cyl 2.4L Eng. - Gas, 19.36 Oz. R-134a; 5.40 Oz. PAG-46	59007
13 - 12	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
13 - 12	4 Cyl 2.4L Eng. - Gas, 20.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
12 - 11	4 Cyl 2.4L Eng. - Electric/Gas, 19.00 Oz. R-134a; 4.73-5.41 Oz. Hybrid Oil	59889
11	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - Gas, 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
10 - 09	6 Cyl 3.3L Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
08	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
08	6 Cyl 3.3L Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
07	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
07	6 Cyl 3.3L Eng. - 19.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
06	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
05	4 Cyl 2.4L Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
05	6 Cyl 2.7L Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
05 - 01	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
00 - 99	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
98 - 96	All Eng. - 27.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
95	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
94 - 89	All Eng. - 33.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>TIBURON</b>		
08	4 Cyl 2.0L Eng. - 18.00+/-0.88 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
08	6 Cyl 2.7L Eng. - 18.00+/-0.88 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
07	All Eng. - 21.00 Oz. R-134a; 4.73-5.41 Oz. PAG-46	59007
06	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
05 - 03	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 99	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
98 - 97	4 Cyl 2.0L Eng. - 25.00 Oz. R-134a; 5.74-6.42 Oz. PAG-46	59007
97	4 Cyl 1.8L Eng. - 25.00 Oz. R-134a; 5.74-6.42 Oz. PAG-46	59007
<b>TUCSON</b>		
17 - 16	4 Cyl 1.6L Eng. - 20.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
17 - 16	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
17 - 16	All Eng. - Electric/Hydrogen, 20.00 Oz. R-134a; 4.50 Oz. POE Oil	59889
15 - 14	4 Cyl 2.0L Eng. - 4.50 Oz. PAG-46; 17.76 Oz. R-134a	59007
15 - 14	4 Cyl 2.4L Eng. - 4.50 Oz. PAG-46; 17.76 Oz. R-134a	59007
13 - 12	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
13 - 12	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 3.72-4.40 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
11 - 10	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
09	6 Cyl Eng. - 17.89+/-0.88 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
08	4 Cyl 2.0L Eng. - 17.98+/-0.88 Oz. R-134a; 4.05-4.56 Oz. PAG-46	59007
08	6 Cyl 2.7L Eng. - 17.98+/-0.88 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
07	6 Cyl 2.7L Eng. - 18.00 Oz. R-134a; 6.76-7.27 Oz. PAG-46	59007
07	All Eng. - 18.00 Oz. R-134a; 4.00-4.56 Oz. PAG-46	59007
06 - 05	All Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06 - 05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>VELOSTER</b>		
17 - 14	4 Cyl 1.6L Eng. - Naturally Aspirated, 14.88 Oz. R-134a; 4.40 Oz. PAG-46	59007
17 - 14	4 Cyl 1.6L Eng. - Turbocharged, 14.88 Oz. R-134a; 4.40 Oz. PAG-46	59007
13	4 Cyl 1.6L Eng. - Naturally Aspirated, 15.69 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007
12	4 Cyl 1.6L Eng. - Naturally Aspirated, 16.00 Oz. R-134a; 3.71-4.39 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## HYUNDAI

Year	Description	Lubricant
<b>VERA CRUZ</b>		
12	6 Cyl 3.8L Eng. - 4.70-5.40 Oz. PAG-46; 15.00 Oz. R-134a	59007
11	6 Cyl 3.8L Eng. - 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46	59007
11 - 09	6 Cyl 3.8L Eng. - w/ Rear AC; 31.74+/-0.88 Oz. R-134a; 7.10+/-0.34 Oz. PAG-46	59007
10 - 09	6 Cyl 3.8L Eng. - w/o Rear AC; 24.69+/-0.88 Oz. R-134a; 5.07+/-0.34 Oz. PAG-46	59007
08	6 Cyl 3.8L Eng. - w/ Rear AC; 31.68+/-0.05 Oz. R-134a; 7.10+/-0.10 Oz. PAG-46	59007
08	6 Cyl 3.8L Eng. - w/o Rear AC; 24.64+/-0.05 Oz. R-134a; 5.07+/-0.10 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 8.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
07	All Eng. - w/o Rear AC; 5.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>XG300</b>		
01	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; 4.70-5.41 Oz. PAG-46	59007
<b>XG350</b>		
05 - 02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

## INFINITI

Year	Description	Lubricant
<b>EX35</b>		
12 - 11	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 08	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>FX35</b>		
12 - 11	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>FX45</b>		
08 - 03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>FX50</b>		
13 - 09	8 Cyl 5.0L Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
<b>G20</b>		
02 - 99	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
96 - 94	All Eng. - 28.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93 - 91	All Eng. - 29.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>G25</b>		
12 - 11	6 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>G35</b>		
08 - 03	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>G37</b>		
12 - 11	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08	All Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
<b>I30</b>		
01 - 98	All Eng. - 6.75 Oz. PAG-46; 25.00 Oz. R-134a	59007
97 - 96	All Eng. - 8.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>I35</b>		
04 - 02	All Eng. - 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>J30</b>		
97 - 94	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 8.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>M30</b>		
92 - 90	All Eng. - 6.75 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>M35 / M35h</b>		
13 - 12	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.21 Oz. Hybrid Oil	59889
10 - 09	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 06	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>M37</b>		
13 - 11	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## INFINITI

Year	Description	Lubricant
<b>M45</b>		
10 - 09	8 Cyl 4.5L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 06	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04 - 03	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>M56</b>		
13 - 11	8 Cyl 5.6L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>Q40</b>		
15	6 Cyl 3.7L Eng. - 19.36 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>Q45</b>		
06 - 02	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
00 - 97	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
96	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
95 - 94	All Eng. - 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 10.00 Oz. Mineral Oil; 42.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 90	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>Q50</b>		
17 - 16	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	6 Cyl 3.0L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	6 Cyl 3.5L Eng. - HYBRID, 17.60 Oz. R-134a; 5.07 Oz. Hybrid Oil	59889
15 - 14	6 Cyl 3.5L Eng. - HYBRID, 17.60 Oz. R-134a; 5.10 Oz. POE Oil	59889
15 - 14	6 Cyl 3.7L Eng. - 17.60 Oz. R-134a; 3.00 Oz. PAG-46	59007
<b>Q60</b>		
18 - 17	4 Cyl 2.0L Eng. - 19.36 Oz. R-134a; 5.10 Oz. PAG-46	59007
18 - 17	6 Cyl 3.0L Eng. - 19.36 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>Q70</b>		
18 - 14	8 Cyl 5.6L Eng. - 19.36 Oz. R-134a; 5.10 Oz. PAG-46	59007
17 - 14	6 Cyl 3.5L Eng. - HYBRID, 19.36 Oz. R-134a; 5.10 Oz. POE Oil	59889
17 - 14	6 Cyl 3.7L Eng. - 19.36 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>QX4</b>		
03 - 02	All Eng. - 6.00 Oz. PAG-100; 16.00 Oz. R-134a	59002
01 - 97	All Eng. - 6.75 Oz. PAG-100; 25.00 Oz. R-134a	59002
<b>QX56</b>		
13 - 11	8 Cyl 5.6L Eng. - 7.10 Oz. PAG-46; 34.00 Oz. R-134a	59007
10 - 09	8 Cyl 5.6L Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
08 - 04	All Eng. - 40.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
<b>QX60</b>		
18 - 14	4 Cyl 2.5L Eng. - HYBRID, 19.36 Oz. R-134a; 7.80 Oz. PAG-46	59007
18 - 14	6 Cyl 3.5L Eng. - 19.36 Oz. R-134a; 7.80 Oz. PAG-46	59007
<b>QX80</b>		
18 - 14	8 Cyl 5.6L Eng. - 7.00 Oz. PAG-46; 37.12 Oz. R-134a	59007

## INTERNATIONAL

Year	Description	Lubricant
<b>PICKUP</b>		
12	6 Cyl 7.6L Eng. - 40.00 Oz. R-134a; 10.00 Oz. PAG-100	59002

## ISUZU

Year	Description	Lubricant
<b>AMIGO</b>		
00 - 99	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93 - 91	All Eng. - 30.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>ASCENDER</b>		
08 - 06	All Eng. - w/ Rear AC; 42.50 Oz. R-134a; 8.50 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## ISUZU

Year	Description	Lubricant
<b>ASCENDER</b>		
08 - 06	All Eng. - w/o Rear AC; 7.50 Oz. PAG-46; 30.50 Oz. R-134a	59007
05 - 03	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
05 - 03	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
<b>AXIOM</b>		
04 - 02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>HOMBRE</b>		
00 - 99	All Eng. - w/ Denso Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 99	All Eng. - w/ OE Harrison Compressor; 30.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98 - 97	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 97	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
<b>I-280</b>		
06	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>I-290</b>		
08 - 07	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>i-350</b>		
06	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>i-370</b>		
08 - 07	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>I-MARK</b>		
89	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>IMPULSE</b>		
92	All Eng. - 5.00 Oz. Mineral Oil; 21.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 6.75 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
88	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>OASIS</b>		
99 - 96	All Eng. - w/ Rear AC; 30.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
99 - 96	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
<b>Pickup / P up</b>		
95 - 94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 6.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - 30.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RODEO</b>		
04 - 02	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01 - 94	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
93	All Eng. - 5.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 6.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>RODEO SPORT</b>		
03	4 Cyl 2.2L Eng. - 5.00 Oz. PAG-100; 25.00 Oz. R-134a	59002
03	6 Cyl 3.2L Eng. - 5.00 Oz. PAG-100; 25.00 Oz. R-134a	59002
02 - 01	4 Cyl 2.2L Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
02 - 01	6 Cyl 3.2L Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
<b>STYLUS</b>		
93 - 92	All Eng. - 5.00 Oz. Mineral Oil; 21.00 Oz. R-12	59000 <sup>(1)</sup>
91	All Eng. - 6.75 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
<b>TROOPER</b>		
02	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## ISUZU

Year	Description	Lubricant
<b>TROOPER</b>		
01	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Denso Compressor; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ OE Harrison Compressor; 21.00 Oz. R-134a; 5.00 Oz. PAG-150	59003
97 - 94	All Eng. - 5.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
93 - 92	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 33.50 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 34.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## VEHICROSS

01	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 99	All Eng. - w/ Denso Compressor; 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 99	All Eng. - w/ OE Harrison Compressor; 23.00 Oz. R-134a; 5.00 Oz. PAG-150	59003

## JAGUAR

Year	Description	Lubricant
<b>E-PACE</b>		
18	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
<b>F-PACE</b>		
18	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
17	4 Cyl 2.0L Eng. - Diesel, 19.20 Oz. R-1234yf; 2.70 Oz. PAG Oil	59234
17	6 Cyl 3.0L Eng. - 19.20 Oz. R-1234yf; 2.70 Oz. PAG Oil	59234
<b>F-TYPE</b>		
18	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
17	6 Cyl 3.0L Eng. - 24.64 Oz. R-1234yf; 4.02 Oz. PAG Oil	59234
17	8 Cyl 5.0L Eng. - 24.64 Oz. R-1234yf; 4.02 Oz. PAG Oil	59234
16 - 14	6 Cyl 3.0L Eng. - 2.70 Oz. PAG-46; 28.16 Oz. R-134a	59007
16 - 14	8 Cyl 5.0L Eng. - 2.70 Oz. PAG-46; 28.16 Oz. R-134a	59007
<b>S-TYPE</b>		
08 - 03	All Eng. - 26.50 Oz. R-134a; 7.00 Oz. PAG-100	59002
02 - 00	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
<b>SUPER V8</b>		
09 - 08	8 Cyl 4.2L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.90 Oz. PAG-46	59007
07 - 05	8 Cyl 4.2L Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
<b>VANDEN PLAS</b>		
09 - 08	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.90 Oz. PAG-46	59007
09 - 08	8 Cyl 4.2L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07 - 04	8 Cyl 4.2L Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
03 - 01	8 Cyl 4.0L Eng. - 24.00 Oz. R-134a; 5.44-6.76 Oz. PAG-46	59007
00 - 98	All Eng. - 24.00 Oz. R-134a; 5.44-6.76 Oz. PAG-46	59007
97 - 95	6 Cyl 4.0L Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
94	6 Cyl 4.0L Eng. - 40.00 Oz. R-134a; 4.06-5.07 PAG-100	59002
93	6 Cyl 4.0L Eng. - 40.00 Oz. R-134a; 4.06-5.07 PAG-100	59000 <sup>(1)</sup>
92 - 90	6 Cyl 4.0L Eng. - 4.60 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 90	6 Cyl 4.0L Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>X-TYPE</b>		
08	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
06	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 02	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>XF</b>		
17	4 Cyl 2.0L Eng. - Diesel, 19.20 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17	6 Cyl 3.0L Eng. - 19.20 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16 - 14	6 Cyl 3.0L Eng. - 28.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## JAGUAR

Year	Description	Lubricant
<b>XF</b>		
15 - 14	4 Cyl 2.0L Eng. - 28.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	8 Cyl 5.0L Eng. - 28.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
13	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
13 - 12	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
12	8 Cyl 5.0L Eng. - 27.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
10	8 Cyl 4.2L Eng. - 3.70 Oz. PAG-46; 27.00 Oz. R-134a	59007
10	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 27.00 Oz. R-134a	59007
09	8 Cyl 4.2L Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
<b>XFR</b>		
15 - 14	8 Cyl 5.0L Eng. - PAG-46; 28.16 Oz. R-134a	59007
13	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
12	8 Cyl 5.0L Eng. - 27.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
10	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 27.00 Oz. R-134a	59007
<b>XJ</b>		
17 - 16	6 Cyl 5.0L Eng. - 24.64 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
17 - 16	8 Cyl 3.0L Eng. - 24.64 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
15	8 Cyl 3.0L Eng. - 2.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
14	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
14	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
13	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
13	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
12	8 Cyl 5.0L Eng. - 25.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>XJ12</b>		
96 - 95	All Eng. - 8.00 Oz. PAG-100; 38.50 Oz. R-134a	59002
94	All Eng. - 44.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
<b>XJ6</b>		
97 - 95	All Eng. - 7.50 Oz. PAG-100; 38.50 Oz. R-134a	59002
94 - 93	All Eng. - 40.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
93	6 Cyl 4.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 3.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>XJ8</b>		
09 - 08	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.90 Oz. PAG-46	59007
09 - 08	8 Cyl 4.2L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
06	All Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
05 - 04	8 Cyl 4.2L Eng. - 28.00 Oz. R-134a; 6.07 Oz. PAG-46	59007
03	8 Cyl 4.0L Eng. - 24.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02	All Eng. - 24.00 Oz. R-134a; 5.41-6.576 Oz. PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
00 - 98	All Eng. - 6.75 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>XJR</b>		
17	8 Cyl 3.0L Eng. - 28.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 14	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 28.16 Oz. R-134a	59007
09 - 08	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.90 Oz. PAG-46	59007
09 - 08	8 Cyl 4.2L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
07 - 06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05 - 04	8 Cyl 4.2L Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
03	8 Cyl 4.0L Eng. - 22.93-24.70 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02 - 98	All Eng. - 22.93-24.70 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
97 - 95	6 Cyl 4.0L Eng. - 37.04-40.56 Oz. R-134a; 6.08-6.76 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## JAGUAR

Year	Description	Lubricant
<b>XJRS</b>		
93	All Eng. - 40.00 Oz. R-134a; 5.00 Oz. PAG-150	59003
<b>XJS</b>		
96	All Eng. - 39.68-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
95	All Eng. - 39.67-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
94	All Eng. - 39.68-41.28 Oz. R-134a; 4.06-5.07 Oz. PAG-100	59002
93	All Eng. - 40.00 Oz. R-134a; 6.50 Oz. PAG-100	59002
92 - 90	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil; w/ Delco Compressor	59000 <sup>(1)</sup>
89	All Eng. - 56.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 84	12 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>XK</b>		
15	8 Cyl 5.0L Eng. - 2.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
14	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
13	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
12 - 10	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
09 - 08	8 Cyl 4.2L Eng. - 26.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
<b>XK8</b>		
06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05 - 03	8 Cyl 4.2L Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
02	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
01 - 99	All Eng. - 23.00 Oz. R-134a; 5.14-6.76 Oz. PAG-46	59007
98	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
97	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
<b>XKR</b>		
15 - 14	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007
13 - 10	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
09	8 Cyl 4.2L Eng. - 26.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
07	8 Cyl 4.2L Eng. - 25.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
06	All Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
05 - 04	8 Cyl 4.2L Eng. - 23.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
03	8 Cyl 4.2L Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
02 - 01	All Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
00	8 Cyl 4.0L Eng. - 23.00 Oz. R-134a; 5.41-6.76 Oz. PAG-46	59007
<b>XKRS</b>		
14	8 Cyl 5.0L Eng. - 3.70 Oz. PAG-46; 24.64 Oz. R-134a	59007

## JEEP

Year	Description	Lubricant
<b>CHEROKEE</b>		
18 - 14	4 Cyl 2.4L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 14	4 Cyl 2.4L Eng. - PAG-46; 19.04 Oz. R-134a	59007
18 - 14	6 Cyl 3.2L Eng. - 18.08 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 14	6 Cyl 3.2L Eng. - PAG-46; 19.04 Oz. R-134a	59007
01 - 00	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 97	All Eng. - 20.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
96 - 95	All Eng. - 32.00 Oz. R-134a; 7.75 Oz. PAG-100	59002
94	4 Cyl 2.5L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
94	6 Cyl 4.0L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
94 - 90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 2.1L Eng. - 36.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - 36.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 2.8L Eng. - 36.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## JEEP

Year	Description	Lubricant
<b>CHEROKEE</b>		
84	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CJ SERIES</b>		
86 - 85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 82	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>COMANCHE</b>		
92 - 90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 4.0L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.5L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	4 Cyl 2.1L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	6 Cyl 2.8L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>COMMANDER</b>		
10	6 Cyl 3.7L Eng. - w/ Rear AC; 7.50 Oz. PAG-46; 34.00 Oz. R-134a	59007
10	8 Cyl 4.7L Eng. - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
10 - 09	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 5.07 Oz. PAG-46	59007
10 - 09	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 5.07 Oz. PAG-46	59007
10 - 09	8 Cyl 5.7L Eng. - w/ Rear AC; 7.50 Oz. PAG-46; 34.00 Oz. R-134a	59007
09	8 Cyl 4.7L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 5.07 Oz. PAG-46	59007
09	8 Cyl 4.7L Eng. - w/ Rear AC; 7.50 Oz. PAG-46; 34.00 Oz. R-134a	59007
08 - 06	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.50 Oz. PAG-46	59007
08 - 06	All Eng. - w/ Rear AC; 7.50 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>COMPASS</b>		
17 - 14	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
17 - 14	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
13 - 11	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 21.00 Oz. R-134a	59007
13 - 11	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 21.00 Oz. R-134a	59007
10 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08 - 07	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>GRAND CHEROKEE</b>		
18	8 Cyl 6.2L Eng. - 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	8 Cyl 6.2L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
18 - 15	6 Cyl 3.0L Eng. - Diesel, 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 15	6 Cyl 3.0L Eng. - Diesel, 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
18 - 15	6 Cyl 3.6L Eng. - 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 15	8 Cyl 5.7L Eng. - 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 15	8 Cyl 6.4L Eng. - 20.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 14	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
18 - 14	8 Cyl 5.7L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
18 - 14	8 Cyl 6.4L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
14	6 Cyl 3.0L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
13 - 12	8 Cyl 6.4L Eng. - 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.7L Eng. - 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10	6 Cyl 3.0L Eng. - 4.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
10 - 09	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
10 - 09	8 Cyl 4.7L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
10 - 09	8 Cyl 5.7L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
10 - 09	8 Cyl 6.1L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08 - 05	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04 - 02	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01	All Eng. - 24.00 Oz. R-134a; 5.75 Oz. PAG-100	59002
00	All Eng. - 24.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
99 - 98	All Eng. - 26.00 Oz. R-134a; 7.50 Oz. PAG-100	59002
97 - 96	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-100	59002

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## JEEP

Year	Description	Lubricant
------	-------------	-----------

### GRAND CHEROKEE

95	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-100	59007
94 - 93	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-100	59002

### GRAND WAGONEER

93	All Eng. - 28.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### LIBERTY

12 - 11	6 Cyl 3.7L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 08	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
06	All Eng. - 8.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
05	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
04 - 02	All Eng. - 26.00 Oz. R-134a; 8.00 Oz. PAG-100	59002

### PATRIOT

18 - 14	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
18 - 14	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 20.96 Oz. R-134a	59007
13 - 12	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 21.00 Oz. R-134a	59007
13 - 11	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 21.00 Oz. R-134a	59007
11 - 09	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08 - 07	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007

### RENEGADE

18 - 15	4 Cyl 1.4L Eng. - 4.40 Oz. PAG-46; 16.00 Oz. R-1234yf	59234
18 - 15	4 Cyl 2.4L Eng. - 4.40 Oz. PAG-46; 16.00 Oz. R-1234yf	59234

### WAGONEER

90	All Eng. - 38.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 4.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83	6 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### WRANGLER

17 - 16	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
15 - 14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 18.08 Oz. R-134a	59007
13 - 12	6 Cyl 3.6L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
11	6 Cyl 3.8L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 05	4 Cyl 2.4L Eng. - 6.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
06 - 05	6 Cyl 4.0L Eng. - 6.10 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
04 - 01	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
00	All Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 97	All Eng. - 20.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
95 - 94	All Eng. - 32.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
93 - 90	All Eng. - 32.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.5L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 4.2L Eng. - 32.00 Oz. R-12; 6.00-6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

## KIA

Year	Description	Lubricant
------	-------------	-----------

### AMANTI

09	6 Cyl 3.8L Eng. - 23.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 04	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007

### BORREGO

11	6 Cyl 3.8L Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
----	---	-------

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## KIA

Year	Description	Lubricant
<b>BORREGO</b>		
09	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>CADENZA</b>		
18 - 17	6 Cyl 3.3L Eng. - 19.20 Oz. R-1234yf; 3.70 Oz. PAG Oil	59234
16 - 14	6 Cyl 3.3L Eng. - 3.70 Oz. PAG-46; 19.20 Oz. R-134a	59007
<b>FORTE</b>		
18 - 17	4 Cyl 1.6L Eng. - FORTE5, 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
18 - 17	4 Cyl 2.0L Eng. - FORTE5, 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
18 - 14	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
16 - 14	4 Cyl 1.6L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
16 - 14	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 18.40 Oz. R-134a	59007
13	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
13	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
12	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
12 - 11	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
10	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
<b>K900</b>		
18 - 15	6 Cyl 3.8L Eng. - 4.00 Oz. PAG-46; 23.20 Oz. R-134a	59007
18 - 15	8 Cyl 5.0L Eng. - 4.00 Oz. PAG-46; 23.20 Oz. R-134a	59007
<b>MAGENTIS</b>		
10	4 Cyl 2.4L Eng. - 17.60 Oz. R-134a; 4.30 Oz. PAG-46	59007
<b>NIRO</b>		
18 - 17	4 Cyl 1.6L Eng. - Electric/Gas, 17.60 Oz. R-1234yf or R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>OPTIMA</b>		
18	4 Cyl 1.6L Eng. - 19.36 Oz. R-1234yf; 4.40 Oz. PAG Oil	59234
18	4 Cyl 2.0L Eng. - 19.36 Oz. R-1234yf; 4.40 Oz. PAG Oil	59234
18	4 Cyl 2.4L Eng. - 19.36 Oz. R-1234yf; 4.40 Oz. PAG Oil	59234
17	4 Cyl 2.0L Eng. - Electric/Gas, 19.36 Oz. R-134a; 3.70 Oz. POE Oil	59889
17	4 Cyl 2.4L Eng. - 3.70 Oz. PAG-46; 22.88 Oz. R-134a	59007
17 - 16	4 Cyl 1.6L Eng. - 3.70 Oz. PAG-46; 22.88 Oz. R-134a	59007
17 - 16	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 22.88 Oz. R-134a	59007
16	4 Cyl 2.4L Eng. - Electric/Gas, 19.36 Oz. R-1234yf; 4.40 Oz. POE Oil	59889
16	4 Cyl 2.4L Eng. - Gas, 3.70 Oz. PAG-46; 22.88 Oz. R-134a	59007
15	4 Cyl 2.4L Eng. - Electric/Gas, 19.36 Oz. R-134a; 3.70 Oz. POE Oil	59889
15 - 14	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 19.36 Oz. R-134a	59007
15 - 14	4 Cyl 2.4L Eng. - Gas, 3.70 Oz. PAG-46; 19.36 Oz. R-134a	59007
14	4 Cyl 2.4L Eng. - Electric/Gas, 19.36 Oz. R-134a; 4.50 Oz. POE Oil	59889
13 - 11	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
13 - 11	4 Cyl 2.4L Eng. - Electric/Gas, 19.00 Oz. R-134a; 4.20 Oz. POE Oil	59889
13 - 11	4 Cyl 2.4L Eng. - Gas, 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 09	6 Cyl 2.7L Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08 - 07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06	All Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
05 - 01	All Eng. - 5.00 Oz. PAG-46; 22.00-24.00 Oz. R-134a	59007
<b>RIO / RIO5</b>		
18 - 14	4 Cyl 1.6L Eng. - 14.88 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 12	4 Cyl 1.6L Eng. - 16.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
10 - 09	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08 - 07	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05	All Eng. - 5.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
04 - 01	All Eng. - 5.00 Oz. PAG-46; 22.00-24.00 Oz. R-134a	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## KIA

Year	Description	Lubricant
<b>RONDO</b>		
14	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 22.00 - 24.00 Oz. R-134a	59007
12 - 11	4 Cyl 2.4L Eng. - 15.88+/-0.88 R-134a; 4.05+/-0.34 Oz. PAG-46	59007
12 - 11	6 Cyl 2.7L Eng. - 15.88+/-0.88 R-134a; 4.05+/-0.34 Oz. PAG-46	59007
10 - 08	4 Cyl 2.4L Eng. - 4.10 Oz. PAG-46; 16.00 Oz. R-134a	59007
10 - 08	6 Cyl 2.7L Eng. - 4.10 Oz. PAG-46; 16.00 Oz. R-134a	59007
07	All Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007

## SEDONA

18 - 15	6 Cyl 3.3L Eng. - 31.68 Oz. R-134a; 7.40 Oz. PAG-46	59007
14	6 Cyl 3.5L Eng. - 31.68 Oz. R-134a; 7.40 Oz. PAG-46	59007
12 - 11	6 Cyl 3.5L Eng. - 32.00 Oz. R-134a; 4.10-7.40 Oz. PAG-46	59007
10 - 08	6 Cyl 3.8L Eng. - 32.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
07 - 06	All Eng. - 32.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
05 - 02	All Eng. - 7.00 Oz. PAG-46; 34.40-36.10 Oz. R-134a	59007

## SEPHIA

01 - 98	All Eng. - 6.75 Oz. PAG-46; 26.50 Oz. R-134a	59007
97 - 94	All Eng. - 24.00 Oz. R-134a	59007

## SORENTO

13	4 Cyl 2.4L Eng. - w/ Rear AC; 7.10 Oz. PAG-46; 26.40+/-0.88 Oz. R-134a	59007
13	4 Cyl 2.4L Eng. - w/o Rear AC; 21.10+/-0.88 Oz. R-134a; 5.07 Oz. PAG-46	59007
13 - 11	6 Cyl 3.5L Eng. - w/ Rear AC; 26.00 Oz. R-134a; 6.70-7.40 Oz. PAG-46	59007
13 - 11	6 Cyl 3.5L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
12 - 11	4 Cyl 2.4L Eng. - w/ Rear AC; 26.00 Oz. R-134a; 6.70-7.40 Oz. PAG-46	59007
12 - 11	4 Cyl 2.4L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
09 - 08	6 Cyl 3.3L Eng. - 21.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
09 - 08	6 Cyl 3.8L Eng. - 21.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
07	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 03	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007

## SOUL

18 - 16	4 Cyl 1.6L Eng. - Gas, 4.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
18 - 16	4 Cyl 2.0L Eng. - Gas, 4.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
18 - 15	All Eng. - Electric, SOUL EV, 19.36 Oz. R-134a; 6.00 Oz. POE Oil	59889
15 - 14	4 Cyl 1.6L Eng. - 4.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
15 - 14	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
13	4 Cyl 1.6L Eng. - 19.40+/-0.88 Oz. R-134a; 3.38+/-0.16-.33 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
12 - 11	4 Cyl 1.6L Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
12 - 11	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.00-3.70 Oz. PAG-46	59007
10	4 Cyl 1.6L Eng. - 3.40 Oz. PAG-46; 20.00 Oz. R-134a	59007
10	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 20.00 Oz. R-134a	59007

## SPECTRA / SPECTRA5

09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
07	All Eng. - 18.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06 - 04	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
03 - 02	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01 - 00	All Eng. - 25.00 Oz. R-134a; 6.08 Oz. PAG-46	59007

## SPORTAGE

18 - 17	4 Cyl 2.0L Eng. - 20.00 Oz. R-1234yf; 4.40 Oz. PAG Oil	59234
18 - 17	4 Cyl 2.4L Eng. - 20.00 Oz. R-1234yf; 4.40 Oz. PAG Oil	59234
16	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
16	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
15 - 14	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
15 - 14	4 Cyl 2.4L Eng. - 17.60 Oz. R-134a; 4.40 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
13	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## KIA

Year	Description	Lubricant
<b>SPORTAGE</b>		
12 - 11	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.70-4.40 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - 17.90+/-0.88 Oz. R-134a; 4.05+/-0.33 Oz. PAG-46	59007
10	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10-4.60 Oz. PAG-46	59007
10	6 Cyl 2.7L Eng. - 18.00 Oz. R-134a; 6.80-7.30 Oz. PAG-46	59007
09 - 06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.30 Oz. PAG-46	59007
05	6 Cyl 2.7L Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
02	4 Cyl 2.0L Eng. - 25.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
01 - 95	All Eng. - 25.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

## STINGER

18	4 Cyl 2.0L Eng. - 20.48 Oz. R-1234yf; 3.50 Oz. PAG Oil	59234
18	6 Cyl 3.3L Eng. - 20.48 Oz. R-1234yf; 3.50 Oz. PAG Oil	59234

## LAND ROVER

Year	Description	Lubricant
------	-------------	-----------

### Defender

97	All Eng. - 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94 - 93	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

### Defender 110

93	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
----	---	----------------------

### Defender 90

97	All Eng. - 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

### Discovery

04 - 00	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
04 - 00	All Eng. - w/o Rear AC; 25.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
99 - 94	All Eng. - w/ Rear AC; 41.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
99 - 94	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 6.50 Oz. PAG-46	59007

### Discovery Sport

17 - 16	4 Cyl 2.0L Eng. - 22.40 Oz. R-1234yf; 3.70 Oz. PAG Oil	59234
15	4 Cyl 2.0L Eng. - 22.40 Oz. R-1234yf; 5.20 Oz. PAG Oil	59234

### FREELANDER

05 - 03	6 Cyl 2.5L Eng. - 15.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
02	All Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

### LR2

15 - 14	4 Cyl 2.0L Eng. - 30.40 Oz. R-134a; 5.30 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 26.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
12 - 11	6 Cyl 3.2L Eng. - 3.70 Oz. PAG-46; 26.00 Oz. R-134a	59007
10 - 08	6 Cyl 3.2L Eng. - 26.00 Oz. R-134a; 5.10 Oz. PAG-46	59007

### LR3

09	8 Cyl 4.4L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 05	All Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07	All Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06 - 05	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

### LR4

16 - 15	6 Cyl 3.0L Eng. - 22.40 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
13 - 12	8 Cyl 5.0L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 3.72 Oz. PAG-46	59007
13 - 12	8 Cyl 5.0L Eng. - w/ Rear AC; 33.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
11 - 10	8 Cyl 5.0L Eng. - w/ Rear AC; 32.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
11 - 10	8 Cyl 5.0L Eng. - w/o Rear AC; 3.70 Oz. PAG-46; 23.00 Oz. R-134a	59007

### Range Rover

13	8 Cyl 5.0L Eng. - w/o Rear AC; 25.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
----	--	-------

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LAND ROVER

Year	Description	Lubricant
<b>Range Rover</b>		
13 - 10	8 Cyl 5.0L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
12	8 Cyl 5.0L Eng. - w/o Rear AC; 26.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.0L Eng. - w/o Rear AC; 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
10	8 Cyl 5.0L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
09	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.00 Oz. PAG-46	59007
09	8 Cyl 4.2L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.00 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05 - 02	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
01 - 00	All Eng. - 6.00 Oz. PAG-46; 49.00 Oz. R-134a	59007
99	All Eng. - 6.00 Oz. PAG-46; 41.00 Oz. R-134a	59007
98 - 97	All Eng. - 5.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96	All Eng. - New Body Style; 5.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
96	All Eng. - Old Body Style; 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95	All Eng. - 32.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
94	8 Cyl 3.9L Eng. - 42.00 Oz. R-134a; 5.06 Oz. PAG-46	59007
94	8 Cyl 4.2L Eng. - 42.00 Oz. R-134a; 5.06 Oz. PAG-46	59007
<b>RANGE ROVER EVOQUE</b>		
17	4 Cyl 2.0L Eng. - 22.40 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16	4 Cyl 2.0L Eng. - 22.40 Oz. R-1234yf; 3.70 Oz. PAG Oil	59234
15 - 14	4 Cyl 2.0L Eng. - 22.40 Oz. R-1234yf; 5.30 Oz. PAG Oil	59234
13 - 12	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
<b>Range Rover Sport</b>		
15 - 14	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	8 Cyl 5.0L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	8 Cyl 5.0L Eng. - w/o Rear AC; 25.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
13 - 10	8 Cyl 5.0L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
12	8 Cyl 5.0L Eng. - w/o Rear AC; 26.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.0L Eng. - w/o Rear AC; 3.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
10	8 Cyl 5.0L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
09	8 Cyl 4.2L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.00 Oz. PAG-46	59007
09	8 Cyl 4.2L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - 24.00 Oz. R-134a; w/o Rear AC; 4.00 Oz. PAG-46	59007
09	8 Cyl 4.4L Eng. - w/ Rear AC; 31.00 Oz. R-134a; 5.70 Oz. PAG-46	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007

## LEXUS

Year	Description	Lubricant
<b>CT200</b>		
17	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 11	4 Cyl 1.8L Eng. - 16.60 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil; See Under Hood Decal for Lubricant Capacity	59889
<b>ES250</b>		
91 - 90	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ES300</b>		
18 - 17	4 Cyl 2.5L Eng. - Electric/Gas, ES300h, 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
16 - 14	4 Cyl 2.5L Eng. - Electric/Gas, ES300h, 17.60 Oz. R-134a; 4.50 Oz. POE Oil	59889
13	All Eng. - 16.60-18.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
03 - 02	All Eng. - 19.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
01 - 98	All Eng. - 7.00 Oz. PAG-46; 26.50-30.00 Oz. R-134a	59007
97 - 94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ES330</b>		
06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
05 - 04	All Eng. - 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LEXUS

Year	Description	Lubricant
<b>ES350</b>		
18 - 17	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 14	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; 3.90 Oz. PAG-46	59007
15	6 Cyl 3.5L Eng. - 16.60-18.70 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 10	6 Cyl 3.5L Eng. - 16.60-18.70 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	6 Cyl 3.5L Eng. - 16.60-18.70 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
08 - 07	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>GS200</b>		
17	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GS300</b>		
06	All Eng. - 5.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
05 - 02	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
01 - 98	All Eng. - 7.00 Oz. PAG-46; 21.00-23.0 Oz. R-134a	59007
97 - 93	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>GS350</b>		
16 - 15	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14 - 13	6 Cyl 3.5L Eng. - 17.67+/-1.76 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	6 Cyl 3.5L Eng. - 15.87+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 15.87+/-1.76 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	6 Cyl 3.5L Eng. - 15.87+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
08 - 07	6 Cyl 3.5L Eng. - 4.50 Oz. PAG-46; 15.87+/-1.76 Oz. R-134a	59007
<b>GS400</b>		
00 - 98	All Eng. - 7.00 Oz. PAG-46; 21.00-23.0 Oz. R-134a	59007
<b>GS430</b>		
07 - 06	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 01	All Eng. - 7.00 Oz. PAG-46; 21.00-23.0 Oz. R-134a	59007
<b>GS450</b>		
18 - 16	6 Cyl 3.5L Eng. - Electric/Gas, GS450h, 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15	6 Cyl 3.5L Eng. - Electric/Gas, GS450h, 15.90-19.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
14	6 Cyl 3.5L Eng. - Electric/Gas, GS450h, 4.50 Oz. Hybrid Oil; 15.90-19.40 Oz. R-134a	59889
13	6 Cyl 3.5L Eng. - Electric/Gas, 15.87+/-1.76 Oz. R-134a; 4.10+/-0.51 Oz. Hybrid Oil	59889
11 - 07	6 Cyl 3.5L Eng. - Electric/Gas, 15.87+/-1.76 Oz. R-134a; 4.10+/-0.51 Oz. Hybrid Oil	59889
<b>GS460</b>		
11	8 Cyl 4.6L Eng. - 19.00 Oz. R-134a; 4.10-5.10 Oz. PAG-46	59007
11	8 Cyl 4.6L Eng. - 1UR-FSE, 19.39+/-1.76 Oz. R-134a; 4.60+/-0.51 Oz. PAG-46	59007
10 - 08	8 Cyl 4.6L Eng. - 1UR-FSE, 19.39+/-1.76 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GX460</b>		
15 - 14	8 Cyl 4.6L Eng. - 19.30 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Rear Cooler	59007
15 - 14	8 Cyl 4.6L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/ Rear Cooler	59007
13	8 Cyl 4.6L Eng. - 30.00 Oz. R-134a; 5.10 Oz. PAG-46, w/ Cool Box	59007
13 - 10	8 Cyl 4.6L Eng. - 29.00 Oz. R-134a; 5.08 Oz. PAG-46, w/o Cool Box	59007
13 - 10	8 Cyl 4.6L Eng. - w/o Rear AC; 19.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
12 - 10	8 Cyl 4.6L Eng. - 30.00 Oz. R-134a; 5.08 Oz. PAG-46, w/ Cool Box	59007
<b>GX470</b>		
09	8 Cyl 4.7L Eng. - w/ Rear AC; 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09 - 07	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 07	All Eng. - w/ Rear AC; 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Rear AC; 4.50 Oz. PAG-46; 28.10-28.90 Oz. R-134a	59007
06 - 03	All Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 22.40-24.00 Oz. R-134a	59007
<b>HS250</b>		
12 - 10	4 Cyl 2.4L Eng. - HYBRID, 17.00 Oz. R-134a; 3.50 Oz. Hybrid Oil	59889
<b>IS F</b>		
14	8 Cyl 5.0L Eng. - 14.10-17.63 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	8 Cyl 5.0L Eng. - 16.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
13	8 Cyl 5.0L Eng. - 18.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12 - 08	8 Cyl 5.0L Eng. - 14.10-17.63 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LEXUS

Year	Description	Lubricant
<b>IS200</b>		
17 - 16	8 Cyl 2.0L Eng. - Electric/Gas, IS200t, 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>IS250</b>		
15 - 14	6 Cyl 2.5L Eng. - 15.20 Oz. R-134a; 3.90 Oz. PAG-46	59007
13	6 Cyl 2.5L Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12	6 Cyl 2.5L Eng. - 15.00 Oz. R-134a; 4.60-5.10 Oz. PAG-46	59007
11 - 10	6 Cyl 2.5L Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	6 Cyl 2.5L Eng. - 15.17+/-1.06 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 06	6 Cyl 2.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>IS300</b>		
17 - 16	6 Cyl 3.5L Eng. - 15.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 03	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
02 - 01	All Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>IS350</b>		
17 - 16	6 Cyl 3.5L Eng. - 15.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	6 Cyl 3.5L Eng. - 15.20 Oz. R-134a; 3.90 Oz. PAG-46	59007
13 - 10	6 Cyl 3.5L Eng. - 15.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09 - 06	6 Cyl 3.5L Eng. - 15.17+/-1.06 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>LC500</b>		
18	8 Cyl 5.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
<b>LS400</b>		
00 - 98	All Eng. - 22.90-26.50 Oz. R-134a; 7.75 Oz. PAG-46	59007
97 - 94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	8 Cyl 4.0L Eng. - 3.10-5.20 Oz. PAG-46; 33.60 Oz. R-134a	59000 <sup>(1)</sup>
93	All Eng. - 33.50 Oz. R-134a; 5.25 Oz. PAG-46	59007
92 - 90	All Eng. - 7.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
<b>LS430</b>		
06 - 03	All Eng. - w/ Rear AC; 4.50 Oz. PAG-46; 30.00-33.50 Oz. R-134a	59007
06 - 03	All Eng. - w/o Rear AC; 4.50 Oz. PAG-46; 22.00-24.00 Oz. R-134a	59007
02 - 01	All Eng. - w/ Rear AC; 30.00-33.50 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
02 - 01	All Eng. - w/o Rear AC; 22.00-24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>LS460</b>		
15 - 14	8 Cyl 4.6L Eng. - 24.70 Oz. R-134a; 5.30 Oz. PAG-46, w/ Rear Cooler	59007
15 - 14	8 Cyl 4.6L Eng. - 24.70 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Rear Cooler	59007
13	8 Cyl 4.6L Eng. - w/ Rear AC; 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
13 - 10	8 Cyl 4.6L Eng. - w/o Rear AC; 23.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12	8 Cyl 4.6L Eng. - 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 10	8 Cyl 4.6L Eng. - w/ Rear AC; 28.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	8 Cyl 4.6L Eng. - w/o Rear AC; 23.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 08	8 Cyl 4.6L Eng. - w/ Rear AC; 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	8 Cyl 4.6L Eng. - w/o Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07	8 Cyl 4.6L Eng. - 21.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Rear Cooler	59007
07	8 Cyl 4.6L Eng. - 26.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
<b>LS600</b>		
16	8 Cyl 5.0L Eng. - Electric/Gas, LS600h, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
15 - 14	8 Cyl 5.0L Eng. - Electric/Gas, LS600h, 29.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 14	8 Cyl 5.0L Eng. - HYBRID, 28.60-30.70 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
13	8 Cyl 5.0L Eng. - HYBRID, 17.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
12 - 10	8 Cyl 5.0L Eng. - HYBRID, 28.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
09	8 Cyl 5.0L Eng. - HYBRID, 31.70 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
08	8 Cyl 5.0L Eng. - HYBRID, w/ Rear AC; 26.50 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
08	8 Cyl 5.0L Eng. - HYBRID, w/o Rear AC; 22.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>LX450</b>		
97 - 96	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>LX470</b>		
07	8 Cyl 4.7L Eng. - 31.70+/-1.18. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LEXUS

Year	Description	Lubricant
<b>LX470</b>		
06 - 98	All Eng. - 35.30-38.80 Oz. R-134a; 7.75 Oz. PAG-46	59007
<b>LX570</b>		
15 - 14	8 Cyl 5.7L Eng. - 32.50+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Cool Box	59007
15 - 14	8 Cyl 5.7L Eng. - 34.20+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/ Cool Box	59007
13	8 Cyl 5.7L Eng. - 34.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Cool Box	59007
13	8 Cyl 5.7L Eng. - 35.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/ Cool Box	59007
11 - 09	8 Cyl 5.7L Eng. - 32.50+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Cool Box	59007
11 - 09	8 Cyl 5.7L Eng. - 34.20+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/ Cool Box	59007
08	8 Cyl 5.7L Eng. - 32.50+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, Standard Air	59007
08	8 Cyl 5.7L Eng. - 34.20+/-1.10 Oz. R-134a; See Under Hood Decal for Lubricant Capacity, w/o Cool Box	59007
<b>NX200</b>		
17	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>NX300</b>		
17 - 16	4 Cyl 2.5L Eng. - Electric/Gas, NX300h, 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15	4 Cyl 2.5L Eng. - Electric/Gas, NX300h, 18.40 Oz. R-134a; 4.50 Oz. POE Oil	59889
<b>RC300</b>		
18	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>RX300</b>		
03	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 6.91 Oz. PAG-46	59007
02	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
01 - 99	All Eng. - 21.00 Oz. R-134a; 4.80 Oz. PAG-46	59007
<b>RX330</b>		
06 - 04	All Eng. - 4.00 Oz. PAG-46; 22.00-24.00 Oz. R-134a	59007
<b>RX350</b>		
17 - 16	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; 3.90 Oz. PAG-46	59007
15 - 10	6 Cyl 3.5L Eng. - 15.90-19.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	6 Cyl 3.5L Eng. - 19.40-22.90 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 07	All Eng. - 19.40-22.90 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>RX400h</b>		
08 - 06	6 Cyl 3.3L Eng. - HYBRID, 19.40-22.90 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>RX450</b>		
18	6 Cyl 3.5L Eng. - Electric/Gas, RX450h, 21.12 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15	6 Cyl 3.5L Eng. - 19.40-22.90 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
14	6 Cyl 3.5L Eng. - 19.40-22.80 Oz. R-134a; 4.10-4.60 Oz. Hybrid Oil	59889
14	6 Cyl 3.5L Eng. - Electric/Gas, RX450h, 21.12 Oz. R-134a; 4.60 Oz. POE Oil	59889
13	6 Cyl 3.5L Eng. - HYBRID, 23.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
12	6 Cyl 3.5L Eng. - HYBRID, 21.00 Oz. R-134a; 4.10-4.60 Oz. Hybrid Oil	59889
11 - 10	6 Cyl 3.5L Eng. - HYBRID, 21.00 Oz. R-134a; 3.53 Oz. Hybrid Oil	59889
<b>SC300</b>		
00 - 97	All Eng. - 7.00 Oz. PAG-46; 32.00-34.0 Oz. R-134a	59007
96	All Eng. - 7.00 Oz. PAG-46; 31.80-35.30 Oz. R-134a	59007
95 - 94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SC400</b>		
00 - 96	All Eng. - 33.50 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 30.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SC430</b>		
10	8 Cyl 4.3L Eng. - 4.00 Oz. PAG-46; 15.20 Oz. R-134a	59007
09	8 Cyl 4.3L Eng. - 4.00 Oz. PAG-46; 21.16 Oz. R-134a	59007
08	8 Cyl 4.3L Eng. - 4.50 Oz. PAG-46; 21.16 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LEXUS

Year	Description	Lubricant
<b>SC430</b>		
07	8 Cyl 4.3L Eng. - 21.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
06 - 02	All Eng. - 21.00 Oz. R-134a; 4.10 Oz. PAG-46	59007

## LINCOLN

Year	Description	Lubricant
<b>AVIATOR</b>		
05 - 03	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
<b>BLACKWOOD</b>		
02	All Eng. - 9.00 Oz. PAG-46; 37.00 Oz. R-134a	59007

## CONTINENTAL

17	6 Cyl 2.7L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	6 Cyl 3.0L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
02 - 98	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
97 - 95	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
94	All Eng. - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 74	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## LS

06 - 00	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
---------	--	-------

## MARK LIGHT TRUCK

08 - 06	All Eng. - 8.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
---------	--	-------

## MARK SERIES

98 - 95	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
94	All Eng. - 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
93	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
92 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 80	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 77	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 72	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## MKC

18 - 17	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 17	4 Cyl 2.3L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 15	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
16 - 15	4 Cyl 2.3L Eng. - 24.00 Oz. R-134a; 4.40 Oz. PAG-46	59007

## MKS

16 - 15	6 Cyl 3.5L Eng. - 26.08 Oz. R-134a; 5.40 Oz. PAG-46	59007
16 - 15	6 Cyl 3.7L Eng. - 22.88 Oz. R-134a; 5.40 Oz. PAG-46	59007
14	6 Cyl 3.5L Eng. - 7.00 Oz. PAG-46; 25.92 Oz. R-134a	59007
14	6 Cyl 3.7L Eng. - 7.00 Oz. PAG-46; 22.88 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LINCOLN

Year	Description	Lubricant
<b>MKS</b>		
13 - 11	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
13 - 11	6 Cyl 3.7L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
10 - 09	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>MKT</b>		
18 - 17	6 Cyl 3.5L Eng. - 39.20 Oz. R-134a; 7.95 Oz. PAG-46	59007
18 - 16	6 Cyl 3.7L Eng. - 36.96 Oz. R-134a; 8.90 Oz. PAG-46	59007
17	4 Cyl 2.0L Eng. - 39.20 Oz. R-134a; 7.95 Oz. PAG-46	59007
16	4 Cyl 2.0L Eng. - 38.88 Oz. R-134a; 7.95 Oz. PAG-46	59007
16	6 Cyl 3.5L Eng. - 38.88 Oz. R-134a; 7.95 Oz. PAG-46	59007
15 - 14	4 Cyl 2.0L Eng. - 38.88 Oz. R-134a; 9.50 Oz. PAG-46	59007
15 - 14	6 Cyl 3.5L Eng. - 38.88 Oz. R-134a; 9.50 Oz. PAG-46	59007
15 - 14	6 Cyl 3.7L Eng. - 36.96 Oz. R-134a; 9.50 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - 39.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
13 - 10	6 Cyl 3.5L Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
13 - 10	6 Cyl 3.7L Eng. - 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
<b>MKX</b>		
18 - 16	6 Cyl 2.7L Eng. - 4.00 Oz. PAG-46; 20.32 Oz. R-134a	59007
18 - 14	6 Cyl 3.7L Eng. - 4.00 Oz. PAG-46; 20.32 Oz. R-134a	59007
13 - 11	6 Cyl 3.7L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
10 - 07	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>MKZ</b>		
18 - 17	4 Cyl 2.0L Eng. - Gas, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 17	4 Cyl 2.0L Eng. - HYBRID, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
16	4 Cyl 2.0L Eng. - Gas, 20.00 Oz. R-134a; 4.70 Oz. PAG Oil	59007
16	6 Cyl 3.7L Eng. - Gas, 24.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
16 - 13	4 Cyl 2.0L Eng. - HYBRID, 20.00 Oz. R-134a; 4.60 Oz. POE Oil	59889
15	4 Cyl 2.0L Eng. - Gas, 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
15	4 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
14	6 Cyl 2.0L Eng. - Gas, 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
14 - 13	6 Cyl 3.7L Eng. - 24.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - Gas, 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
12	4 Cyl 2.5L Eng. - HYBRID, 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
12 - 11	6 Cyl 3.5L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
11	4 Cyl 2.5L Eng. - HYBRID, 22.00 Oz. R-134a; 6.00 Oz. Hybrid Oil	59889
10 - 07	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>NAVIGATOR</b>		
17 - 16	6 Cyl 3.5L Eng. - L-Reserve, L-Select, 7.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
17 - 16	6 Cyl 3.5L Eng. - Select, Reserve, 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
15	6 Cyl 3.5L Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
14 - 12	8 Cyl 5.4L Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
11	8 Cyl 5.4L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
10 - 09	All Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
10 - 09	All Eng. - L, 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 07	All Eng. - w/o Rear AC; 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
07	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
06	All Eng. - w/ Rear AC; 14.00 Oz. PAG-46; 58.00 Oz. R-134a	59007
06	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 03	All Eng. - w/ Rear AC; 14.00 Oz. PAG-46; 54.00 Oz. R-134a	59007
05 - 03	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02 - 98	All Eng. - w/ Rear AC; 14.00 Oz. PAG-46; 62.00 Oz. R-134a	59007
02 - 98	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
<b>TOWN CAR</b>		
11 - 09	8 Cyl 4.6L Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 06	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 03	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
02 - 98	All Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
97	All Eng. - 7.50 Oz. PAG-46; 34.00 Oz. R-134a	59007



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## LINCOLN

Year	Description	Lubricant
<b>TOWN CAR</b>		
96 - 95	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
94	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
94	All Eng. - w/o Rear AC; 40.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 10.00 Oz. Mineral Oil; 48.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 82	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## ZEPHYR

06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
----	--	-------

## MAZDA

Year	Description	Lubricant
<b>323</b>		
94 - 93	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
92 - 89	All Eng. - 6.75 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - 30.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>626</b>		
02 - 98	All Eng. - 8.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
97 - 94	All Eng. - 8.00 Oz. PAG-100; 25.00 Oz. R-134a	59002
93 - 89	All Eng. - 6.00 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 37.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - w/ R12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 79	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>808</b>		
77 - 74	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>929</b>		
95 - 94	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-100	59002
93 - 92	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 5.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>B1600</b>		
78	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B1800</b>		
78	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B2000</b>		
86	All Eng. - B2000, 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 79	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B2200</b>		
93 - 92	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 90	All Eng. - B2200, 8.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
89 - 87	All Eng. - B2200, 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B2300</b>		
08 - 06	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 01	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96 - 94	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>B2500</b>		
01 - 98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MAZDA

Year	Description	Lubricant
<b>B2600</b>		
93 - 92	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 87	All Eng. - B2600, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>B2900</b>		
06	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 97	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96 - 94	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>B3000</b>		
08 - 06	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 97	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96 - 94	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>B4000</b>		
08 - 06	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
05 - 97	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96 - 94	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>BT-50</b>		
08 - 07	All Eng. - 9.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
<b>COSMO</b>		
78 - 76	2 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CX-3</b>		
18 - 16	4 Cyl 2.0L Eng. - 15.68 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CX-5</b>		
17 - 14	4 Cyl 2.5L Eng. - 17.60 Oz. R-134a; 3.30 Oz. PAG-46	59007
16 - 14	4 Cyl 2.0L Eng. - 17.60 Oz. R-134a; 3.30 Oz. PAG-46	59007
<b>CX-7</b>		
12 - 10	4 Cyl 2.3L Eng. - 15.70-17.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 10	4 Cyl 2.5L Eng. - 15.70-17.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 07	4 Cyl 2.3L Eng. - 17.70 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CX-9</b>		
18 - 16	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
15 - 14	6 Cyl 3.7L Eng. - 24.16 Oz. R-134a; 5.40 Oz. PAG-46	59007
12 - 09	6 Cyl 3.7L Eng. - 5.50 Oz. PAG-46; 23.00-25.00 Oz. R-134a	59007
08	6 Cyl 3.7L Eng. - 23.00-25.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
07	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
<b>GLC</b>		
85 - 83	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 79	4 Cyl 1.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 77	4 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MAZDA 2</b>		
14	4 Cyl 1.5L Eng. - 16.48 Oz. R-134a; 5.75 Oz. PAG-100	59002
13 - 11	4 Cyl 1.5L Eng. - 15.70-17.40 Oz. R-134a; 3.72 Oz. PAG-46	59007
<b>MAZDA 3</b>		
18 - 17	4 Cyl 2.0L Eng. - 16.96 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 17	4 Cyl 2.5L Eng. - 16.96 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 11	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 11	4 Cyl 2.3L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13 - 11	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	4 Cyl 2.0L Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	4 Cyl 2.3L Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	4 Cyl 2.5L Eng. - 17.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
09	4 Cyl 2.3L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 04	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>MAZDA 5</b>		
15 - 14	4 Cyl 2.5L Eng. - 17.60 Oz. R-134a; 4.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MAZDA

Year	Description	Lubricant
<b>MAZDA 5</b>		
13 - 12	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10	4 Cyl 2.3L Eng. - 18.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
09	4 Cyl 2.3L Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 5.08 Oz. PAG-46	59007
07 - 06	All Eng. - 18.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
<b>MAZDA 6</b>		
17 - 14	4 Cyl 2.5L Eng. - 4.00 Oz. PAG-46; 17.60-19.40 Oz. R-134a	59007
13	4 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
13	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
12 - 11	4 Cyl 2.5L Eng. - 4.10 Oz. PAG-46; 17.60-19.40 Oz. R-134a	59007
12 - 11	6 Cyl 3.7L Eng. - 4.10 Oz. PAG-46; 17.60-19.40 Oz. R-134a	59007
10 - 09	4 Cyl 2.5L Eng. - 17.60-19.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 09	6 Cyl 3.7L Eng. - 17.60-19.40 Oz. R-134a; 4.06 Oz. PAG-46	59007
08 - 05	All Eng. - 16.80 Oz. R-134a; 5.07 Oz. PAG-46	59007
04 - 03	All Eng. - 17.60 Oz. R-134a; 5.07 Oz. PAG-46	59007
<b>MIATA</b>		
17 - 14	4 Cyl 2.0L Eng. - MX-5 Miata, 15.84 Oz. R-134a; 4.40 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; 4.39 Oz. PAG-46	59007
08 - 06	All Eng. - 16.00 Oz. R-134a; 4.39 Oz. PAG-46	59007
05	All Eng. - 14.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
04	All Eng. - 14.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
03 - 01	All Eng. - 5.00 Oz. PAG-100; 14.00 Oz. R-134a	59002
00 - 99	All Eng. - 20.00 Oz. R-134a; 8.75 Oz. PAG-100	59002
97 - 94	All Eng. - 21.00 Oz. R-134a; 8.75 Oz. PAG-100	59002
93	All Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 90	All Eng. - 29.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MILLENNIA</b>		
02 - 95	All Eng. - 6.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
<b>MPV</b>		
06 - 03	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
06 - 03	All Eng. - w/o Rear AC; 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
02 - 00	All Eng. - w/ Rear AC; 30.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
02 - 00	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
98 - 97	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
98 - 97	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
96 - 95	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
96 - 95	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	All Eng. - w/ Rear AC; 8.75 Oz. PAG-46; 44.00 Oz. R-134a	59007
94	All Eng. - w/o Rear AC; 8.75 Oz. PAG-46; 37.00 Oz. R-134a	59007
93 - 91	All Eng. - w/ Rear AC; 6.50 Oz. Mineral Oil; 49.50 Oz. R-12	59000 <sup>(1)</sup>
93 - 91	All Eng. - w/o Rear AC; 43.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - w/ Rear AC; 49.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - w/o Rear AC; 42.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MX-3</b>		
95 - 94	All Eng. - 26.50 Oz. R-134a; 6.25 Oz. PAG-100	59002
93 - 92	All Eng. - 28.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MX-5</b>		
13 - 10	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
08 - 06	All Eng. - 16.00 Oz. R-134a; 4.39 Oz. PAG-46	59007
<b>MX-6</b>		
97	All Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
96 - 94	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
93 - 89	All Eng. - 6.00 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MAZDA

Year	Description	Lubricant
<b>MX-6</b>		
88	All Eng. - 37.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>NAVAJO</b>		
94	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
94	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
93 - 91	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>PROTEGE</b>		
03 - 02	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
03 - 01	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
01 - 99	4 Cyl 1.6L Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
00 - 95	4 Cyl 1.8L Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
98 - 95	4 Cyl 1.5L Eng. - 21.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
94	4 Cyl 1.8L Eng. - 28.00 Oz. R-12; 3.88-4.56 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	4 Cyl 1.8L Eng. - 28.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>PROTEGE5</b>		
03	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 5.07 Oz. PAG-46	59007
02	All Eng. - 5.00 Oz. PAG-46; 18.50 Oz. R-134a	59007
<b>Rotary Pickup</b>		
77 - 76	2 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RX-2</b>		
74 - 72	2 Cyl 1.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RX-3</b>		
78 - 72	2 Cyl 1.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RX-4</b>		
78 - 74	2 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RX-7</b>		
95 - 94	All Eng. - 19.00 Oz. R-134a; 5.75 Oz. PAG-100	59002
93	All Eng. - 5.00 Oz. Mineral Oil; 22.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 29.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Denso Compressor; 29.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	2 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 79	2 Cyl 1.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>RX-8</b>		
11 - 09	2 Cyl 1.3L Eng. - 15.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 04	All Eng. - 7.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>TRIBUTE</b>		
11	4 Cyl 2.5L Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
11 - 09	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
10	4 Cyl 2.5L Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
09	4 Cyl 2.5L Eng. - Electric/Gas, 38.00 Oz. R-134a; 5.00 Oz. Hybrid Oil	59889
09	4 Cyl 2.5L Eng. - Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
08	All Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
06 - 01	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

## MERCEDES-BENZ

Year	Description	Lubricant
<b>190 SERIES</b>		
93 - 89	All Eng. - 190E, 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 190D, 7.50 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	6 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 86	5 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 84	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>220 SERIES</b>		
73 - 68	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>230 SERIES</b>		
78 - 74	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68 - 65	6 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>240 SERIES</b>		
83 - 76	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>260 SERIES</b>		
89 - 87	6 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>280 SERIES</b>		
81 - 77	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>300 SERIES</b>		
18	All Eng. - 300, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93	All Eng. - 300CE, 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 300CE, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300D, 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 300D, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300E, 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 300E, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300SD, w/ R12; w/o Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300SE, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300SE, w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93	All Eng. - 300SL, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300SL, w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93	All Eng. - 300TE, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 300TE, w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93 - 92	All Eng. - 300SD, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93 - 92	All Eng. - 300SD, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
92	6 Cyl 3.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	6 Cyl 3.0L Eng. - w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
92 - 91	All Eng. - 300D, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 90	All Eng. - 300SL, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 300CE, 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 300E, 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 300TE, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 89	All Eng. - 300SE, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 300SEL, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 300D, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 86	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 77	5 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>350 SERIES</b>		
91	All Eng. - 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 350SDL, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>380 SERIES</b>		
85 - 81	8 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>400 SERIES</b>		
93	All Eng. - 400E, 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 400SEL, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93	All Eng. - 400SEL, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
92	All Eng. - 400E, w/ Rear AC; 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 400E, w/o Rear AC; 39.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 400SE, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
92	All Eng. - 400SE, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>420 SERIES</b>		
91 - 89	All Eng. - 420SEL, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>450 SERIES</b>		
80 - 73	8 Cyl 4.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>500 SERIES</b>		
93	All Eng. - 500E, 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 500SEC, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93	All Eng. - 500SEC, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 500SL, w/ R134a; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93 - 92	All Eng. - 500SEL, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93 - 92	All Eng. - 500SEL, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
92	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
92	All Eng. - 500E, w/ Rear AC; 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 500E, w/o Rear AC; 39.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 500SL, w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 90	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>560 SERIES</b>		
91 - 89	All Eng. - 560SEC, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 560SEL, 46.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 560SL, See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 86	8 Cyl 5.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>600 SERIES</b>		
93	All Eng. - 600SEC, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93	All Eng. - 600SEC, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - 600SL, w/o Rear AC; 33.50 Oz. R-134a; 5.00 Oz. PAG-46	59007
93 - 92	All Eng. - 600SEL, w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
93 - 92	All Eng. - 600SEL, w/o Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>B200</b>		
11	4 Cyl 2.0L Eng. - 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>B250</b>		
16	4 Cyl 2.0L Eng. - B250, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>B250e</b>		
16	All Eng. - Electric, B250e, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59234
<b>C160</b>		
04	4 Cyl 1.8L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 02	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>C180</b>		
14 - 12	4 Cyl 1.8L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05 - 04	4 Cyl 1.8L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 94	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C200</b>		
14 - 12	4 Cyl 1.8L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05 - 04	4 Cyl 1.8L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 94	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C220 / C220d</b>		
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 94	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C230</b>		
11	6 Cyl 2.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl 2.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
07 - 06	6 Cyl 2.5L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
05	6 Cyl 2.6L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
05 - 04	4 Cyl 1.8L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 95	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>C240</b>		
06	6 Cyl 2.5L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
05 - 04	6 Cyl 2.6L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 95	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C250 / C250d</b>		
14 - 12	4 Cyl 1.8L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	6 Cyl 2.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl 2.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>C270</b>		
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C280</b>		
12 - 08	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07 - 06	6 Cyl 3.0L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
06	6 Cyl 3.5L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
00 - 94	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C300 / C300d</b>		
17	4 Cyl 2.0L Eng. - Gas, C300, 20.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	4 Cyl 2.0L Eng. - C300, 2.80 Oz. PAG-46; 20.80 Oz. R-134a	59007
14 - 13	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 08	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>C32 AMG</b>		
04	6 Cyl 3.2L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 02	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>C320</b>		
05 - 04	6 Cyl 3.2L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
03 - 01	All Eng. - 4.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C350</b>		
14 - 08	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07 - 06	6 Cyl 3.5L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
<b>C350e</b>		
17 - 16	4 Cyl 2.0L Eng. - Electric/Gas, C350e, 24.00 Oz. R-134a; 4.20 Oz. POE Oil	59889
<b>C36 AMG</b>		
97 - 95	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C43 AMG</b>		
17	6 Cyl 3.0L Eng. - C43 AMG, 20.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
00 - 98	All Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>C450 AMG</b>		
16	6 Cyl 3.0L Eng. - C450 AMG, 21.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>C55 AMG</b>		
06	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05	8 Cyl 5.5L Eng. - 30.00 Oz. R-134a; 5.20 Oz. PAG-46	59007
<b>C63 AMG / C63 AMG S</b>		
17	8 Cyl 4.0L Eng. - C63 AMG, 20.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	8 Cyl 4.0L Eng. - C63 S AMG, 20.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	8 Cyl 4.0L Eng. - C63 AMG, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
16	8 Cyl 4.0L Eng. - C63 S AMG, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
14 - 12	8 Cyl 6.3L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13 - 10	8 Cyl 6.2L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 6.3L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl 6.3L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
09	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>C63 AMG / C63 AMG S</b>		
08	8 Cyl 6.3L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CL500</b>		
14	8 Cyl 4.6L Eng. - 3.70 Oz. PAG-46; 37.60 Oz. R-134a	59007
13	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12 - 11	8 Cyl 4.6L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	12 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
10	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
09 - 08	8 Cyl 5.5L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl 5.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05 - 01	All Eng. - w/ Rear AC; 33.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 98	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>CL55 AMG</b>		
06	8 Cyl 5.5L Eng. - 26.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05 - 01	All Eng. - w/ Rear AC; 33.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
00	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 41.50 Oz. R-134a	59007
00	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>CL550</b>		
14	8 Cyl 4.6L Eng. - 3.70 Oz. PAG-46; 37.60 Oz. R-134a	59007
13	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	8 Cyl 4.6L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
09 - 08	8 Cyl 5.5L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl 5.5L Eng. - 26.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CL600</b>		
14	12 Cyl 5.5L Eng. - 29.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
13 - 10	12 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
09 - 08	12 Cyl 5.5L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07	12 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
06	12 Cyl 5.5L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 01	All Eng. - w/ Rear AC; 33.50 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 98	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>CL63 AMG</b>		
14	8 Cyl 5.5L Eng. - 4.00 Oz. PAG-46; 37.60 Oz. R-134a	59007
13	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12 - 11	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
10	8 Cyl 6.3L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CL65 AMG</b>		
14	12 Cyl 6.0L Eng. - 3.70 Oz. PAG-46; 37.60 Oz. R-134a	59007
13 - 11	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
10	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
09 - 08	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
06	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 03	All Eng. - w/ Rear AC; 33.50 Oz. R-134a; 4.00 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>CLA250</b>		
17 - 16	4 Cyl 2.0L Eng. - CLA250, 23.52 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CLA45 AMG</b>		
17 - 16	4 Cyl 2.0L Eng. - CLA45 AMG, 23.52 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CLK200</b>		
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CLK230</b>		
02 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CLK240</b>		
04 - 02	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>CLK270</b>		
03	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>CLK320</b>		
05	6 Cyl 3.2L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CLK350</b>		
09 - 08	6 Cyl 3.5L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07 - 06	6 Cyl 3.5L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CLK430</b>		
03 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CLK500</b>		
09 - 07	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl 5.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
05	8 Cyl 5.0L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
04 - 02	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>CLK55 AMG</b>		
06 - 05	8 Cyl 5.5L Eng. - 26.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CLK550</b>		
09 - 07	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLK63 AMG</b>		
09 - 07	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLS350</b>		
12	8 Cyl 4.6L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLS400</b>		
17 - 16	6 Cyl 3.0L Eng. - CLS400, 21.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>CLS500</b>		
14	8 Cyl 4.6L Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
13	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 4.7L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 4.6L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 06	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
06	8 Cyl 5.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLS55 AMG</b>		
10	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 06	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLS550</b>		
17 - 16	8 Cyl 4.6L Eng. - CLS550, 21.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>CLS550</b>		
14	8 Cyl 4.6L Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
13	8 Cyl 4.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 4.7L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 4.6L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 07	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>CLS63 AMG / CLS63 AMG S</b>		
17 - 16	8 Cyl 5.5L Eng. - CLS63 AMG, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	8 Cyl 5.5L Eng. - 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
13 - 12	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 6.3L Eng. - 34.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 07	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>E200</b>		
13	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 22.40 Oz. R-134a	59007
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E220 / E220d</b>		
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E230</b>		
97 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E240</b>		
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 97	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E250</b>		
16	4 Cyl 2.1L Eng. - Diesel, E250, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
13	4 Cyl 1.8L Eng. - 4.00 Oz. PAG-46; 22.40 Oz. R-134a	59007
12	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
00 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E270</b>		
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E280</b>		
11	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10	6 Cyl 3.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E290</b>		
99 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E300 / E300 Turbo Diesel</b>		
17	4 Cyl 2.0L Eng. - E300, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.5L Eng. - 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 12	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13 - 12	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>E300 / E300 Turbo Diesel</b>		
11	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10	6 Cyl 3.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
99 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E320 / E320 CDI</b>		
11	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10	6 Cyl 3.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	6 Cyl 3.2L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E350 / E350d</b>		
16	6 Cyl 3.5L Eng. - E350, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
14	6 Cyl 3.5L Eng. - 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 12	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13 - 12	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
11 - 10	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	6 Cyl 3.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07 - 06	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 04	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>E400</b>		
17	6 Cyl 3.0L Eng. - E400, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - E400, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
14	6 Cyl 3.5L Eng. - 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>E420</b>		
99 - 96	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
95 - 94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>E43 AMG</b>		
17	6 Cyl 3.0L Eng. - E43 AMG, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>E430</b>		
03 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 97	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E50 AMG</b>		
97	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E500</b>		
14	8 Cyl 4.6L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
13 - 12	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13 - 12	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 09	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08 - 06	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06	8 Cyl 5.0L Eng. - 34.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 02	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
94	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>E55 AMG</b>		
06	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 01	All Eng. - 35.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 97	All Eng. - 33.50 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>E550</b>		
17	8 Cyl 4.6L Eng. - E550, 21.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	8 Cyl 4.6L Eng. - E550, 4.00 Oz. PAG-46; 21.60 Oz. R-134a	59007
14	8 Cyl 4.6L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
13 - 12	8 Cyl 4.6L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 09	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08 - 07	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>E63 AMG / E63 AMG S</b>		
13 - 12	8 Cyl 5.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10	8 Cyl 6.2L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 09	8 Cyl 6.3L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>G500</b>		
14	8 Cyl 5.5L Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
13	12 Cyl 6.0L Eng. - 36.80 Oz. R-134a; 6.10 Oz. PAG-46	59007
13	8 Cyl 5.5L Eng. - 31.00 Oz. R-134a; 6.08 Oz. PAG-46, From 1/1/13	59007
13	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 6.08 Oz. PAG-46, To 12/31/13	59007
12	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.4L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.4L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
09 - 08	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
08	8 Cyl 5.0L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
07	8 Cyl 5.0L Eng. - 37.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06 - 02	8 Cyl 5.0L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
<b>G55 AMG</b>		
14	8 Cyl 5.5L Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
13	8 Cyl 5.5L Eng. - 31.00 Oz. R-134a; 6.08 Oz. PAG-46, From 1/1/13	59007
13	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 6.08 Oz. PAG-46, To 12/31/13	59007
12	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.4L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.4L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
09 - 08	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
08	8 Cyl 5.0L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
07	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06 - 03	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
<b>G550 / G550 4x4</b>		
17 - 16	8 Cyl 4.0L Eng. - G550, 36.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	8 Cyl 5.5L Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
13	8 Cyl 5.5L Eng. - 31.00 Oz. R-134a; 6.08 Oz. PAG-46, From 1/1/13	59007
13	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 6.08 Oz. PAG-46, To 12/31/13	59007
12	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.4L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.4L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
10	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
09	8 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.75 Oz. PAG-46	59007



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>G63 AMG</b>		
17	8 Cyl 5.5L Eng. - G63 AMG, 36.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	8 Cyl 5.5L Eng. - G63 AMG, 4.70 Oz. PAG-46; 36.80 Oz. R-134a	59007
14	8 Cyl 5.5L Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-46	59007
13	8 Cyl 5.5L Eng. - 31.00 Oz. R-134a; 6.08 Oz. PAG-46, From 1/1/13	59007
13	8 Cyl 5.5L Eng. - 35.00 Oz. R-134a; 6.08 Oz. PAG-46, To 12/31/13	59007
<b>G65 AMG</b>		
17 - 16	8 Cyl 6.0L Eng. - G65 AMG, 36.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	12 Cyl 6.0L Eng. - 36.80 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>GL320 / GL320 BlueTec / GL320 CDI</b>		
11	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	6 Cyl 3.0L Eng. - 43.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GL350</b>		
14	6 Cyl 3.0L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
12 - 10	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
<b>GL450</b>		
13	8 Cyl 4.6L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13	8 Cyl 4.7L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
12 - 08	8 Cyl 4.6L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 08	8 Cyl 4.6L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	8 Cyl 4.6L Eng. - 43.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GL500</b>		
13	8 Cyl 4.6L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13	8 Cyl 4.7L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
12 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>GL550</b>		
13	8 Cyl 4.6L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13	8 Cyl 4.7L Eng. - 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
12 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>GL63 AMG</b>		
13	8 Cyl 5.5L Eng. - w/o Rear AC; 37.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
<b>GLA250</b>		
17 - 16	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLA45 AMG</b>		
17 - 15	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLC300 / GLC300e</b>		
17 - 16	4 Cyl 2.0L Eng. - GLC300, 22.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLE300d</b>		
16	4 Cyl 2.1L Eng. - Diesel, GLE300d, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLE350</b>		
17 - 16	6 Cyl 3.5L Eng. - GLE350, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLE400</b>		
16	6 Cyl 3.0L Eng. - GLE400, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLE450 / GLE450 AMG</b>		
16	6 Cyl 3.0L Eng. - GLE450 AMG, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLE63 AMG / GLE63 AMG S</b>		
16	8 Cyl 5.5L Eng. - GLE63 AMG, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	8 Cyl 5.5L Eng. - GLE63 S AMG, 37.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>GLK300</b>		
14	6 Cyl 3.5L Eng. - 43.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 11	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>GLK350</b>		
14	6 Cyl 3.5L Eng. - 43.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 10	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>Metris</b>		
17 - 16	4 Cyl 2.0L Eng. - 21.28 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>ML230</b>		
00 - 98	All Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>ML270</b>		
04	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>ML300</b>		
11	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>ML320 / ML320 Bluetec</b>		
11 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
03 - 01	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 98	All Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>ML350</b>		
14	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13 - 12	6 Cyl 3.0L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
13 - 12	6 Cyl 3.5L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
12	8 Cyl 4.7L Eng. - 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
11 - 10	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11 - 10	8 Cyl 5.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 10	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11 - 08	6 Cyl 3.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07 - 06	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 02	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>ML430</b>		
02 - 01	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 98	All Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>ML450</b>		
11 - 10	6 Cyl 3.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>ML500</b>		
13 - 12	8 Cyl 4.6L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13 - 12	8 Cyl 4.6L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
13 - 12	8 Cyl 4.7L Eng. - 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
12	8 Cyl 5.5L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
11 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07 - 06	8 Cyl 5.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
05 - 01	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
<b>ML55 AMG</b>		
05 - 01	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
00 - 99	All Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>ML550</b>		
13 - 12	8 Cyl 4.6L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13 - 12	8 Cyl 4.6L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
13 - 12	8 Cyl 4.7L Eng. - 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
11 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
<b>ML63 AMG</b>		
13 - 12	8 Cyl 5.5L Eng. - w/ Rear AC; 46.00 Oz. R-134a; 5.40 Oz. PAG-46	59007
13 - 12	8 Cyl 5.5L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
11 - 08	8 Cyl 6.3L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	8 Cyl 6.3L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>ML63 AMG</b>		
10	8 Cyl 6.2L Eng. - 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	8 Cyl 6.3L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>R280</b>		
12 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11 - 08	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07	6 Cyl 3.0L Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007
<b>R300</b>		
12 - 09	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11 - 09	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
<b>R320 / R320 Bluetec / R320 CDI</b>		
11 - 08	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
07	6 Cyl 3.0L Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007
<b>R350</b>		
13	6 Cyl 3.0L Eng. - 27.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
12 - 10	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
12 - 08	6 Cyl 3.5L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 08	6 Cyl 3.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 34.00 Oz. R-134a	59007
11 - 10	6 Cyl 3.0L Eng. - w/ Rear AC; 43.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07 - 06	6 Cyl 3.5L Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007
<b>R500</b>		
07 - 06	8 Cyl 5.0L Eng. - 34.00 Oz. R-134a; 5.91 Oz. PAG-46	59007
<b>R63 AMG</b>		
07	8 Cyl 6.3L Eng. - 43.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>S280</b>		
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S300</b>		
13	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
97	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
97	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S320</b>		
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
04 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
00 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S350 / S350d</b>		
13	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
13 - 12	12 Cyl 5.5L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
13 - 11	6 Cyl 3.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12	12 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12 - 11	6 Cyl 3.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
12 - 11	6 Cyl 3.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - w/o Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
06	6 Cyl 3.7L Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 02	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 02	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
95 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S400 / S400d / S400L</b>		
13	6 Cyl 3.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>S400 / S400d / S400L</b>		
13 - 11	6 Cyl 3.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12 - 11	6 Cyl 3.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
12 - 11	6 Cyl 3.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
10	6 Cyl 3.5L Eng. - w/o Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S420</b>		
99 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
99 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S430</b>		
06	8 Cyl 4.3L Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00 - 99	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 99	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S450</b>		
11 - 10	8 Cyl 4.6L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
09 - 08	8 Cyl 4.6L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
<b>S500 / S500L</b>		
13	8 Cyl 4.6L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 4.6L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
13	8 Cyl 4.6L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
13	8 Cyl 5.5L Eng. - 42.00 Oz. R-134a; 3.72 Oz. PAG-46, w/ 7SEU17C	59007
13	8 Cyl 5.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
11	12 Cyl 5.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
11	12 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 4.6L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 10	12 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
09 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07 - 06	8 Cyl 5.5L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06	8 Cyl 5.0L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S55 AMG</b>		
06	8 Cyl 5.5L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S550 / S550 Maybach</b>		
13 - 12	8 Cyl 4.6L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 12	8 Cyl 4.6L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
13 - 12	8 Cyl 4.6L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>S550 / S550 Maybach</b>		
11	8 Cyl 4.6L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11 - 08	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
09 - 08	8 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
07	8 Cyl 5.5L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
<b>S550e</b>		
17 - 16	6 Cyl 3.0L Eng. - Electric/Gas, S550e, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
<b>S600 / S600 Maybach</b>		
17 - 15	12 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
13 - 12	12 Cyl 5.5L Eng. - w/o Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 11	12 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	12 Cyl 5.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
11 - 09	12 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
09 - 08	12 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
07	12 Cyl 5.5L Eng. - 3.72-5.41 Oz. PAG-46; 41.00 Oz. R-134a	59007
06	12 Cyl 5.5L Eng. - 37.00 Oz. R-134a; 5.41 Oz. PAG-46	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 01	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
00 - 94	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
00 - 94	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S600L</b>		
95	All Eng. - w/ Rear AC; 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
95	All Eng. - w/o Rear AC; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>S63 AMG / S63L AMG</b>		
14	8 Cyl 5.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
13	8 Cyl 5.5L Eng. - 42.00 Oz. R-134a; 3.72 Oz. PAG-46, w/ 7SEU17C	59007
13	8 Cyl 5.5L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
13	8 Cyl 6.2L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
12	8 Cyl 6.2L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 10	12 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
12 - 10	12 Cyl 6.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11	8 Cyl 5.5L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	8 Cyl 5.5L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
11 - 10	8 Cyl 6.2L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
10	8 Cyl 6.3L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10 - 08	8 Cyl 6.3L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
10 - 08	8 Cyl 6.3L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
<b>S65 AMG / S65L AMG</b>		
13	12 Cyl 6.0L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 09	12 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
13 - 08	12 Cyl 6.0L Eng. - w/o Rear AC; 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
07	12 Cyl 6.0L Eng. - 3.72-5.41 Oz. PAG-46; 41.00 Oz. R-134a	59007
06	12 Cyl 6.0L Eng. - 3.72-5.41 Oz. PAG-46; 37.00 Oz. R-134a	59007
05	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
05 - 04	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 6.00 Oz. PAG-46	59007
04	All Eng. - w/ Rear AC; 6.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
<b>SL320</b>		
00 - 94	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SL350</b>		
05 - 03	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>SL500</b>		
14	8 Cyl 4.6L Eng. - 22.08 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>SL500</b>		
13	8 Cyl 4.6L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13	8 Cyl 4.7L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
11 - 10	12 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
08	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
07 - 06	8 Cyl 5.5L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
06	8 Cyl 5.0L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05 - 01	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 94	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SL55 AMG</b>		
11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
08	12 Cyl 5.5L Eng. - 33.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
08	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
08	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
07 - 06	8 Cyl 5.5L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05 - 01	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 99	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SL550</b>		
17 - 16	8 Cyl 4.6L Eng. - SL550, 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	8 Cyl 4.6L Eng. - 22.08 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	8 Cyl 4.6L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
13	8 Cyl 4.7L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
11	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
09	8 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
08	8 Cyl 5.5L Eng. - 3.72 Oz. PAG-46; 33.00 Oz. R-134a	59007
07	8 Cyl 5.5L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
<b>SL60 AMG</b>		
99 - 97	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SL600</b>		
12	12 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	12 Cyl 5.5L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	12 Cyl 5.5L Eng. - 33.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07 - 06	12 Cyl 5.5L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05 - 01	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00 - 94	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SL63 AMG</b>		
17 - 16	8 Cyl 5.5L Eng. - SL63 AMG, 22.08 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	8 Cyl 5.5L Eng. - 20.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	8 Cyl 6.2L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 11	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
12 - 09	8 Cyl 6.3L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
11	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
<b>SL65 AMG</b>		
19 - 15	12 Cyl 6.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59234



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>SL65 AMG</b>		
14	12 Cyl 6.0L Eng. - 8.50 Oz. PAG-46; 41.50 Oz. R-134a	59007
13	12 Cyl 6.0L Eng. - 3.72 Oz. PAG-46; 38.00 Oz. R-134a	59007
13	12 Cyl 6.0L Eng. - w/ Armored Body; w/ Rear AC; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	12 Cyl 6.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 3.72 Oz. PAG-46	59007
11	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
08	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.06 Oz. PAG-46, w/ 7SEU16C	59007
08	12 Cyl 6.0L Eng. - 33.00 Oz. R-134a; 4.74 Oz. PAG-46, w/ 7SEU17C	59007
07 - 06	12 Cyl 6.0L Eng. - 32.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
05 - 04	All Eng. - 29.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>SLK200</b>		
14	4 Cyl 1.8L Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
13 - 12	4 Cyl 1.8L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
12 - 10	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 23.20 Oz. R-134a	59007
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SLK230</b>		
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 98	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SLK250</b>		
14	4 Cyl 1.8L Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
13 - 12	4 Cyl 1.8L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>SLK280</b>		
11 - 08	6 Cyl 3.0L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 08	6 Cyl 3.0L Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07 - 06	6 Cyl 3.0L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
<b>SLK300</b>		
11 - 09	6 Cyl 3.0L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 09	6 Cyl 3.0L Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>SLK32 AMG</b>		
04 - 02	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>SLK320</b>		
04 - 01	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
<b>SLK350</b>		
14	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
13	6 Cyl 3.5L Eng. - 20.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
12 - 10	6 Cyl 3.5L Eng. - 4.00 Oz. PAG-46; 23.20 Oz. R-134a	59007
09 - 08	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
09 - 08	6 Cyl 3.5L Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06 - 05	6 Cyl 3.5L Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
04	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>SLK55 AMG</b>		
14	8 Cyl 5.5L Eng. - 4.00 Oz. PAG-46; 20.80 Oz. R-134a	59007
13 - 12	8 Cyl 5.5L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11 - 10	8 Cyl 5.4L Eng. - 19.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
10 - 08	8 Cyl 5.5L Eng. - 23.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
07	8 Cyl 5.5L Eng. - 24.00 Oz. R-134a; 4.05 Oz. PAG-46	59007
06 - 05	8 Cyl 5.5L Eng. - 24.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
04	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>SLS AMG</b>		
13	8 Cyl 6.2L Eng. - 28.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12	8 Cyl 6.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
11	8 Cyl 6.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCEDES-BENZ

Year	Description	Lubricant
<b>Sprinter</b>		
14	4 Cyl 2.1L Eng. - Diesel, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>Sprinter 2500</b>		
17 - 16	6 Cyl 3.0L Eng. - Diesel, Sprinter 2500, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
17 - 15	4 Cyl 2.1L Eng. - Diesel, Sprinter 2500, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
14	4 Cyl 2.1L Eng. - Diesel, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - Diesel, 35.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
13 - 10	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 6.40 Oz. PAG-46, Code HH9	59007
13 - 10	6 Cyl 3.0L Eng. - 35.00 Oz. R-134a; 6.40 Oz. PAG-46, Code H08	59007
13 - 10	6 Cyl 3.0L Eng. - 42.00 Oz. R-134a; 6.40 Oz. PAG-46, w/ Option Code HH7	59007
13 - 10	6 Cyl 3.0L Eng. - 5.40 Oz. PAG-46; 63.00 Oz. R-134a, w/ Option Code HK4	59007
<b>Sprinter 3500</b>		
17 - 16	6 Cyl 3.0L Eng. - Diesel, Sprinter 3500, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
17 - 15	4 Cyl 2.1L Eng. - Diesel, Sprinter 3500, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
14	4 Cyl 2.1L Eng. - Diesel, See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - Diesel, 35.00 Oz. R-134a; 6.40 Oz. PAG-46	59007
13 - 10	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 6.40 Oz. PAG-46, Code HH9	59007
13 - 10	6 Cyl 3.0L Eng. - 35.00 Oz. R-134a; 6.40 Oz. PAG-46, Code H08	59007
13 - 10	6 Cyl 3.0L Eng. - 42.00 Oz. R-134a; 6.40 Oz. PAG-46, w/ Option Code HH7	59007
13 - 10	6 Cyl 3.0L Eng. - 5.40 Oz. PAG-46; 63.00 Oz. R-134a, w/ Option Code HK4	59007

## MERCURY

Year	Description	Lubricant
<b>CAPRI</b>		
94	All Eng. - 10.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
93 - 91	All Eng. - 10.00 Oz. Mineral Oil; 25.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 83	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 82	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>COLONY PARK</b>		
91 - 85	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>COMET</b>		
77 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>COUGAR</b>		
02 - 00	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
99	All Eng. - 26.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
97 - 95	All Eng. - 36.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93 - 89	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 40.00 Oz. R-12, To 1/86	59000 <sup>(1)</sup>
86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil, From 1/86	59000 <sup>(1)</sup>
85 - 83	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 80	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 77	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	6 Cyl 3.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 70	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 73	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70	8 Cyl 6.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>GRAND MARQUIS</b>		
11 - 09	8 Cyl 4.6L Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 06	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 97	All Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
96 - 95	All Eng. - 7.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
94	All Eng. - 7.00 Oz. PAG-46; 34.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCURY

Year	Description	Lubricant
<b>GRAND MARQUIS</b>		
93	8 Cyl 4.6L Eng. - 36.00 Oz. R-134a; 7.00 Oz. Mineral Oil	59007
93	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 13.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12, To 9/86	59000 <sup>(1)</sup>
87	All Eng. - 13.00 Oz. Mineral Oil; 52.00 Oz. R-12, From 9/86	59000 <sup>(1)</sup>
86	8 Cyl 5.8L Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 10.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 81	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 78	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LN7</b>		
83 - 82	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LYNX</b>		
87 - 85	4 Cyl 1.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 81	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MARAUDER</b>		
04 - 03	All Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
<b>MARINER</b>		
11	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
11 - 10	4 Cyl 2.5L Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
11 - 10	4 Cyl 2.5L Eng. - Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
10	All Eng. - Excl. Hybrid, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
09 - 08	All Eng. - Electric/Gas, 32.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
09 - 08	All Eng. - Gas, 5.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
07 - 06	4 Cyl 2.3L Eng. - Gas, 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 05	6 Cyl 3.0L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05	4 Cyl 2.3L Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>MARQUIS</b>		
84 - 83	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 81	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
82 - 79	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81 - 78	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
78 - 75	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MILAN</b>		
11 - 10	4 Cyl 2.5L Eng. - Electric/Gas, 22.00 Oz. R-134a; 4.40 Oz. Hybrid Oil	59889
11 - 09	6 Cyl 3.0L Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	4 Cyl 2.3L Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>MONARCH</b>		
80	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 78	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80 - 78	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
75	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTEGO</b>		
07 - 05	All Eng. - w/ Rear AC; 9.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
07 - 05	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
76 - 74	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
76 - 71	8 Cyl 5.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCURY

Year	Description	Lubricant
<b>MONTEGO</b>		
74 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTEREY</b>		
07 - 04	All Eng. - w/ Rear AC; 12.00 Oz. PAG-46; 53.00 Oz. R-134a	59007
07 - 04	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
<b>MOUNTAINEER</b>		
10	8 Cyl 4.6L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 47.00 Oz. R-134a	59007
10	8 Cyl 4.6L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
10 - 09	6 Cyl 4.0L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 47.00 Oz. R-134a	59007
10 - 09	6 Cyl 4.0L Eng. - w/o Rear AC; 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
09	8 Cyl 4.6L Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 44.00 Oz. R-134a	59007
09	8 Cyl 4.6L Eng. - w/o Rear AC; 27.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
08 - 06	All Eng. - w/ Rear AC; 16.00 Oz. PAG-46; 47.00 Oz. R-134a	59007
08 - 06	All Eng. - w/o Rear AC; 31.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/ Rear AC; 56.00 Oz. R-134a; 13.00 Oz. PAG-46	59007
05 - 02	All Eng. - w/o Rear AC; 9.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
01 - 98	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
97	All Eng. - 9.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>MYSTIQUE</b>		
00 - 95	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>SABLE</b>		
09 - 08	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46, w/ Front AC	59007
09 - 08	All Eng. - w/ Rear AC; 36.00 Oz. R-134a; 9.50 Oz. PAG-46	59007
05 - 96	All Eng. - 34.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95 - 94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 92	6 Cyl 3.0L Eng. - 5.00 Oz. PAG-46; 19.50 Oz. R-134a	59007
92 - 91	All Eng. - 40.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 10.00 Oz. Mineral Oil; 44.00 Oz. R-12	59000 <sup>(1)</sup>
<b>TOPAZ</b>		
94	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 8.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 89	All Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	4 Cyl 2.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TRACER</b>		
99	All Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
97	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
96 - 94	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 34.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 34.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 10.00 Oz. Mineral Oil; 31.00 Oz. R-12	59000 <sup>(1)</sup>
87	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>VILLAGER</b>		
02 - 00	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
02 - 99	All Eng. - w/ Rear AC; 52.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
99 - 98	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
98 - 94	All Eng. - w/ Rear AC; 52.00 Oz. R-134a; 10.00 Oz. PAG-100	59002
97 - 94	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
93	All Eng. - w/ Rear AC; 10.00 Oz. Mineral Oil; 56.00 Oz. R-12	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ZEPHYR</b>		
82 - 80	8 Cyl 4.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MERCURY

Year	Description	Lubricant
------	-------------	-----------

### ZEPHYR

79 - 78	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
---------	---	----------------------

## MERKUR

Year	Description	Lubricant
------	-------------	-----------

### SCORPIO

89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
----	---	----------------------

### XR4TI

89	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
----	---	----------------------

## MINI

Year	Description	Lubricant
------	-------------	-----------

### Cooper / JOHN COOPER WORKS

15 - 14	4 Cyl 1.5L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 1.6L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 2.0L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

### Cooper Countryman

15 - 14	4 Cyl 1.5L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 1.6L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

### Cooper Paceman

15 - 14	4 Cyl 1.5L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 1.6L Eng. - 17.26 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

## MITSUBISHI

Year	Description	Lubricant
------	-------------	-----------

### 3000GT

99 - 94	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
93	All Eng. - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil, From 10/92	59000 <sup>(1)</sup>
92	All Eng. - 34.00 Oz. R-12; 7.00 Oz. Mineral Oil, To 9/92	59000 <sup>(1)</sup>
91	All Eng. - 34.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

### CORDIA

88 - 84	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 84	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### DIAMANTE

04 - 00	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99 - 97	All Eng. - 24.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
96	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95 - 94	All Eng. - Sedan, 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
95 - 94	All Eng. - Wagon, 28.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
93	All Eng. - Sedan, 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - Wagon, 28.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

### ECLIPSE

12 - 09	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
12 - 09	6 Cyl 3.8L Eng. - 20.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
08 - 06	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 00	All Eng. - 5.50 Oz. PAG-46; 15.00 Oz. R-134a	59007
99 - 95	All Eng. - 26.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
94 - 90	All Eng. - 33.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

### ENDEAVOR

11 - 10	6 Cyl 3.8L Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
08 - 04	All Eng. - 21.00 Oz. R-134a; 4.75 Oz. PAG-46	59007

### EXPO

95 - 94	All Eng. - 27.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
93 - 92	All Eng. - 30.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

### EXPO LRV

94	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
----	---	----------------------

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MITSUBISHI

Year	Description	Lubricant
<b>GALANT</b>		
12 - 09	4 Cyl 2.4L Eng. - 4.70 Oz. PAG-46; 22.00 Oz. R-134a	59007
09	6 Cyl 3.8L Eng. - 4.70 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 06	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
05 - 00	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
99 - 97	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
96 - 94	All Eng. - 24.00 Oz. R-134a; 8.75 Oz. PAG-46	59007
93 - 89	All Eng. - 33.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LANCER</b>		
17 - 14	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 18.40 Oz. R-134a	59007
17 - 14	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 18.40 Oz. R-134a	59007
13 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
13 - 09	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
08	All Eng. - 4.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
07 - 03	All Eng. - 18.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
02	All Eng. - 18.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
<b>MIGHTY MAX</b>		
96 - 94	All Eng. - 28.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
93 - 90	All Eng. - 30.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 86	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 86	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MIRAGE</b>		
18 - 17	4 Cyl 1.2L Eng. - 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 17	4 Cyl 1.2L Eng. - Mirage G4, 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 1.2L Eng. - 18.40 Oz. R-134a; 2.00 Oz. PAG-46	59007
02	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
01 - 97	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
96 - 94	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 36.00 Oz. R-12; 8.06 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTERO</b>		
06 - 02	All Eng. - w/ Rear AC; 27.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 02	All Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
01	All Eng. - w/ Rear AC; 5.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
01	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
00 - 94	All Eng. - 23.00 Oz. R-134a; 5.75 Oz. PAG-46	59007
93 - 92	All Eng. - 28.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTERO SPORT</b>		
04 - 97	All Eng. - 24.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
<b>OUTLANDER</b>		
18 - 14	4 Cyl 2.0L Eng. - Outlander Sport, 3.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
18 - 14	4 Cyl 2.4L Eng. - 18.40 Oz. R-134a; 3.80 Oz. PAG-46	59007
18 - 14	4 Cyl 2.4L Eng. - Outlander Sport, 3.00 Oz. PAG-46; 19.20 Oz. R-134a	59007
18 - 14	6 Cyl 3.0L Eng. - 18.40 Oz. R-134a; 3.80 Oz. PAG-46	59007
13 - 11	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 08	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 08	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07 - 03	All Eng. - 19.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>PRECIS</b>		
93 - 90	All Eng. - 30.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 5.50 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## MITSUBISHI

Year	Description	Lubricant
<b>RAIDER</b>		
09	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07 - 06	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>SIGMA</b>		
90	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 32.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>STARION</b>		
89	All Eng. - 29.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TREDIA</b>		
88 - 85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>VAN</b>		
90 - 87	All Eng. - w/ Rear AC; 5.00 Oz. Mineral Oil; 52.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 87	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## NISSAN

Year	Description	Lubricant
<b>200 SERIES</b>		
98 - 95	All Eng. - 6.75 Oz. PAG-46; 25.00 Oz. R-134a	59007
88 - 87	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>240 SERIES</b>		
98 - 95	All Eng. - 8.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
94	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 6.75 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
<b>300 SERIES</b>		
96 - 94	All Eng. - 23.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
93 - 91	All Eng. - 30.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 34.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 6.75 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>350Z</b>		
09	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 19.50 Oz. R-134a	59007
08 - 07	All Eng. - 5.00 Oz. PAG-100; 19.50 Oz. R-134a	59002
06 - 03	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>370Z</b>		
18 - 14	6 Cyl 3.7L Eng. - 17.60 Oz. R-134a; 5.00 Oz. PAG-46	59007
13 - 09	6 Cyl 3.7L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
<b>720 PICKUP</b>		
86	All Eng. - 38.00 Oz. R-12; 8.50 Oz. Mineral Oil, To 6/86	59000 <sup>(1)</sup>
85	All Eng. - 38.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>ALTIMA</b>		
18 - 15	4 Cyl 2.5L Eng. - 19.36 Oz. R-134a; 4.30 Oz. PAG-46	59007
18 - 15	6 Cyl 3.5L Eng. - 19.36 Oz. R-134a; 4.30 Oz. PAG-46	59007
14	4 Cyl 2.5L Eng. - 5.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
14	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 19.36 Oz. R-134a	59007
13 - 12	4 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
13 - 12	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 09	4 Cyl 2.5L Eng. - Electric/Gas, 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
11 - 09	4 Cyl 2.5L Eng. - Gas, 19.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
11 - 09	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
09 - 07	All Eng. - Electric/Gas, 18.00 Oz. R-134a; 4.20 Oz. Hybrid Oil	59889
08	All Eng. - Gas, 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## NISSAN

Year	Description	Lubricant
<b>ALTIMA</b>		
07	All Eng. - Gas, 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
06 - 02	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
01	All Eng. - 6.75 Oz. PAG-100; 22.00 Oz. R-134a	59002
00 - 93	All Eng. - 6.75 Oz. PAG-100; 26.50 Oz. R-134a	59002
93	4 Cyl 2.4L Eng. - 6.75 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
<b>ARMADA</b>		
15 - 14	8 Cyl 5.6L Eng. - 38.08 Oz. R-134a; 9.80 Oz. PAG-46	59007
13 - 09	8 Cyl 5.6L Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
08 - 05	All Eng. - 38.00 Oz. R-134a; 9.80 Oz. PAG-46	59007
<b>AXXESS</b>		
90	All Eng. - 6.75 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
<b>CUBE</b>		
14 - 09	4 Cyl 1.8L Eng. - 16.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
<b>D21 PICKUP</b>		
94	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
94	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93	4 Cyl 2.4L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
92 - 90	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89 - 88	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 6.75 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil, From 6/86	59000 <sup>(1)</sup>
<b>FRONTIER</b>		
18 - 14	4 Cyl 2.5L Eng. - 6.00 Oz. PAG-100; 24.64 Oz. R-134a	59002
18 - 14	6 Cyl 4.0L Eng. - 6.00 Oz. PAG-100; 24.64 Oz. R-134a	59002
13 - 09	6 Cyl 4.0L Eng. - 6.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
12 - 11	4 Cyl 2.4L Eng. - 6.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
12 - 09	4 Cyl 2.5L Eng. - 6.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
08	All Eng. - 6.00 Oz. PAG-100; 26.50 Oz. R-134a	59002
07 - 98	All Eng. - 6.75 Oz. PAG-100; 25.00 Oz. R-134a	59002
<b>JUKE</b>		
17 - 14	4 Cyl 1.6L Eng. - 14.40 Oz. R-134a; 5.00 Oz. PAG-46	59007
13 - 11	4 Cyl 1.6L Eng. - 4.10 Oz. PAG-46; 14.00 Oz. R-134a	59007
<b>LEAF</b>		
18 - 14	All Eng. - Electric, 15.04 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
13	All Eng. - HYBRID, w/o Heat Pump; 15.04 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
12 - 11	All Eng. - HYBRID, 15.04 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>MAXIMA</b>		
18 - 16	6 Cyl 3.5L Eng. - 19.36 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.5L Eng. - 19.36 Oz. R-134a; 5.30 Oz. PAG-46	59007
13 - 09	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
08 - 04	All Eng. - 19.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
03 - 02	All Eng. - 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
01 - 97	All Eng. - 23.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
96	All Eng. - 8.50 Oz. PAG-46; 25.00 Oz. R-134a	59007
95	All Eng. - 29.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
94 - 93	All Eng. - 33.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
93 - 91	All Eng. - 33.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 6.75 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 86	All Eng. - 38.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MURANO</b>		
18	6 Cyl 3.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
17 - 15	6 Cyl 3.5L Eng. - 3.40 Oz. PAG-46; 21.12 Oz. R-134a	59007
16	4 Cyl 2.5L Eng. - Electric/Gas, 3.40 Oz. PAG-46; 21.12 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## NISSAN

Year	Description	Lubricant
<b>MURANO</b>		
14	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 21.12 Oz. R-134a	59007
13 - 11	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10	All Eng. - 21.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
09	All Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
08	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
07 - 03	All Eng. - 19.00 Oz. R-134a; 5.25 Oz. PAG-46	59007
<b>NV1500</b>		
13	6 Cyl 4.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	6 Cyl 4.0L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl 4.0L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>NV200</b>		
18 - 16	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 2.0L Eng. - 5.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>NV2500 / NV2500 HD</b>		
13	6 Cyl 4.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	6 Cyl 4.0L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13	8 Cyl 5.6L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	8 Cyl 5.6L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl 4.0L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	8 Cyl 5.6L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>NV3500 /NV3500 HD</b>		
13	6 Cyl 4.0L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	6 Cyl 4.0L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
13	8 Cyl 5.6L Eng. - w/ Rear AC; 42.00 Oz. R-134a; 7.80 Oz. PAG-46	59007
13	8 Cyl 5.6L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	6 Cyl 4.0L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12	8 Cyl 5.6L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>PATHFINDER</b>		
17 - 16	6 Cyl 3.5L Eng. - 29.92 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	6 Cyl 3.5L Eng. - 30.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 09	6 Cyl 4.0L Eng. - w/ Rear AC; 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
12 - 09	6 Cyl 4.0L Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
12 - 09	8 Cyl 5.6L Eng. - w/ Rear AC; 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
12 - 09	8 Cyl 5.6L Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
08	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08	All Eng. - w/o Rear AC; 6.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
07 - 06	All Eng. - w/ Rear AC; 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 06	All Eng. - w/o Rear AC; 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
05 - 02	All Eng. - 6.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
01 - 96	All Eng. - 23.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
95 - 93	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	6 Cyl 3.0L Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PICKUP</b>		
97 - 94	All Eng. - 30.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
<b>PULSAR NX / NX</b>		
93 - 91	All Eng. - 6.75 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 88	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 88	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87	All Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>QUEST</b>		
17 - 16	6 Cyl 3.5L Eng. - 31.68 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	6 Cyl 3.5L Eng. - 8.50 Oz. PAG-46; 31.68 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## NISSAN

Year	Description	Lubricant
<b>QUEST</b>		
13 - 11	6 Cyl 3.5L Eng. - 32.00 Oz. R-134a; 8.80 Oz. PAG-46	59007
09	6 Cyl 3.5L Eng. - 32.00 Oz. R-134a; 7.44 Oz. PAG-46	59007
08	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
07 - 06	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
05	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
02 - 01	All Eng. - w/ Rear AC; 54.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
02 - 94	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
00 - 94	All Eng. - w/ Rear AC; 52.00 Oz. R-134a; 11.00 Oz. PAG-100	59002
93	All Eng. - 10.00 Oz. Mineral Oil; 56.00 Oz. R-12, w/ Front and Rear AC	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>ROGUE</b>		
18 - 17	4 Cyl 2.0L Eng. - Electric/Gas, 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
18 - 17	4 Cyl 2.0L Eng. - ROGUE Sport, 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 17	4 Cyl 2.5L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	4 Cyl 2.5L Eng. - 17.60 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 09	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>SENTRA</b>		
18 - 16	4 Cyl 1.6L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
18 - 16	4 Cyl 1.8L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 1.8L Eng. - 17.60 Oz. R-134a; 3.00 Oz. PAG-46	59007
13	4 Cyl 1.8L Eng. - 5.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
12 - 09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
12 - 09	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 07	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 00	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 94	All Eng. - 6.75 Oz. PAG-100; 25.00 Oz. R-134a	59002
93 - 91	All Eng. - 6.75 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 33.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 5.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 35.00 Oz. R-12; 5.10 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>STANZA</b>		
92 - 91	All Eng. - 30.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 32.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 6.75 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - Sedan / Coupe, 6.75 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - Wagon, 5.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TITAN</b>		
15 - 14	8 Cyl 5.6L Eng. - 7.00 Oz. PAG-46; 24.96 Oz. R-134a	59007
13 - 09	8 Cyl 5.6L Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
08 - 04	All Eng. - 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>TITAN XD</b>		
18 - 16	8 Cyl 5.0L Eng. - Diesel, 24.96 Oz. R-134a; 5.10 Oz. PAG-46	59007
<b>TSURU</b>		
08 - 07	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 00	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
99 - 95	All Eng. - 6.75 Oz. PAG-100; 25.00 Oz. R-134a	59002
<b>VERSA</b>		
18 - 14	4 Cyl 1.6L Eng. - 4.10 Oz. PAG-46; 14.08 Oz. R-134a	59007
13 - 11	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
12	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## NISSAN

Year	Description	Lubricant
<b>VERSA</b>		
12 - 11	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
12 - 11	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
11	4 Cyl 1.6L Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10 - 07	All Eng. - 18.00 Oz. R-134a; 3.40 Oz. PAG-46	59007
10 - 07	All Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-100	59002
<b>X-TRAIL</b>		
14	4 Cyl 2.5L Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59002
<b>XTERRA</b>		
15 - 14	6 Cyl 4.0L Eng. - 6.00 Oz. PAG-46; 24.64 Oz. R-134a	59007
13 - 09	6 Cyl 4.0L Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
08 - 07	All Eng. - 6.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
06 - 00	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007

## OLDSMOBILE

Year	Description	Lubricant
<b>98 / 98 REGENCY</b>		
98 - 96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 29.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	All Eng. - 46.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 72	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
64 - 63	8 Cyl 6.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## ACHIEVA

98 - 95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 92	All Eng. - 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

## ALERO

04 - 02	All Eng. - 9.00 Oz. PAG-46; 22.00 Oz. R-134a	59003
01 - 99	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003

## AURORA

03	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
02 - 01	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
99 - 95	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003

## BRAVADA

04 - 02	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
04 - 02	All Eng. - w/o Rear AC; 29.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
01 - 99	All Eng. - w/ Denso Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
01 - 99	All Eng. - w/ OE Harrison Compressor; 31.00 Oz. R-134a; 8.50 Oz. PAG-150	59003
98 - 96	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
98 - 96	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	6 Cyl 4.3L Eng. - 40.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 8.00 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## CALAIS / CUTLASS CALAIS

91	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 87	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 7.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## OLDSMOBILE

Year	Description	Lubricant
<b>CALAIS / CUTLASS CALAIS</b>		
85	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CIERA / CUTLASS CIERA</b>		
96 - 94	4 Cyl 2.2L Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
96 - 94	6 Cyl 3.1L Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93 - 92	All Eng. - 38.00 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>CUTLASS / CUTLASS SUPREME</b>		
99 - 98	All Eng. - 28.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - 9.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 89	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88	All Eng. - 56.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 52.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 69	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CUTLASS CRUISER</b>		
94	6 Cyl 3.1L Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG 150	59003
90 - 87	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89	6 Cyl 3.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
89 - 87	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>DELTA 88 CUSTOM CRUISER / CUSTOM CRUISER</b>		
92 - 91	All Eng. - 6.00 Oz. Mineral Oil; 49.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 56.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>DELTA 88 SEDAN</b>		
99 - 98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 92	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 90	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 46.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 6.00 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 46.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67 - 65	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
66 - 65	8 Cyl 5.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FIRENZA</b>		
88 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 82	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>INTRIGUE</b>		
02 - 98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## OLDSMOBILE

Year	Description	Lubricant
<b>LSS</b>		
99 - 96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>OMEGA</b>		
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
74 - 73	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SILHOUETTE</b>		
04 - 01	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
04 - 01	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 98	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 46.00 Oz. R-134a	59003
00 - 98	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
97	6 Cyl 3.4L Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 46.00 Oz. R-134a	59003
97	6 Cyl 3.4L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
96	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
95 - 94	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
95 - 94	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	6 Cyl 3.1L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 56.00 Oz. R-134a	59007
93	All Eng. - w/ Denso Compressor; w/o Rear AC; 42.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 56.00 Oz. R-134a	59003
93	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 42.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
92	All Eng. - w/ Rear AC; 11.00 Oz. Mineral Oil; 67.00 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/o Rear AC; 8.00 Oz. Mineral Oil; 51.00 Oz. R-12	59000 <sup>(1)</sup>
90	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

## TORONADO

92 - 89	All Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	6 Cyl 3.8L Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	8 Cyl 5.0L Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	8 Cyl 5.7L Eng. - 38.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
72 - 71	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## PEUGEOT

Year	Description	Lubricant
<b>405</b>		
91 - 89	All Eng. - 6.75 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
<b>505</b>		
91 - 89	All Eng. - 6.75 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>

## PLYMOUTH

Year	Description	Lubricant
<b>ACCLAIM</b>		
95 - 94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>BREEZE</b>		
00	All Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99	All Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
98	All Eng. - 26.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97 - 96	All Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CARAVELLE</b>		
88 - 86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PLYMOUTH

Year	Description	Lubricant
<b>CARAVELLE</b>		
85	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>COLT</b>		
94	4 Cyl 1.5L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
94	4 Cyl 1.8L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
94	4 Cyl 2.4L Eng. - 28.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
93	4 Cyl 1.5L Eng. - 28.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
93	4 Cyl 1.8L Eng. - 28.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
92 - 85	4 Cyl 1.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
91 - 85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 89	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
90 - 89	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CONQUEST</b>		
86 - 85	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>GRAN FURY</b>		
89 - 80	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83 - 80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>HORIZON</b>		
90 - 89	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 34.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 84	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 81	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
79 - 78	4 Cyl 1.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LASER</b>		
94	All Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>NEON</b>		
01 - 00	All Eng. - 27.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
99	All Eng. - 28.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
98 - 97	All Eng. - 6.75 Oz. PAG-46; 25.00 Oz. R-134a	59007
96 - 95	All Eng. - 29.00 Oz. R-134a; 4.75 Oz. PAG-46	59007
<b>PROWLER</b>		
01	6 Cyl 3.5L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
00	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
99	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>RELIANT</b>		
89	4 Cyl 2.2L Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	4 Cyl 2.5L Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	All Eng. - 7.25 Oz. Mineral Oil; 37.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 81	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 81	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SAPPORO</b>		
83 - 81	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUNDANCE</b>		
94	4 Cyl 2.2L Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	4 Cyl 2.5L Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
94	6 Cyl 3.0L Eng. - 26.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
93 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PLYMOUTH

Year	Description	Lubricant
------	-------------	-----------

### SUNDANCE

90 - 89	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	All Eng. - 38.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>

### TRAILDUSTER

81	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
81	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### TURISMO

85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
83	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### VOLARE

80	6 Cyl 3.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
80	8 Cyl 5.9L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### VOYAGER / GRAND VOYAGER

00	All Eng. - w/ Rear AC; 46.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
00 - 96	All Eng. - w/o Rear AC; 5.00 Oz. PAG-46; 34.00 Oz. R-134a	59007
99 - 96	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
95 - 93	All Eng. - w/ Rear AC; 50.00 Oz. R-134a; 7.40 Oz. PAG-46	59007
95 - 93	All Eng. - w/o Rear AC; 36.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
93	4 Cyl 2.5L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	6 Cyl 3.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 44.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - w/o Rear AC; 32.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
91 - 89	All Eng. - w/ Rear AC; 13.00 Oz. Mineral Oil; 43.00 Oz. R-12; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.25 Oz. Mineral Oil; w/ Fixed Displacement Compressor	59000 <sup>(1)</sup>
89	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 8.75 Oz. Mineral Oil; w/ Variable Displacement Compressor	59000 <sup>(1)</sup>
88	All Eng. - w/o Rear AC; 44.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/o Rear AC; 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.2L Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.6L Eng. - 38.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	4 Cyl 2.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	4 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## PONTIAC

Year	Description	Lubricant
------	-------------	-----------

### 6000

91 - 88	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - Excl. STE, 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - STE, 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### AZTEK

05 - 01	All Eng. - 27.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
---------	--	-------

### BONNEVILLE

05 - 02	All Eng. - 35.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01 - 98	All Eng. - 32.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97 - 96	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 94	All Eng. - w/ Denso Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 94	All Eng. - w/ OE Harrison Compressor; 39.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93 - 91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 8.00 Oz. Mineral Oil; 38.50 Oz. R-12	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PONTIAC

Year	Description	Lubricant
<b>BONNEVILLE</b>		
88 - 87	All Eng. - 8.00 Oz. Mineral Oil; 53.00 Oz. R-12	59000 <sup>(1)</sup>
86	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
71 - 68	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CATALINA</b>		
73 - 70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FIERO</b>		
88 - 86	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 2.8L Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>FIREBIRD</b>		
02 - 98	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	6 Cyl 3.8L Eng. - w/ Denso Compressor; 26.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; 26.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
97 - 96	8 Cyl 5.7L Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
97 - 96	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	6 Cyl 3.8L Eng. - w/ Denso Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96	6 Cyl 3.8L Eng. - w/ OE Harrison Compressor; 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95 - 93	All Eng. - w/ Denso Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95 - 93	All Eng. - w/ OE Harrison Compressor; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	6 Cyl 3.4L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	8 Cyl 5.7L Eng. - w/ OE Harrison Compressor; w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 6.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 87	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86	All Eng. - 48.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85 - 83	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 83	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 71	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 67	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
67	8 Cyl 5.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>G3</b>		
10	4 Cyl 1.6L Eng. - 18.08 Oz. R-134a; 6.80 Oz. PAG-46	59007
09	4 Cyl 1.6L Eng. - 17.00 Oz. R-134a; 6.80 Oz. PAG-46	59007
<b>G5</b>		
10 - 07	All Eng. - 5.00 Oz. PAG-46; 14.50 Oz. R-134a	59007
<b>G6</b>		
10 - 09	4 Cyl 2.4L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
10 - 09	6 Cyl 3.5L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	6 Cyl 3.6L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PONTIAC

Year	Description	Lubricant
<b>G6</b>		
09	6 Cyl 3.9L Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 05	All Eng. - 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
<b>G8</b>		
09	8 Cyl 6.2L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09 - 08	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09 - 08	8 Cyl 6.0L Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>GRAND AM</b>		
05 - 02	4 Cyl 2.2L Eng. - 35.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05 - 02	6 Cyl 3.4L Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
01 - 99	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
98 - 95	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
94	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
93	All Eng. - 42.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 42.50 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.5L Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 3.0L Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>GRAND PRIX</b>		
08 - 06	6 Cyl 3.8L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 05	8 Cyl 5.3L Eng. - 19.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
05	6 Cyl 3.8L Eng. - 8.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
04	All Eng. - 8.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
03 - 98	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
97	All Eng. - 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96 - 94	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	6 Cyl 3.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
94	6 Cyl 3.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93 - 92	All Eng. - 9.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
91 - 88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87 - 86	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	6 Cyl 4.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
85	6 Cyl 3.8L Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 72	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>GTO</b>		
06 - 04	All Eng. - 29.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
<b>J2000</b>		
84 - 83	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>LEMANS</b>		
93 - 88	All Eng. - 8.00 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
73 - 70	8 Cyl 7.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 68	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
69 - 68	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>MONTANA</b>		
08 - 01	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
08 - 01	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 99	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 46.00 Oz. R-134a	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PONTIAC

Year	Description	Lubricant
<b>MONTANA</b>		
00 - 99	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
<b>PARISIENNE</b>		
86 - 85	All Eng. - 60.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>PHOENIX</b>		
84 - 82	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
84 - 82	6 Cyl 2.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SAFARI</b>		
89 - 87	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SOLSTICE</b>		
09	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
09	4 Cyl 2.4L Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
08	All Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
07 - 06	All Eng. - 26.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>SUNBIRD</b>		
94	All Eng. - 36.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
93 - 88	All Eng. - 8.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	4 Cyl 2.0L Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.8L Eng. - 44.00 Oz. R-12; 8.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>SUNFIRE</b>		
05 - 03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl 2.2L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	4 Cyl 2.2L Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
02	4 Cyl 2.4L Eng. - 21.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
01 - 95	All Eng. - 24.00 Oz. R-134a; 9.00 Oz. PAG-150	59003
<b>TEMPEST</b>		
70	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70 - 68	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
70 - 68	8 Cyl 6.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
68	8 Cyl 7.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>TORRENT</b>		
09	6 Cyl 3.4L Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
09	6 Cyl 3.6L Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
08 - 06	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>TRANS SPORT</b>		
98 - 97	All Eng. - w/ Rear AC; 11.00 Oz. PAG-150; 46.00 Oz. R-134a	59003
98 - 97	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
96	6 Cyl 3.4L Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
96	6 Cyl 3.4L Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
95	All Eng. - w/ Denso Compressor; w/ Rear AC; 11.00 Oz. PAG-46; 48.00 Oz. R-134a	59007
95	All Eng. - w/ Denso Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
95	All Eng. - w/ OE Harrison Compressor; w/ Rear AC; 11.00 Oz. PAG-150; 48.00 Oz. R-134a	59003
95	All Eng. - w/ OE Harrison Compressor; w/o Rear AC; 36.00 Oz. R-134a; 8.00 Oz. PAG-150	59003
94	6 Cyl 3.1L Eng. - 36.00 Oz. R-134a, Front	59003
94	6 Cyl 3.1L Eng. - 48.00 Oz. R-134a, Front and Rear	59007
94	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59003
94	6 Cyl 3.8L Eng. - w/ Denso Compressor; See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
93 - 92	6 Cyl 3.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93 - 90	6 Cyl 3.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>VENTURA</b>		
73 - 71	6 Cyl 4.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PONTIAC

Year	Description	Lubricant
------	-------------	-----------

### VENTURA

73 - 71	8 Cyl 5.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
73 - 71	8 Cyl 5.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### VIBE

10 - 09	4 Cyl 1.8L Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 4.50 Oz. PAG-46; 15.00 Oz. R-134a	59007
08 - 04	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
03	All Eng. - 23.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

## PORSCHE

Year	Description	Lubricant
------	-------------	-----------

### 911 SERIES

16	6 Cyl 4.0L Eng. - 32.00 Oz. R-134a; 5.60 Oz. PAG-46	59007
16 - 14	6 Cyl 3.4L Eng. - 32.00 Oz. R-134a; 5.60 Oz. PAG-46	59007
16 - 14	6 Cyl 3.8L Eng. - 32.00 Oz. R-134a; 5.60 Oz. PAG-46	59007
13 - 12	6 Cyl 3.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 08	6 Cyl 3.8L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12 - 08	6 Cyl 3.6L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07 - 05	All Eng. - AWD, 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 05	All Eng. - RWD, 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04 - 01	All Eng. - 31.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
00 - 99	All Eng. - 28.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
98 - 93	All Eng. - 29.50 Oz. R-134a; 4.75 Oz. PAG-46	59007
92 - 90	All Eng. - 33.00 Oz. R-12; 3.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 33.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	6 Cyl 3.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### 924 SERIES

88 - 87	All Eng. - 30.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
78	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

### 928 SERIES

95 - 93	All Eng. - 30.00 Oz. R-134a; 9.00 Oz. PAG-46	59007
91 - 89	All Eng. - 33.50 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	8 Cyl 5.0L Eng. - 33.50 Oz. R-12; 9.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

### 944 SERIES

91 - 89	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 2.5L Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>

### 968 SERIES

95 - 93	All Eng. - 30.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
92	All Eng. - 33.50 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>

### BOXSTER

16	6 Cyl 3.8L Eng. - 5.60 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
16 - 15	6 Cyl 2.7L Eng. - 5.60 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
16 - 15	6 Cyl 3.4L Eng. - 5.60 Oz. PAG-46; See Under Hood Decal for Refrigerant Capacity	59007
14	6 Cyl 2.7L Eng. - 31.20 Oz. R-134a; 5.60 Oz. PAG-46	59007
14	6 Cyl 3.4L Eng. - 31.20 Oz. R-134a; 5.60 Oz. PAG-46	59007
13	6 Cyl 2.7L Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
13 - 08	6 Cyl 3.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12 - 09	6 Cyl 2.9L Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
08	6 Cyl 2.7L Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
07 - 06	All Eng. - 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
05 - 97	All Eng. - 30.00 Oz. R-134a; 6.50 Oz. PAG-46	59007

### CAYENNE

17	6 Cyl 3.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
06	All Eng. - w/ Rear AC; 10.00 Oz. PAG-46; 37.00 Oz. R-134a	59007
06	All Eng. - w/o Rear AC; 25.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
05 - 04	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; 12.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## PORSCHE

Year	Description	Lubricant
<b>CAYENNE</b>		
05 - 04	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>CAYMAN</b>		
14	6 Cyl 2.7L Eng. - 31.20 Oz. R-134a; 5.60 Oz. PAG-46	59007
14	6 Cyl 3.4L Eng. - 31.20 Oz. R-134a; 5.60 Oz. PAG-46	59007
14	6 Cyl 3.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
12 - 09	6 Cyl 2.9L Eng. - 30.00 Oz. R-134a; 6.10-7.10 Oz. PAG-46	59007
12 - 08	6 Cyl 3.4L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 07	6 Cyl 2.7L Eng. - 30.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07 - 06	6 Cyl 3.4L Eng. - 30.00 Oz. R-134a; 6.60 Oz. PAG-46	59007
<b>MACAN</b>		
15	6 Cyl 3.0L Eng. - 3.70 Oz. PAG-46; 20.00 Oz. R-134a	59007
15	6 Cyl 3.6L Eng. - 3.70 Oz. PAG-46; 20.00 Oz. R-134a	59007
<b>PANAMERA</b>		
17	6 Cyl 2.9L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
16	6 Cyl 3.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
16 - 14	6 Cyl 3.0L Eng. - 4.70 Oz. PAG-46; 20.48 Oz. R-134a	59007
16 - 14	6 Cyl 3.6L Eng. - 4.70 Oz. PAG-46; 20.48 Oz. R-134a	59007
16 - 14	8 Cyl 4.8L Eng. - 4.70 Oz. PAG-46; 20.48 Oz. R-134a	59007
15	3.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
14	6 Cyl 3.0L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889

## RAM

Year	Description	Lubricant
<b>1500 SERIES</b>		
17 - 14	6 Cyl 3.0L Eng. - Diesel, 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	6 Cyl 3.0L Eng. - Diesel, 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	6 Cyl 3.6L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	6 Cyl 3.6L Eng. - 20.00 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	8 Cyl 5.7L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 5.7L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
13	6 Cyl 3.6L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	8 Cyl 4.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
12 - 11	6 Cyl 3.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>2500 SERIES</b>		
17 - 14	8 Cyl 5.7L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 5.7L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	8 Cyl 6.4L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 6.4L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	8 Cyl 6.7L Eng. - Diesel, 6.00 Oz. PAG-46; 22.08 Oz. R-134a	59007
13 - 12	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 10	8 Cyl 4.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 10	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
11	6 Cyl 6.7L Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
10	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>3500 SERIES</b>		
17 - 14	8 Cyl 5.7L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 5.7L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	8 Cyl 6.4L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 6.4L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007
17 - 14	8 Cyl 6.7L Eng. - Diesel, 22.08 Oz. R-134a; 6.00 Oz. PAG Oil	59007
13 - 12	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
11	6 Cyl 6.7L Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>4000 SERIES</b>		
17 - 14	8 Cyl 5.7L Eng. - 18.08 Oz. R-1234yf; 6.00 Oz. PAG Oil	59234
17 - 14	8 Cyl 5.7L Eng. - 19.04 Oz. R-134a; 6.00 Oz. PAG Oil	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## RAM

Year	Description	Lubricant
<b>4000 SERIES</b>		
13 - 12	6 Cyl 6.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 11	8 Cyl 5.7L Eng. - 6.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
11	6 Cyl 6.7L Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>C/V</b>		
15 - 14	6 Cyl 3.6L Eng. - 4.00 Oz. PAG-46; 28.96 Oz. R-134a; w/ Front AC	59007
15 - 14	6 Cyl 3.6L Eng. - 5.00 Oz. PAG-46; 40.48 Oz. R-134a; w/ Front and Rear AC	59007
13	6 Cyl 3.6L Eng. - w/o Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
13 - 12	6 Cyl 3.6L Eng. - w/ Rear AC; 40.48 Oz. R-134a; 5.07 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>DAKOTA</b>		
11	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	8 Cyl 4.7L Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
11	6 Cyl 3.7L Eng. - 20.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
<b>PROMASTER 1500</b>		
17 - 14	6 Cyl 3.0L Eng. - Diesel, 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
<b>PROMASTER 2500</b>		
17 - 14	6 Cyl 3.0L Eng. - Diesel, 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
<b>PROMASTER 3500</b>		
17 - 14	6 Cyl 3.0L Eng. - Diesel, 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - 6.00 Oz. PAG-46; 23.04 Oz. R-134a	59007
<b>PROMASTER CITY</b>		
17 - 15	4 Cyl 2.4L Eng. - 14.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

## RAM HD

Year	Description	Lubricant
<b>4500 SERIES</b>		
14	8 Cyl 6.4L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
13 - 11	6 Cyl 6.7L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>5500 SERIES</b>		
14	8 Cyl 6.4L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
13 - 11	6 Cyl 6.7L Eng. - 26.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>RENAULT</b>		
Year	Description	Lubricant
<b>ALLIANCE</b>		
87	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	4 Cyl 1.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 85	4 Cyl 1.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>ENCORE</b>		
86 - 85	4 Cyl 1.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
86 - 85	4 Cyl 1.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## SAAB

Year	Description	Lubricant
<b>9-2</b>		
06 - 05	4 Cyl 2.5L Eng. - 16.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
05	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
<b>9-3</b>		
11 - 10	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 4.56 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
09	6 Cyl 2.8L Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
08 - 03	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
02 - 99	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SAAB

Year	Description	Lubricant
<b>9-5</b>		
11	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - 24.00 Oz. R-134a; w/ Delphi Compressor; 5.00 Oz. PAG-46	59007
11 - 10	6 Cyl 2.8L Eng. - 24.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
11 - 10	6 Cyl 2.8L Eng. - 24.00 Oz. R-134a; w/ Delphi Compressor; 5.00 Oz. PAG-46	59007
09	4 Cyl 2.3L Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
08 - 04	All Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007
03 - 00	All Eng. - 31.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
99	All Eng. - 29.00 Oz. R-134a; 4.06 Oz. PAG-46	59007

<b>9-7</b>		
09	6 Cyl 4.2L Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	8 Cyl 5.3L Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
09	8 Cyl 6.0L Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
08 - 05	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<b>900 SERIES</b>		
98 - 97	All Eng. - 25.50 Oz. R-134a; 5.00 Oz. PAG-100	59002
98 - 97	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-46	59007
96 - 94	All Eng. - 25.50 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	4 Cyl 2.1L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 35.00 Oz. R-12; 5.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<b>9000 SERIES</b>		
98 - 94	4 Cyl 2.3L Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
97 - 95	6 Cyl 3.0L Eng. - 33.00 Oz. R-134a; 6.76 Oz. PAG-100	59002
93	4 Cyl 2.3L Eng. - 33.00 Oz. R-134a; 6.76 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/ Rear AC; 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - w/o Rear AC; 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
91 - 89	All Eng. - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.0L Eng. - 39.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>

## SATURN

Year	Description	Lubricant
<b>ASTRA</b>		
09 - 08	4 Cyl 1.8L Eng. - 14.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

<b>AURA</b>		
09	4 Cyl 2.4L Eng. - Electric/Gas, 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09	6 Cyl 3.6L Eng. - Gas, 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 07	All Eng. - Electric/Gas, 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08 - 07	All Eng. - Gas, 18.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

<b>ION</b>		
07 - 03	All Eng. - 5.00 Oz. PAG-46; 14.50 Oz. R-134a	59007

<b>L SERIES</b>		
05 - 01	All Eng. - For OE Equivalent Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
05 - 01	All Eng. - For Premium Replacement Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007

<b>LS SERIES</b>		
01	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
01 - 00	All Eng. - For OE Equivalent Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
00	All Eng. - For Premium Replacement Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007

<b>LW SERIES</b>		
03 - 00	All Eng. - For OE Equivalent Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
03 - 00	All Eng. - For Premium Replacement Design Compressor; 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007

<b>OUTLOOK</b>		
10 - 09	6 Cyl 3.6L Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007
08 - 07	All Eng. - 37.00 Oz. R-134a; 6.50 Oz. PAG-46	59007

<b>RELAY</b>		
07	All Eng. - w/ Rear AC; 32.00 Oz. R-134a; 8.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SATURN

Year	Description	Lubricant
<b>RELAY</b>		
07	All Eng. - w/o Rear AC; 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 05	All Eng. - w/ Rear AC; 35.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
06 - 05	All Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>SC SERIES</b>		
02 - 01	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
00	4 Cyl 1.9L Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
99 - 97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96 - 94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93 - 91	All Eng. - 6.75 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SKY</b>		
10	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
09	4 Cyl 2.0L Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
09	4 Cyl 2.4L Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
08 - 07	All Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>SL SERIES</b>		
02 - 97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96 - 94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93 - 91	All Eng. - 6.75 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>SW SERIES</b>		
01 - 97	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96 - 94	All Eng. - 24.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
93	All Eng. - 6.75 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>
<b>VUE</b>		
10	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 20.16 Oz. R-134a	59007
09	4 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
09 - 08	6 Cyl 3.5L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
09 - 08	6 Cyl 3.6L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
08	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
07	4 Cyl 2.2L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	4 Cyl 2.4L Eng. - 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07	6 Cyl 3.5L Eng. - w/ Rear AC; 8.00 Oz. PAG-46; 38.00 Oz. R-134a	59007
07	6 Cyl 3.5L Eng. - w/o Rear AC; 27.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06	6 Cyl 3.5L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
06 - 02	4 Cyl 2.2L Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
05	6 Cyl 3.5L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59002
04	6 Cyl 3.5L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
03 - 02	6 Cyl 3.0L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002

## SCION

Year	Description	Lubricant
<b>FR-S</b>		
14	4 Cyl 2.0L Eng. - 28.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
<b>IQ</b>		
14	4 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13	All Eng. - 3.40 Oz. PAG-46; 12.64 Oz. R-134a	59007
<b>TC</b>		
14	4 Cyl 2.5L Eng. - 14.00 Oz. R-134a; 3.90 Oz. PAG-46	59007
13 - 11	4 Cyl 2.5L Eng. - 15.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
10	4 Cyl 2.4L Eng. - 15.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	4 Cyl 2.4L Eng. - 17.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08 - 05	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
<b>XA</b>		
06 - 04	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
<b>XB</b>		
14 - 09	4 Cyl 2.4L Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
08	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SCION

Year	Description	Lubricant
<b>XB</b>		
06 - 04	All Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
<b>XD</b>		
14	4 Cyl 1.8L Eng. - 17.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
13 - 11	4 Cyl 1.8L Eng. - 14.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
10 - 08	4 Cyl 1.8L Eng. - 13.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

## SMART

Year	Description	Lubricant
<b>FORTWO</b>		
18 - 16	3 Cyl 0.9L Eng. - PAG-100; 19.20 Oz. R-134a	59002
18 - 14	All Eng. - Electric, See Under Hood Decal for Refrigerant and Lubricant Capacity	59234
15 - 14	3 Cyl 1.0L Eng. - PAG-100; 19.20 Oz. R-134a	59002
12 - 11	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
10 - 08	3 Cyl 1.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002

## STERLING

Year	Description	Lubricant
<b>827</b>		
91 - 90	All Eng. - 5.00 Oz. Mineral Oil; 36.00 Oz. R-12	59000 <sup>(1)</sup>

## SUBARU

Year	Description	Lubricant
<b>BAJA</b>		
06 - 03	All Eng. - 24.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
<b>BRAT</b>		
87 - 86	All Eng. - w/ Hitachi Compressor; 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 86	All Eng. - w/ Matsushita Compressor; 28.00 Oz. R-12; 5.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 1.8L Eng. - 28.00 Oz. R-12; 6.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>CROSSTREK</b>		
16	4 Cyl 2.0L Eng. - Electric/Gas, 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
<b>FORESTER</b>		
18 - 14	4 Cyl 2.0L Eng. - 16.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
18 - 14	4 Cyl 2.5L Eng. - 16.16 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
13 - 09	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
08	4 Cyl 2.5L Eng. - 23.00 Oz. R-134a; 3.50 Oz. PAG-100	59002
07 - 02	All Eng. - 23.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
01 - 98	All Eng. - 23.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
<b>IMPREZA</b>		
18 - 14	4 Cyl 2.0L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
13 - 10	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
13 - 09	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
08	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
07	4 Cyl 2.5L Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
06 - 02	All Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
01 - 97	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96 - 94	All Eng. - 24.00 Oz. R-134a; 4.00 Oz. PAG-100	59002
93	All Eng. - 6.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>

## IMPREZA OUTBACK

11 - 09	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
08	4 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 4.90 Oz. PAG-100	59002
07 - 02	4 Cyl 2.5L Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
01	4 Cyl 2.2L Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
00	All Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
99 - 97	4 Cyl 2.2L Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
96	4 Cyl 2.2L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
95	4 Cyl 1.8L Eng. - 24.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59003

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SUBARU

Year	Description	Lubricant
<b>JUSTY</b>		
94 - 87	3 Cyl 1.2L Eng. - 27.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>LEGACY</b>		
18 - 17	4 Cyl 2.5L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	6 Cyl 3.6L Eng. - 16.00 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16 - 15	4 Cyl 2.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
16 - 15	6 Cyl 3.6L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
14	4 Cyl 2.5L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
14	6 Cyl 3.6L Eng. - 16.80 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
13 - 10	6 Cyl 3.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
13 - 05	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
09 - 08	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59002
04 - 01	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
00 - 99	All Eng. - 23.00 Oz. R-134a; 5.50 Oz. PAG-100	59002
98 - 94	All Eng. - 26.50 Oz. R-134a; 5.50 Oz. PAG-100	59002
93 - 92	All Eng. - 24.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
93 - 90	All Eng. - 24.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ Calsonic Compressor	59000 <sup>(1)</sup>
91 - 90	All Eng. - 24.00 Oz. R-12; 5.00 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
<b>LEGACY OUTBACK</b>		
99	4 Cyl 2.5L Eng. - 23.00 Oz. R-134a; 5.30 Oz. PAG-46	59007
98 - 96	All Eng. - 24.00 Oz. R-134a; 5.25 Oz. PAG-100	59002
95	All Eng. - 24.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>LOYALE</b>		
94	4 Cyl 1.8L Eng. - 25.00 Oz. R-12; 4.72 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil, To 3/93	59000 <sup>(1)</sup>
93	All Eng. - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil, From 3/93	59000 <sup>(1)</sup>
92	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil, To 3/92	59000 <sup>(1)</sup>
92	All Eng. - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil, From 3/92	59000 <sup>(1)</sup>
91	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil, To 3/91	59000 <sup>(1)</sup>
91	All Eng. - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil, From 3/91	59000 <sup>(1)</sup>
90	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil, To 3/90	59000 <sup>(1)</sup>
90	All Eng. - 30.00 Oz. R-12; 4.75 Oz. Mineral Oil, From 3/90	59000 <sup>(1)</sup>
<b>OUTBACK</b>		
18 - 17	4 Cyl 2.5L Eng. - 15.20 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18 - 17	6 Cyl 3.6L Eng. - 15.20 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
16	6 Cyl 3.6L Eng. - 13.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59234
16 - 14	4 Cyl 2.5L Eng. - 13.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
15 - 14	6 Cyl 3.6L Eng. - 13.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59002
13 - 10	4 Cyl 2.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 10	6 Cyl 3.6L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 05	4 Cyl 2.5L Eng. - 14.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 05	6 Cyl 3.0L Eng. - 14.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
04 - 01	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-100	59002
00	4 Cyl 2.5L Eng. - 21.00 Oz. R-134a; 5.20 Oz. PAG-100	59002
<b>SEDAN, COUPE, WAGON</b>		
89	All Eng. - HL/GL/GL10, 30.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - HL/GL/GL10, w/ Hitachi Compressor; 28.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>SVX</b>		
97	6 Cyl 3.3L Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
96 - 93	All Eng. - 23.00 Oz. R-134a; 5.00 Oz. PAG-100	59002
92	All Eng. - 5.00 Oz. Mineral Oil; 23.00 Oz. R-12	59000 <sup>(1)</sup>
<b>TRIBECA</b>		
14	6 Cyl 3.6L Eng. - 20.96 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 08	6 Cyl 3.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
07 - 06	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SUBARU

Year	Description	Lubricant
<b>XT</b>		
91 - 89	All Eng. - 28.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## SUZUKI

Year	Description	Lubricant
<b>AERIO</b>		
07 - 02	All Eng. - 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>EQUATOR</b>		
12 - 10	4 Cyl 2.5L Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
12 - 10	6 Cyl 4.0L Eng. - 25.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
09	4 Cyl 2.5L Eng. - 16.54 Oz. R-134a; 6.10 Oz. PAG-46	59007
09	6 Cyl 4.0L Eng. - 16.54 Oz. R-134a; 6.10 Oz. PAG-46	59007
<b>ESTEEM</b>		
02 - 96	All Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
95	4 Cyl 1.6L Eng. - 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007

## FORENZA

08	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 04	All Eng. - 7.50 Oz. PAG-100; 22.00 Oz. R-134a	59002

## GRAND VITARA

13 - 11	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 4.70-5.40 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 20.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 09	6 Cyl 3.2L Eng. - 20.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
08 - 06	6 Cyl 2.7L Eng. - 21.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
05 - 04	6 Cyl 2.5L Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
03	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 12.00 Oz. PAG-46	59007
03 - 01	All Eng. - w/o Rear AC; 4.00 Oz. PAG-46; 17.00 Oz. R-134a	59007
02 - 01	All Eng. - w/ Rear AC; 28.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 99	All Eng. - 21.00 Oz. R-134a; 4.00 Oz. PAG-46	59007

## KIZASHI

13 - 12	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; 2.71-3.38 Oz. PAG-46	59007
11	4 Cyl 2.4L Eng. - 3.40 Oz. PAG-46; 15.00 Oz. R-134a	59007
10	4 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 4.40 Oz. PAG-46	59007

## RENO

08 - 05	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
---------	--	-------

## SAMURAI

95 - 94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
93 - 89	All Eng. - 5.00 Oz. Mineral Oil; 18.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	4 Cyl 1.3L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

## SIDEKICK

98 - 94	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
93 - 89	All Eng. - 5.00 Oz. Mineral Oil; 21.00 Oz. R-12	59000 <sup>(1)</sup>

## SWIFT

01 - 94	All Eng. - 18.00 Oz. R-134a; 3.50 Oz. PAG-46	59007
93 - 89	All Eng. - 5.00 Oz. Mineral Oil; 18.00 Oz. R-12	59000 <sup>(1)</sup>

## SX4

13 - 12	4 Cyl 2.0L Eng. - 16.00 Oz. R-134a; 2.71-3.38 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - 3.40 Oz. PAG-46; 15.00 Oz. R-134a	59007
10 - 08	4 Cyl 2.0L Eng. - 15.00 Oz. R-134a; 2.50 Oz. PAG-46	59007
07	4 Cyl 2.0L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

## VERONA

06 - 04	All Eng. - 8.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
---------	--	-------

## VITARA

04	6 Cyl 2.5L Eng. - 4.00 Oz. PAG-46; 14.00 Oz. R-134a	59007
03	4 Cyl 2.0L Eng. - 4.00 Oz. PAG-46; 14.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## SUZUKI

Year	Description	Lubricant
<b>VITARA</b>		
02 - 99	All Eng. - 4.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
<b>X-90</b>		
98 - 96	All Eng. - 21.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>XL-7</b>		
09 - 08	6 Cyl 3.6L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
09 - 07	6 Cyl 3.6L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
07	6 Cyl 3.6L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
06 - 03	6 Cyl 2.7L Eng. - w/ Rear AC; 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
06 - 03	6 Cyl 2.7L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
02	6 Cyl 2.7L Eng. - w/ Rear AC; 26.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
02	6 Cyl 2.7L Eng. - w/o Rear AC; 21.00 Oz. R-134a; 3.38 Oz. PAG-46	59007

## TOYOTA

Year	Description	Lubricant
<b>4RUNNER</b>		
18 - 14	6 Cyl 4.0L Eng. - 19.36 Oz. R-134a; 4.60 Oz. PAG-46	59007
13 - 12	6 Cyl 4.0L Eng. - 20.00 Oz. R-134a; 4.61 Oz. PAG-46	59007
11	6 Cyl 4.0L Eng. - 20.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
10	4 Cyl 2.7L Eng. - 19.50 Oz. R-134a; 6.80 Oz. PAG-46	59007
10	6 Cyl 4.0L Eng. - 19.50 Oz. R-134a; 6.80 Oz. PAG-46	59007
09	6 Cyl 4.0L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
09	8 Cyl 4.7L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 06	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
05 - 03	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
02 - 01	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
00 - 96	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
93 - 91	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 29.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	4 Cyl 2.4L Eng. - 20.80-27.20 Oz. R-12; 5.50-7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	6 Cyl 3.0L Eng. - 20.80-27.20 Oz. R-12; 5.50-7.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	4 Cyl 2.4L Eng. - 20.80-27.20 Oz. R-12; 5.20-6.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	4 Cyl 2.4L Eng. - 27.20 Oz. R-12; 5.20-6.20 Oz. Mineral Oil	59000 <sup>(1)</sup>

## AVALON

18 - 17	4 Cyl 2.5L Eng. - Electric/Gas, 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
18 - 17	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 14	4 Cyl 2.5L Eng. - Electric/Gas, 17.60 Oz. R-134a; 7.00 Oz. POE Oil	59889
16 - 14	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; 7.00 Oz. PAG-46	59007
13	4 Cyl 2.5L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
13 - 09	6 Cyl 3.5L Eng. - 5.00 Oz. PAG-46; 19.50 Oz. R-134a	59007
08 - 05	All Eng. - 4.50 Oz. PAG-46; 19.50 Oz. R-134a	59007
04 - 01	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 95	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

## C-HR

18	4 Cyl 2.0L Eng. - 14.40 Oz. R-1234yf; See Under Hood Decal for Lubricant Capacity	59234
18	4 Cyl 2.0L Eng. - PAG-46; 16.80 Oz. R-134a	59007

## CAMRY

17	4 Cyl 2.5L Eng. - 15.52 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	6 Cyl 3.5L Eng. - 15.52 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 14	4 Cyl 2.5L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
16 - 15	4 Cyl 2.5L Eng. - 7.00 Oz. PAG-46; 15.52 Oz. R-134a	59007
15	6 Cyl 3.5L Eng. - 7.00 Oz. PAG-46; 15.52 Oz. R-134a	59007
14	4 Cyl 2.5L Eng. - 18.72 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.5L Eng. - 7.00 Oz. PAG-46; 18.72 Oz. R-134a	59007
13	4 Cyl 2.5L Eng. - Gas, 19.00 Oz. R-134a; 3.88 Oz. PAG-46	59007
13	6 Cyl 3.5L Eng. - Gas, 19.00 Oz. R-134a; 3.88 Oz. PAG-46	59007
12	4 Cyl 2.5L Eng. - Gas, 19.00 Oz. R-134a; 6.10-6.90 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## TOYOTA

Year	Description	Lubricant
<b>CAMRY</b>		
12	6 Cyl 3.5L Eng. - Gas, 19.00 Oz. R-134a; 6.10-6.90 Oz. PAG-46	59007
11 - 10	4 Cyl 2.4L Eng. - HYBRID, 4.50 Oz. Hybrid Oil; 17.00-20.00 Oz. R-134a	59889
11 - 10	4 Cyl 2.5L Eng. - Gas, 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
11 - 09	6 Cyl 3.5L Eng. - Gas, 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09	4 Cyl 2.4L Eng. - Gas, 19.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
09 - 07	All Eng. - Electric/Gas, 4.50 Oz. Hybrid Oil; 17.00-20.00 Oz. R-134a	59889
08 - 07	All Eng. - Gas, 18.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06 - 04	All Eng. - 21.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
03 - 02	All Eng. - 19.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
01	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
00 - 97	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
96 - 94	All Eng. - 30.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
93	All Eng. - 33.50 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 7.25 Oz. Mineral Oil; 35.00 Oz. R-12	59000 <sup>(1)</sup>
91	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 7.50 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 87	All Eng. - 8.75 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84	4 Cyl 1.8L Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84	4 Cyl 2.0L Eng. - 27.20 Oz. R-12; 5.20-6.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
83	4 Cyl 2.0L Eng. - 27.20 Oz. R-12; 5.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>CELICA</b>		
05 - 00	All Eng. - 7.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
99 - 94	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 7.00 Oz. Mineral Oil; 25.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	All Eng. - 8.75 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
86	4 Cyl 2.0L Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
<b>COROLLA</b>		
18 - 14	4 Cyl 1.8L Eng. - 15.52 Oz. R-134a; 2.40 Oz. PAG-46	59007
13 - 11	4 Cyl 1.8L Eng. - 16.00 Oz. R-134a; 3.89 Oz. PAG-46	59007
13 - 11	4 Cyl 2.4L Eng. - 14.50 Oz. R-134a; 3.50 Oz. PAG-46	59007
10 - 09	4 Cyl 1.8L Eng. - 16.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
10 - 09	4 Cyl 2.4L Eng. - 16.00 Oz. R-134a; 3.51 Oz. PAG-46	59007
08	4 Cyl 1.8L Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
07 - 05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04 - 03	All Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
02 - 01	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 99	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
98 - 96	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 7.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
93	All Eng. - 7.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92 - 91	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 7.50 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
87	All Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 8.75 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
85	All Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84 - 83	4 Cyl 1.6L Eng. - 5.50 Oz. Mineral Oil; 27.20 Oz. R-12	59000 <sup>(1)</sup>
<b>CRESSIDA</b>		
92 - 89	All Eng. - 30.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	6 Cyl 2.8L Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
85	6 Cyl 2.8L Eng. - 8.75 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84	6 Cyl 2.8L Eng. - 27.20 Oz. R-12; 5.20 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## TOYOTA

Year	Description	Lubricant
<b>CRESSIDA</b>		
83	6 Cyl 2.8L Eng. - 27.20 Oz. R-12; 7.30-8.30 Oz. Mineral Oil	59000 <sup>(1)</sup>
82	6 Cyl 2.8L Eng. - 27.20 Oz. R-12; 5.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>ECHO</b>		
05 - 00	All Eng. - 16.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
<b>FJ CRUISER</b>		
18	6 Cyl 4.0L Eng. - 16.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
14	6 Cyl 4.0L Eng. - 4.50 Oz. PAG-46; 21.12 Oz. R-134a	59007
13 - 11	6 Cyl 4.0L Eng. - 4.50 Oz. PAG-46; 20.11-22.20 Oz. R-134a	59007
10 - 09	6 Cyl 4.0L Eng. - 4.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
08 - 07	6 Cyl 4.0L Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>HIGHLANDER</b>		
13 - 11	4 Cyl 2.7L Eng. - Gas, w/ Rear AC; 4.73 Oz. PAG-46; 25.40-28.90 Oz. R-134a	59007
13 - 11	4 Cyl 2.7L Eng. - Gas, w/o Rear AC; 19.40-22.90 Oz. R-134a; 3.38 Oz. PAG-46	59007
12 - 11	6 Cyl 3.5L Eng. - Gas, w/ Rear AC; 4.73 Oz. PAG-46; 25.40-28.90 Oz. R-134a	59007
12 - 11	6 Cyl 3.5L Eng. - Gas, w/o Rear AC; 19.40-22.90 Oz. R-134a; 3.38 Oz. PAG-46	59007
10 - 09	4 Cyl 2.7L Eng. - Gas, w/ Rear AC; 25.40-28.90 Oz. R-134a; 7.70 Oz. PAG-46	59007
10 - 09	4 Cyl 2.7L Eng. - Gas, w/o Rear AC; 4.50 Oz. PAG-46; 19.40-22.90 Oz. R-134a	59007
10 - 08	6 Cyl 3.3L Eng. - HYBRID, w/ Rear AC; 27.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
10 - 08	6 Cyl 3.3L Eng. - HYBRID, w/o Rear AC; 21.00 Oz. R-134a; 4.20-4.80 Oz. Hybrid Oil	59889
10 - 08	6 Cyl 3.5L Eng. - Gas, w/ Rear AC; 25.40-28.90 Oz. R-134a; 7.70 Oz. PAG-46	59007
10 - 08	6 Cyl 3.5L Eng. - Gas, w/o Rear AC; 4.50 Oz. PAG-46; 19.40-22.90 Oz. R-134a	59007
07	All Eng. - Electric/Gas, 19.40-22.90 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
07 - 06	All Eng. - Gas, 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
06	All Eng. - Electric/Gas, 19.40-22.90 Oz. R-134a; 4.80 Oz. Hybrid Oil	59889
05	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04 - 01	All Eng. - 24.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
<b>LAND CRUISER</b>		
13	8 Cyl 5.7L Eng. - 33.50 Oz. R-134a; 4.75 Oz. PAG-46, w/o Cool Box	59007
13	8 Cyl 5.7L Eng. - 35.00 Oz. R-134a; 4.75 Oz. PAG-46, w/ Cool Box	59007
11 - 10	8 Cyl 5.7L Eng. - 33.50 Oz. R-134a; 4.75 Oz. PAG-46, w/o Cool Box	59007
11 - 10	8 Cyl 5.7L Eng. - 35.00 Oz. R-134a; 4.75 Oz. PAG-46, w/ Cool Box	59007
09	8 Cyl 5.7L Eng. - 33.50 Oz. R-134a; 4.75 Oz. PAG-46, w/ Cool Box	59007
09	8 Cyl 5.7L Eng. - 35.00 Oz. R-134a; 4.75 Oz. PAG-46, w/o Cool Box	59007
08	8 Cyl 5.7L Eng. - 33.50 Oz. R-134a; 4.75 Oz. PAG-46, w/o Cool Box	59007
08	8 Cyl 5.7L Eng. - 35.00 Oz. R-134a; 4.75 Oz. PAG-46, w/ Cool Box	59007
07	8 Cyl 4.7L Eng. - 4.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
06 - 01	All Eng. - 24.00 Oz. R-134a; w/o Rear AC; See Under Hood Decal for Lubricant Capacity	59007
06 - 01	All Eng. - w/ Rear AC; 38.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
00 - 98	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
00 - 98	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
97 - 94	All Eng. - 30.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 32.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 33.50 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	6 Cyl 4.2L Eng. - 32.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
84 - 83	6 Cyl 4.2L Eng. - 27.20 Oz. R-12; 5.20-6.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>MATRIX</b>		
13 - 09	4 Cyl 1.8L Eng. - 4.50 Oz. PAG-46; 15.00 Oz. R-134a	59007
13 - 09	4 Cyl 2.4L Eng. - 4.50 Oz. PAG-46; 15.00 Oz. R-134a	59007
08 - 05	All Eng. - 18.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
04 - 03	All Eng. - 18.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>MR2</b>		
05 - 04	All Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
03 - 02	All Eng. - 15.17+/-1.06 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
01 - 00	All Eng. - 18.00 Oz. R-134a; 6.90 Oz. PAG-46	59007
95 - 94	All Eng. - 25.50 Oz. R-134a; 7.00 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## TOYOTA

Year	Description	Lubricant
<b>MR2</b>		
93	All Eng. - 30.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 32.00 Oz. R-12; 7.25 Oz. Mineral Oil	59000 <sup>(1)</sup>
89	All Eng. - 29.00 Oz. R-12; 8.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.6L Eng. - 25.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>MR2 SPYDER</b>		
88 - 85	4 Cyl 1.6L Eng. - 25.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
<b>PASEO</b>		
98 - 96	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
95 - 94	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
93	4 Cyl 1.5L Eng. - 26.45 Oz. R-134a; 5.45-8.70 Oz. Mineral Oil	59007
93	All Eng. - 7.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>PICKUP - STANDARD</b>		
95	All Eng. - 20.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 26.40 Oz. R-134a; 7.00 Oz. PAG-46	59000 <sup>(1)</sup>
94	All Eng. - 7.00 Oz. PAG-46; 26.50 Oz. R-134a	59007
93	All Eng. - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 29.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	All Eng. - 7.50 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
86 - 85	All Eng. - 7.50 Oz. Mineral Oil; 26.00 Oz. R-12	59000 <sup>(1)</sup>
84	4 Cyl 2.4L Eng. - 27.20 Oz. R-12; 5.20-6.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>PREVIA</b>		
97 - 94	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 41.00 Oz. R-134a	59007
97 - 94	All Eng. - w/o Rear AC; 32.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - w/ Rear AC; 42.50 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
93	All Eng. - w/o Rear AC; 33.50 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/ Rear AC; 44.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 91	All Eng. - w/o Rear AC; 35.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>Prius / Prius AWD-e</b>		
18 - 16	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 14	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
13 - 10	4 Cyl 1.8L Eng. - HYBRID, 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
09 - 04	4 Cyl 1.5L Eng. - HYBRID, 17.00 Oz. R-134a; 4.00 Oz. Hybrid Oil	59889
03 - 01	4 Cyl 1.5L Eng. - HYBRID, 19.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>Prius C</b>		
18 - 16	4 Cyl 1.5L Eng. - Electric/Gas, 16.48 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 14	4 Cyl 1.5L Eng. - Electric/Gas, 16.48 Oz. R-134a; 4.50 Oz. POE Oil	59889
<b>Prius Plug-In</b>		
15 - 14	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
13 - 12	4 Cyl 1.8L Eng. - HYBRID, 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
<b>Prius Prime</b>		
18 - 17	4 Cyl 1.8L Eng. - Electric/Gas, 16.48 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
18 - 17	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
<b>Prius V</b>		
18 - 16	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
17 - 16	4 Cyl 1.8L Eng. - Electric/Gas, 16.48 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59889
15 - 14	4 Cyl 1.8L Eng. - Electric/Gas, 16.48 Oz. R-134a; 4.50 Oz. POE Oil	59889
15 - 14	4 Cyl 1.8L Eng. - Electric/Gas, 16.64 Oz. R-134a; 4.50 Oz. Hybrid Oil	59889
13 - 12	4 Cyl 1.8L Eng. - HYBRID, 16.50 Oz. R-134a; 4.40-4.90 Oz. Hybrid Oil	59889
<b>RAV 4</b>		
18 - 16	4 Cyl 2.5L Eng. - Electric/Gas, 15.84 Oz. R-134a; 2.40 Oz. POE Oil	59889
14	All Eng. - Electric, 15.84 Oz. R-134a; 2.40 Oz. POE Oil	59889
13	4 Cyl 2.5L Eng. - 16.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
12	4 Cyl 2.5L Eng. - 16.00 Oz. R-134a; 4.35-4.86 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## TOYOTA

Year	Description	Lubricant
<b>RAV 4</b>		
12	6 Cyl 3.5L Eng. - 16.00 Oz. R-134a; 4.35-4.86 Oz. PAG-46	59007
11 - 09	4 Cyl 2.5L Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
11 - 09	6 Cyl 3.5L Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
08 - 07	All Eng. - 4.50 Oz. PAG-46; 16.00 Oz. R-134a	59007
06 - 04	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03 - 01	All Eng. - Gas, 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
00 - 98	All Eng. - Gas, 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
97 - 96	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
<b>SEQUOIA</b>		
18 - 14	8 Cyl 5.7L Eng. - 7.00 Oz. PAG-46; 31.36 Oz. R-134a	59007
13 - 11	8 Cyl 5.7L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
12 - 11	8 Cyl 4.6L Eng. - 7.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
10	8 Cyl 4.6L Eng. - 7.00 Oz. PAG-46; 30.00-32.50 Oz. R-134a	59007
10 - 08	8 Cyl 5.7L Eng. - 7.00 Oz. PAG-46; 30.00-32.50 Oz. R-134a	59007
09 - 08	8 Cyl 4.7L Eng. - 7.00 Oz. PAG-46; 30.00-32.50 Oz. R-134a	59007
07	8 Cyl 4.7L Eng. - 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06 - 01	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
06 - 01	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>SIENNA</b>		
18 - 17	6 Cyl 3.5L Eng. - 27.52 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16 - 14	6 Cyl 3.5L Eng. - 7.00 Oz. PAG-46; 27.52 Oz. R-134a	59007
13 - 12	6 Cyl 3.5L Eng. - 29.00 Oz. R-134a; 5.31 Oz. PAG-46	59007
12	4 Cyl 2.7L Eng. - 29.00 Oz. R-134a; 5.31 Oz. PAG-46	59007
11	4 Cyl 2.7L Eng. - 5.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
11	6 Cyl 3.5L Eng. - 5.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
10 - 07	All Eng. - 5.50 Oz. PAG-46; 28.50 Oz. R-134a	59007
06 - 05	All Eng. - 4.50 Oz. PAG-46; 28.50 Oz. R-134a	59007
04 - 01	All Eng. - 7.50 Oz. PAG-46; 38.00 Oz. R-134a	59007
00 - 98	All Eng. - 28.00 Oz. R-134a; 7.25 Oz. PAG-46	59007
<b>SOLARA</b>		
08	4 Cyl 2.4L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
08	6 Cyl 3.3L Eng. - 21.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
07 - 04	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
03 - 01	All Eng. - 28.00 Oz. R-134a; 7.50 Oz. PAG-46	59007
00 - 99	All Eng. - 28.00 Oz. R-134a; 8.00 Oz. PAG-46	59007
<b>SUPRA</b>		
98 - 96	All Eng. - 25.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
95 - 94	All Eng. - 7.00 Oz. PAG-46; 25.00 Oz. R-134a	59007
93	6 Cyl 3.0L Eng. - 25.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
92 - 89	All Eng. - 7.00 Oz. Mineral Oil; 27.00 Oz. R-12	59000 <sup>(1)</sup>
88	6 Cyl 3.0L Eng. - 20.80-27.20 Oz. R-12; 5.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
87	All Eng. - 26.00 Oz. R-12; 8.80 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	6 Cyl 3.0L Eng. - 20.80-27.20 Oz. R-12; 5.20 Oz. Mineral Oil	59000 <sup>(1)</sup>
80 - 79	6 Cyl 2.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>T100</b>		
98 - 93	All Eng. - 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
<b>TACOMA</b>		
18 - 16	4 Cyl 2.7L Eng. - 18.40 Oz. R-1234yf; 5.60 Oz. PAG Oil	59234
18 - 16	6 Cyl 3.5L Eng. - 18.40 Oz. R-1234yf; 5.60 Oz. PAG Oil	59234
18 - 16	6 Cyl 3.5L Eng. - 21.12 Oz. R-134a; 5.60 Oz. PAG-46	59007
18 - 14	4 Cyl 2.7L Eng. - 21.12 Oz. R-134a; 5.60 Oz. PAG-46	59007
15 - 14	6 Cyl 4.0L Eng. - 21.12 Oz. R-134a; 5.60 Oz. PAG-46	59007
13	4 Cyl 2.7L Eng. - 22.00 Oz. R-134a; 5.61 Oz. PAG-46	59007
13	6 Cyl 4.0L Eng. - 22.00 Oz. R-134a; 5.61 Oz. PAG-46	59007
12 - 09	4 Cyl 2.7L Eng. - 5.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
12 - 09	6 Cyl 4.0L Eng. - 5.50 Oz. PAG-46; 22.00 Oz. R-134a	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## TOYOTA

Year	Description	Lubricant
------	-------------	-----------

### TACOMA

08 - 05	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
04 - 01	All Eng. - 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
00 - 97	All Eng. - 21.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
96 - 95	All Eng. - 21.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

### TERCEL

98	All Eng. - 7.00 Oz. PAG-46; 16.00 Oz. R-134a	59007
97 - 95	All Eng. - 23.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
94	All Eng. - 24.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
93	All Eng. - 7.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
92	All Eng. - 28.00 Oz. R-12; 7.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 7.00 Oz. Mineral Oil; 26.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 27.00 Oz. R-12; 7.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 87	All Eng. - 27.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
86 - 85	All Eng. - 26.00 Oz. R-12; 8.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	4 Cyl 1.5L Eng. - 26.40 Oz. R-12; 4.10 Oz. Mineral Oil	59000 <sup>(1)</sup>

### TUNDRA

18 - 14	8 Cyl 4.6L Eng. - 4.50 Oz. PAG-46; 21.28 Oz. R-134a	59007
18 - 14	8 Cyl 5.7L Eng. - 4.50 Oz. PAG-46; 21.28 Oz. R-134a	59007
14	6 Cyl 4.0L Eng. - 4.50 Oz. PAG-46; 21.28 Oz. R-134a	59007
13 - 10	8 Cyl 4.6L Eng. - 4.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 08	6 Cyl 4.0L Eng. - 4.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
13 - 08	8 Cyl 5.7L Eng. - 4.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
09 - 08	8 Cyl 4.7L Eng. - 4.50 Oz. PAG-46; 22.00 Oz. R-134a	59007
07 - 06	All Eng. - 2 Door, 23.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
07 - 06	All Eng. - 4 Door, 21.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
05 - 04	All Eng. - 2 Door, 27.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
05 - 04	All Eng. - 4 Door, 20.00 Oz. R-134a; 7.75 Oz. PAG-46	59007
03 - 00	All Eng. - 22.00 Oz. R-134a; 7.75 Oz. PAG-46	59007

### VAN / VAN WAGON

89 - 86	All Eng. - w/ Rear AC; 6.00 Oz. Mineral Oil; 50.00 Oz. R-12	59000 <sup>(1)</sup>
89 - 86	All Eng. - w/o Rear AC; 5.00 Oz. Mineral Oil; 25.00 Oz. R-12	59000 <sup>(1)</sup>
85 - 84	4 Cyl 2.0L Eng. - 25.00 Oz. R-12; 5.20-6.20 Oz. Mineral Oil, w/ Front AC	59000 <sup>(1)</sup>
85 - 84	4 Cyl 2.0L Eng. - 5.20-6.20 Oz. Mineral Oil; 50.00 Oz. R-12, w/ Front AC	59000 <sup>(1)</sup>

### VENZA

16 - 10	4 Cyl 2.7L Eng. - 19.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 2.7L Eng. - 17.60 Oz. R-134a; 4.90 Oz. PAG-46	59007
15 - 14	6 Cyl 3.5L Eng. - 17.60 Oz. R-134a; 4.90 Oz. PAG-46	59007
14 - 10	6 Cyl 3.5L Eng. - 19.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	4 Cyl 2.7L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	6 Cyl 3.5L Eng. - 18.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007

### YARIS

18 - 14	4 Cyl 1.5L Eng. - 12.64 Oz. R-134a; 3.50 Oz. PAG-46	59007
13 - 10	4 Cyl 1.5L Eng. - 4.00 Oz. PAG-46; 14.00 Oz. R-134a	59007
09	4 Cyl 1.5L Eng. - 3.00 Oz. PAG-46; 13.00 Oz. R-134a	59007
08 - 07	All Eng. - 3.00 Oz. PAG-46; 13.00 Oz. R-134a	59007

## VOLKSWAGEN

Year	Description	Lubricant
------	-------------	-----------

### BETLE

13	4 Cyl 2.0L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46	59007
13	4 Cyl 2.0L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13	5 Cyl 2.5L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 2.70-3.30 Oz. PAG-46	59007
13	5 Cyl 2.5L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
12	4 Cyl 2.0L Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
12	5 Cyl 2.5L Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
10	5 Cyl 2.5L Eng. - 27.00 Oz. R-134a; 4.60 Oz. PAG-46	59007
09	5 Cyl 2.5L Eng. - 25.00 Oz. R-134a; 4.60 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLKSWAGEN

Year	Description	Lubricant
<b>BEETLE</b>		
08 - 01	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00 - 98	All Eng. - 24.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>CABRIO</b>		
02 - 01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00 - 95	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
<b>CABRIOLET</b>		
93 - 86	All Eng. - 32.00 Oz. R-12; 4.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>CORRADO</b>		
94 - 93	All Eng. - 35.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93 - 90	All Eng. - 30.00 Oz. R-12; 5.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>EOS</b>		
16	4 Cyl 2.0L Eng. - 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 10	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.50-4.50 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - w/ Denso Compressor; 19.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
08 - 07	All Eng. - 4.50 Oz. PAG-46; 19.50 Oz. R-134a	59007
<b>EUROVAN</b>		
03 - 02	All Eng. - w/o Rear AC; 4.50 Oz. PAG-100; 40.00 Oz. R-134a	59002
03 - 99	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
01 - 99	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 4.50 Oz. PAG-100	59002
97 - 93	All Eng. - w/ Rear AC; 48.00 Oz. R-134a; 8.00 Oz. PAG-100	59002
97 - 93	All Eng. - w/o Rear AC; 33.50 Oz. R-134a; 4.50 Oz. PAG-100	59002
<b>FOX</b>		
93 - 89	All Eng. - 38.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	All Eng. - 40.00 Oz. R-12; See Under Hood Decal for Lubricant Capacity	59000 <sup>(1)</sup>
87	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>GOLF / GTI</b>		
17	4 Cyl 1.8L Eng. - Golf Alltrack, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	4 Cyl 1.8L Eng. - Golf Sportwagen, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 15	4 Cyl 1.8L Eng. - GOLF, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 15	4 Cyl 2.0L Eng. - GOLF R, 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - Diesel, GOLF, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 12	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13 - 12	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - w/ Delphi Compressor; 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 3.20 Oz. PAG-46	59007
13 - 10	4 Cyl 2.0L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
13 - 10	5 Cyl 2.5L Eng. - w/ Delphi Compressor; 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
12 - 10	5 Cyl 2.5L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 3.20 Oz. PAG-46	59007
12 - 10	5 Cyl 2.5L Eng. - w/ Denso Compressor; 18.00 Oz. R-134a; 4.90 Oz. PAG-46	59007
11	4 Cyl 2.0L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
11	5 Cyl 2.5L Eng. - 18.00 Oz. R-134a; 3.70 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08 - 07	4 Cyl 2.0L Eng. - 26.00 Oz. R-134a; 3.71 Oz. PAG-46	59007
06 - 05	All Eng. - 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04 - 01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00 - 99	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
98 - 93	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	All Eng. - 28.00 Oz. R-12; 4.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
92 - 89	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
87 - 86	4 Cyl 1.8L Eng. - 4.50 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 1.8L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLKSWAGEN

Year	Description	Lubricant
<b>JETTA</b>		
17 - 16	4 Cyl 1.4L Eng. - 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	4 Cyl 1.8L Eng. - 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 16	4 Cyl 2.0L Eng. - 18.40 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	4 Cyl 1.4L Eng. - Electric/Gas, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
15	4 Cyl 1.4L Eng. - Electric/Gas, 18.40 Oz. R-134a; 2.50 Oz. PAG-46	59007
15	4 Cyl 1.8L Eng. - 18.40 Oz. R-134a; 2.50 Oz. PAG-46	59007
15	4 Cyl 2.0L Eng. - 18.40 Oz. R-134a; 2.50 Oz. PAG-46	59007
14	4 Cyl 1.4L Eng. - Electric/Gas, 3.70 Oz. PAG-46; 18.40 Oz. R-134a	59007
14	4 Cyl 1.8L Eng. - 3.70 Oz. PAG-46; 18.40 Oz. R-134a	59007
14	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 18.40 Oz. R-134a	59007
14	5 Cyl 2.5L Eng. - 3.70 Oz. PAG-46; 18.40 Oz. R-134a	59007
13 - 10	4 Cyl 2.0L Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
13 - 10	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 3.40-4.00 Oz. PAG-46	59007
09	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
09	5 Cyl 2.5L Eng. - 3.70 Oz. PAG-46; 19.00 Oz. R-134a	59007
08 - 06	All Eng. - 4.00 Oz. PAG-46; 19.50 Oz. R-134a	59007
05	All Eng. - Sedan, 4.00 Oz. PAG-46; 19.50 Oz. R-134a	59007
05	All Eng. - Wagon, 28.00 Oz. R-134a; 5.00 Oz. PAG-46	59007
04 - 01	All Eng. - 27.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
00 - 99	All Eng. - 26.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
98 - 93	All Eng. - 28.00 Oz. R-134a; 4.00 Oz. PAG-46	59007
93	4 Cyl 2.0L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 89	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.6L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
88 - 85	4 Cyl 1.8L Eng. - 4.50 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
<b>PASSAT / CC</b>		
17 - 16	4 Cyl 2.0L Eng. - CC, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17 - 14	4 Cyl 1.8L Eng. - PASSAT, 3.70 Oz. PAG-46; 20.32 Oz. R-134a	59007
17 - 14	6 Cyl 3.6L Eng. - PASSAT, 3.70 Oz. PAG-46; 20.32 Oz. R-134a	59007
16	6 Cyl 3.6L Eng. - CC, 19.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15 - 14	4 Cyl 2.0L Eng. - Diesel, PASSAT, 3.70 Oz. PAG-46; 20.32 Oz. R-134a	59007
14	5 Cyl 2.5L Eng. - PASSAT, 3.70 Oz. PAG-46; 20.32 Oz. R-134a	59007
13 - 12	5 Cyl 2.5L Eng. - 20.00 Oz. R-134a; 3.40-4.10 Oz. PAG-46	59007
13 - 09	4 Cyl 2.0L Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
13 - 09	6 Cyl 3.6L Eng. - 20.00 Oz. R-134a; 3.40-4.50 Oz. PAG-46	59007
08 - 05	All Eng. - 5.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
04	All Eng. - 20.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
03 - 98	All Eng. - 23.00 Oz. R-134a; 8.50 Oz. PAG-46	59007
97 - 95	All Eng. - 4.00 Oz. PAG-46; 33.00 Oz. R-134a	59007
94 - 93	All Eng. - 4.00 Oz. PAG-46; 40.00 Oz. R-134a	59007
93	6 Cyl 2.8L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
92 - 90	All Eng. - 4.00 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
<b>PHAETON</b>		
06 - 04	All Eng. - 7.00 Oz. PAG-46; 22.00 Oz. R-134a	59007
<b>R32</b>		
08	6 Cyl 3.2L Eng. - 18.00 Oz. R-134a; 6.30 Oz. PAG-46	59007
<b>RABBIT</b>		
09	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 6.10 Oz. PAG-46	59007
08 - 06	All Eng. - 23.00 Oz. R-134a; 4.50 Oz. PAG-46	59007
<b>ROUTAN</b>		
12 - 11	6 Cyl 3.6L Eng. - w/ Rear AC; 40.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
12 - 11	6 Cyl 3.6L Eng. - w/o Rear AC; 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
10 - 09	All Eng. - w/ Rear AC; 40.00 Oz. R-134a; 5.10 Oz. PAG-46	59007
10 - 09	All Eng. - w/o Rear AC; 28.00 Oz. R-134a; 4.10 Oz. PAG-46	59007
<b>SCIROCCO</b>		
89	All Eng. - 4.75 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLKSWAGEN

Year	Description	Lubricant
<b>SCIROCCO</b>		
88 - 85	4 Cyl 1.8L Eng. - 4.75 Oz. Mineral Oil; 40.00 Oz. R-12	59000 <sup>(1)</sup>
<b>Tiguan</b>		
17 - 16	4 Cyl 2.0L Eng. - 23.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 09	4 Cyl 2.0L Eng. - 3.70 Oz. PAG-46; 23.00 Oz. R-134a	59007
13 - 09	4 Cyl 2.0L Eng. - w/ Denso Compressor; 23.00 Oz. R-134a; 4.70 Oz. PAG-46	59007
<b>Tiguan Limited</b>		
17	4 Cyl 2.0L Eng. - 23.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
<b>TOUAREG</b>		
15 - 14	6 Cyl 3.0L Eng. - Electric/Gas, 30.40 Oz. R-134a; 4.70 Oz. PAG-46; w/ one evaporator	59007
13	6 Cyl 3.0L Eng. - w/ Rear AC; 39.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46	59007
13	6 Cyl 3.0L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - w/ Rear AC; 39.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46	59007
13	6 Cyl 3.6L Eng. - w/o Rear AC; 32.00 Oz. R-134a; 4.40-5.00 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - w/ Rear AC; 39.00 Oz. R-134a; 4.60 Oz. To 5.30 Oz. PAG-46	59007
12	6 Cyl 3.6L Eng. - w/o Rear AC; 27.00 Oz. R-134a; 4.60 Oz. To 5.30 Oz. PAG-46	59007
12 - 11	6 Cyl 3.0L Eng. - HYBRID, See Under Hood Decal for Refrigerant and Lubricant Capacity	59889
12 - 11	6 Cyl 3.0L Eng. - w/ Rear AC; 39.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
12 - 11	6 Cyl 3.0L Eng. - w/o Rear AC; 30.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
11	6 Cyl 3.6L Eng. - w/ Rear AC; 4.70 Oz. PAG-46; 37.00 Oz. R-134a	59007
11 - 10	6 Cyl 3.6L Eng. - w/o Rear AC; 4.90 Oz. PAG-46; 25.00 Oz. R-134a	59007
10	6 Cyl 3.6L Eng. - w/ Rear AC; 37.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
10 - 09	6 Cyl 3.0L Eng. - w/ Denso Compressor; w/ Rear AC; 37.00-38.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
10 - 09	6 Cyl 3.0L Eng. - w/ Denso Compressor; w/o Rear AC; 24-26.00 Oz. R-134a; 4.73 Oz. PAG-46	59007
09	6 Cyl 3.6L Eng. - 4.90 Oz. PAG-46; 25.00 Oz. R-134a, Dual Zone	59007
09	6 Cyl 3.6L Eng. - 8.50 Oz. PAG-46; 37.00 Oz. R-134a, w/ 4 Zone	59007
09	8 Cyl 4.2L Eng. - 4.90 Oz. PAG-46; 25.00 Oz. R-134a, Dual Zone	59007
09	8 Cyl 4.2L Eng. - 8.50 Oz. PAG-46; 37.00 Oz. R-134a, w/ 4 Zone	59007
08 - 04	All Eng. - w/ Rear AC; 39.00 Oz. R-134a; 10.00 Oz. PAG-46	59007
08 - 04	All Eng. - w/o Rear AC; 26.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>VANAGON</b>		
91 - 89	All Eng. - 8.00 Oz. Mineral Oil; 51.00 Oz. R-12	59000 <sup>(1)</sup>
88 - 86	4 Cyl 2.1L Eng. - 8.00 Oz. Mineral Oil; 51.00 Oz. R-12	59000 <sup>(1)</sup>
85	4 Cyl 1.9L Eng. - 8.00 Oz. Mineral Oil; 51.00 Oz. R-12	59000 <sup>(1)</sup>

## VOLVO

Year	Description	Lubricant
<b>240 SERIES</b>		
93	All Eng. - 7.50 Oz. PAG-46; 26.50 Oz. R-134a	59007
92 - 91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 87	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	All Eng. - 10.00 Oz. Mineral Oil; 46.00 Oz. R-12	59000 <sup>(1)</sup>
86	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
85	4 Cyl 2.1L Eng. - 38.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.3L Eng. - 10.00 Oz. Mineral Oil; 46.00 Oz. R-12	59000 <sup>(1)</sup>
<b>260 SERIES</b>		
79 - 76	6 Cyl 2.7L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>740 SERIES</b>		
92	All Eng. - 4.50 Oz. Mineral Oil; 40.00 Oz. R-12; w/ SD5 Compressor	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 10.00 Oz. Mineral Oil; 41.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD5 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD7 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLVO

Year	Description	Lubricant
<b>740 SERIES</b>		
90 - 89	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
88 - 87	All Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
86	4 Cyl 2.3L Eng. - 10.00 Oz. Mineral Oil; 46.00 Oz. R-12	59000 <sup>(1)</sup>
86	4 Cyl 2.3L Eng. - 46.00 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
86 - 85	6 Cyl 2.4L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	4 Cyl 2.3L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>760 SERIES</b>		
90 - 89	All Eng. - 10.00 Oz. Mineral Oil; 41.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD5 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD7 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
88	4 Cyl 2.3L Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
88 - 85	6 Cyl 2.8L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
87 - 85	4 Cyl 2.3L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
85	6 Cyl 2.4L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
84	6 Cyl 2.4L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
<b>780 SERIES</b>		
91	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 10.00 Oz. Mineral Oil; 41.50 Oz. R-12	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD5 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 4.50 Oz. Mineral Oil; 41.50 Oz. R-12; w/ SD7 Compressor	59000 <sup>(1)</sup>
90 - 89	All Eng. - 41.50 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
90 - 89	All Eng. - 41.50 Oz. R-12; 6.75 Oz. Mineral Oil; w/ Diesel Kiki Compressor	59000 <sup>(1)</sup>
88 - 87	6 Cyl 2.8L Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>850 SERIES</b>		
97 - 96	All Eng. - 32.00 Oz. R-134a; 5.50 Oz. PAG-46	59007
95 - 93	All Eng. - 36.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
<b>940 SERIES</b>		
95	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
95 - 93	All Eng. - 33.50 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
95 - 93	All Eng. - 33.50 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
94	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-46	59007
93	4 Cyl 2.3L Eng. - w/ R12; See Under Hood Decal for Refrigerant and Lubricant Capacity	59000 <sup>(1)</sup>
93	All Eng. - 33.50 Oz. R-134a; 7.50 Oz. PAG-100	59002
92	All Eng. - 4.50 Oz. Mineral Oil; 40.00 Oz. R-12; w/ SD5 Compressor	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 40.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
91	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
<b>960 SERIES</b>		
97 - 96	All Eng. - 32.00 Oz. R-134a; 8.50 Oz. PAG-100; w/ SD7 Compressor	59002
95 - 93	All Eng. - 32.00 Oz. R-134a; 4.50 Oz. PAG-100; w/ SD5 Compressor	59002
95 - 93	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
95 - 93	All Eng. - 32.00 Oz. R-134a; 8.00 Oz. PAG-100; w/ SD7 Compressor	59002
92	All Eng. - 39.00 Oz. R-12; 4.50 Oz. Mineral Oil; w/ SD5 Compressor	59000 <sup>(1)</sup>
92	All Eng. - 39.00 Oz. R-12; 6.75 Oz. Mineral Oil	59000 <sup>(1)</sup>
92	All Eng. - 39.00 Oz. R-12; 8.00 Oz. Mineral Oil; w/ SD7 Compressor	59000 <sup>(1)</sup>
<b>C30</b>		
13 - 08	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
12 - 11	4 Cyl 1.6L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
10	5 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.



# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLVO

Year	Description	Lubricant
<b>C70</b>		
13 - 08	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
07 - 06	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
04 - 02	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
01 - 98	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
<b>S40</b>		
11 - 09	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 6.09 Oz. PAG-46	59007
10 - 07	5 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
08 - 07	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
06 - 05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-100	59002
04 - 01	All Eng. - 30.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
00	All Eng. - 31.00 Oz. R-134a; 6.00 Oz. PAG-100	59002
<b>S60</b>		
19	4 Cyl 2.0L Eng. - 25.00 Oz. R-134a; 4.40 Oz. PAG-46	59007
18 - 16	4 Cyl 2.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	5 Cyl 2.5L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	5 Cyl 2.5L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14 - 12	5 Cyl 2.5L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14 - 12	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
11	6 Cyl 3.0L Eng. - 35.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09	5 Cyl 2.5L Eng. - 27.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
09 - 07	5 Cyl 2.4L Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
08 - 07	5 Cyl 2.5L Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
06 - 01	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>S70</b>		
00 - 98	All Eng. - 29.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
<b>S80</b>		
16	4 Cyl 2.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.2L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13	4 Cyl 2.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 08	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 08	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
12	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
10	8 Cyl 4.4L Eng. - 3.70 Oz. PAG-46; 28.00 Oz. R-134a	59007
09 - 08	8 Cyl 4.4L Eng. - 2.40 Oz. PAG-46; 25.00 Oz. R-134a	59007
07	6 Cyl 3.2L Eng. - 21.86 Oz. R-134a; 6.08 Oz. PAG-46	59007
07	8 Cyl 4.4L Eng. - 24.69 Oz. R-134a; 6.08 Oz. PAG-46	59007
06 - 00	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
99	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>S90</b>		
19 - 18	4 Cyl 2.0L Eng. - 23.00 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
98	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
98 - 97	6 Cyl 2.9L Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
97	6 Cyl 2.9L Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
<b>V40</b>		
04 - 00	All Eng. - 32.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>V50</b>		
11 - 08	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
10 - 08	5 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 6.76 Oz. PAG-46	59007
07	5 Cyl 2.4L Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007

# Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

## VOLVO

Year	Description	Lubricant
<b>V50</b>		
07	5 Cyl 2.5L Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
06 - 05	All Eng. - 19.00 Oz. R-134a; 7.00 Oz. PAG-46	59007
<b>V70</b>		
10 - 08	6 Cyl 3.2L Eng. - 3.70 Oz. PAG-46; 22.00 Oz. R-134a	59007
07	5 Cyl 2.4L Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
07	5 Cyl 2.5L Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
06 - 98	All Eng. - 35.00 Oz. R-134a; 6.75 Oz. PAG-46	59007
<b>V90</b>		
17	4 Cyl 2.0L Eng. - 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
17	4 Cyl 2.0L Eng. - V90 Cross Country, 24.64 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
98	All Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
97	6 Cyl 2.9L Eng. - 32.00 Oz. R-134a; 6.75 Oz. PAG-100	59002
<b>XC60</b>		
17 - 16	4 Cyl 2.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	5 Cyl 2.5L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	4 Cyl 2.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	5 Cyl 2.5L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.2L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.2L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 10	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 10	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
12	4 Cyl 2.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
<b>XC70</b>		
16	4 Cyl 2.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
16	4 Cyl 2.5L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.0L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
15	6 Cyl 3.2L Eng. - 25.60 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.0L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
14	6 Cyl 3.2L Eng. - 27.20 Oz. R-134a; See Under Hood Decal for Lubricant Capacity	59007
13 - 09	6 Cyl 3.0L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
13 - 09	6 Cyl 3.2L Eng. - See Under Hood Decal for Refrigerant and Lubricant Capacity	59007
08	6 Cyl 3.2L Eng. - 3.70 Oz. PAG-46; 45.00 Oz. R-134a	59007
07	5 Cyl 2.5L Eng. - 46.00 Oz. R-134a; 6.08 Oz. PAG-46	59007
06 - 03	All Eng. - 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007
<b>XC90</b>		
14	6 Cyl 3.2L Eng. - 35.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
13	6 Cyl 3.2L Eng. - w/ Rear AC; 35.00 Oz. R-134a; 6.70 Oz. PAG-46	59007
13	6 Cyl 3.2L Eng. - w/o Rear AC; 6.70 Oz. PAG-46; 25.00 Oz. R-134a	59007
12 - 11	6 Cyl 3.2L Eng. - 22.00 Oz. R-134a; 6.08 Oz. PAG-46, w/ Front AC	59007
12 - 11	6 Cyl 3.2L Eng. - 35.00 Oz. R-134a; 6.08 Oz. PAG-46, w/ Dual AC	59007
11	8 Cyl 4.4L Eng. - 24.00 Oz. R-134a; 6.08 Oz. PAG-46, w/o Dual AC	59007
11	8 Cyl 4.4L Eng. - 36.00 Oz. R-134a; 6.08 Oz. PAG-46, w/ Dual AC	59007
10 - 09	6 Cyl 3.2L Eng. - 25.00 Oz. R-134a; 4.40 Oz. PAG-46, w/ Front AC	59007
10 - 09	6 Cyl 3.2L Eng. - 35.00 Oz. R-134a; 4.40 Oz. PAG-46, w/ Dual AC	59007
10 - 09	8 Cyl 4.4L Eng. - 25.00 Oz. R-134a; 4.40 Oz. PAG-46, w/o Dual AC	59007
10 - 09	8 Cyl 4.4L Eng. - 37.00 Oz. R-134a; 4.40 Oz. PAG-46, w/ Dual AC	59007
08	6 Cyl 3.2L Eng. - 35.00 Oz. R-134a; 6.10 Oz. PAG-46, w/ Front AC	59007
08	6 Cyl 3.2L Eng. - 46.00 Oz. R-134a; 6.10 Oz. PAG-46, w/ Dual AC	59007
08	8 Cyl 4.4L Eng. - 35.00 Oz. R-134a; 6.10 Oz. PAG-46, w/o Dual AC	59007
08	8 Cyl 4.4L Eng. - 46.00 Oz. R-134a; 6.10 Oz. PAG-46, w/ Dual AC	59007
07	6 Cyl 3.2L Eng. - 32.20 Oz. R-134a; 6.08 Oz. PAG-46, w/ Front AC	59007
07	6 Cyl 3.2L Eng. - 32.90 Oz. R-134a; 6.08 Oz. PAG-46, w/ Dual AC	59007
07	8 Cyl 4.4L Eng. - 32.20 Oz. R-134a; 6.08 Oz. PAG-46	59007
06 - 03	All Eng. - w/ Rear AC; 7.00 Oz. PAG-46; 46.00 Oz. R-134a	59007

## Compressor / System Refrigerant & Lubricant Specs

All oil specifications assume that the A/C system has been properly cleaned, and a new Accumulator/Filter Drier has been installed. Specs are for total system capacities. Always refer to the under-hood decal as the primary source for refrigerant and lubricant information

### VOLVO

Year	Description	Lubricant
<b>XC90</b>		
06 - 03	All Eng. - w/o Rear AC; 35.00 Oz. R-134a; 6.00 Oz. PAG-46	59007

### YUGO

Year	Description	Lubricant
<b>GV</b>		
91 - 89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>
<b>GVX</b>		
89	All Eng. - 32.00 Oz. R-12; 6.00 Oz. Mineral Oil	59000 <sup>(1)</sup>

<sup>(1)</sup>When retrofitting to R134a PAG Oil must be used.